Shovels					
Spades	117 118	SDS PLUS drill bits Drill bit sets for concrete	151 152	15 LIGHTING	217
Forks	118	Drill bit sets for stone	153	LED headlamps	218
Rake	119	Point chisels	153	LED workshop lamps	219
Garden hoe	119	Listers	154	LED flashlights	222
Garden spade	119	Chisels	154	LED spotlights	223
Scissors	120	Fret saws	155	Spotlight cover	226
Pruning scissors	121	Drill bits for wood	156		
Foldable handsaw	122	Metal discs Stone discs	158 160	16 CHEMICAL PREPARATIONS	5 227
10 HAMMEDS AND AVES	123	Diamond discs	160		
10 HAMMERS AND AXES	123	"Planer" wood saw blade	162	Universal rust remover	228
Endurance hammers	124	Diamond grinding discs	163	Rust remover with mos2	228
Carpentry hammers	124	Diamond grinding discs	164	Rust remover with rust off effect	228
Shoemaker's hammers	125	Diamond grinding blocks	164	Rope and chain lubricant	228
Masonry hammers	125	Jigsaw blade sets	165	Dry lubricant with Teflon	228
Locksmith hammers	126	Front brushes	166	Drilling and tapping oil	228
Club hammers	127	Bits	168	Silicone spray	229
Rubber cap for club hammer	127	Bit sets	169	Aluzinc preparation	229
				Anti-scratch welding preparation	229
Rubber hammers	127	13 WORKSHOP TOOLS	475	Multifunction formulation pro40	229
Recoilless hammer Installation metalworking hammer	128		175	Penetrating grease	229
	128 128	Pliers		Contact spray	229
Axes Garden machete	130	Pincers	176	Universal remover for brakes with /	230
Wedges	130	Cutters	182	without acetone	
		Screwdrivers	182	Marking ink	230
11 CUTTING TOOLS	131	Screwdriver sets	184 186		
Multi-purpose knives	132	Voltage testers Allen wrench sets	189	17 EXHIBITION SYSTEMS	231
Safety knives	135	Torx wrench sets	190		
Plastic folding knife	136	Torx and hex wrench sets	191	System shelving Laser display	234
Paint scrapers	136	Wrench sets	191	Cabinets	238 238
Replacement blades for scrapers	136	Box wrenches	192 193	Pyramids	238
Replacement blades for knives	136	Universal sockets  Hook wrench for pipes and bolts	196	Racks, stands, displays	240
Plasterboard cutter	138	Adjustable wrenches	197		
Cutter for polystyrene foam and	138	.,	197		
insulation	130		198		
Cutter for mineral wool and polystyrene	138	Multi-purpose key for control cabinets	198		
Saw blades	139	Pipe wrenches Metal files	199		
Saws for cellular concrete	139	Wood files	200		
Bow saw	140		202		
Saws for metal	140	Chain sharpening files File sets	203 204		
Saw blades	141	File SetS	204		
Metal shears	142	44115417110045577	005		
Wire cutters	144	14 HEALTH & SAFETY	205		
Multitools and folding knives	144				
Pipe cutters	146	Knee pads	206		
·		Belts, handles and holsters	207		
12 POWER TOOL ACCESSORIES	147	Protective gloves	211		
		Magnetic band	214		
Drill bits for metal	148	Safety glasses	214		
HSS drill bits for metal Cylindrical drill bits	149 150				
- , 311001 01111 0110	100				

# **ABOUT US**

#### **ABOUT THE PRO COMPANY**

For over 30 years, PRO Sp. z o.o. has been setting the standards as an industry leader and Poland's largest manufacturer of measuring tools and equipment used in construction. The most significant of these is the red PRO spirit level - the fundamental measuring tool on every construction site.

"Setting the standards" is part of the company's mission, implemented through the principle of Total Quality Management. The beginning of this road to perfection was the certification of the Quality System according to ISO 9000 standard in 1999, extended by the introduction of the Integrated Management System (ISO 9001, ISO 14000, PN-N-18001).

Winning the Silesian and then the national edition of the Polish Quality Award in 2003 confirmed the quality of the applied company management methods. In the following year - 2004 - the PRO company also received a distinction for its pro-ecological activities in the Pantheon of Polish Ecology competition.

A well-managed company is capable of producing excellent products. The PRO company manufactures some of the best spirit levels in the world, which was recognized by the European Medal for Products in 2002 and the Gold Medal for the PRO spirit level at BUDMA 2003 International Construction Fair.

PRO not only cares about the highest quality of its tools, but also about their aesthetics, for which it received an award in the only European competition in the field of design management - the Design Management Europe Award 2014. DME award winners are innovative organizations for which design is a major element of marketing strategy.

The Company was awarded the Forbes Diamonds in 2010 for its dynamic development. PRO's current offer includes a whole range of tools utilized by every professional in the construction industry, starting with a tape measure and ending with technologically advanced digital and laser measuring devices.

The company was recognized and awarded for these innovative products in 2015, in the 6th edition of the Company of the Year competition, in the "Innovative Company" category, organized by RIHiP in Bielsko-Biała. The company is, first of all, the people. For a market leader who applies TQM methods in practice, occupational safety is a priority concern. This was recognized by the National Labor Inspectorate with an award in the "Employer-Organizer of Safe Work" competition, which promotes the best practices in improving safety conditions at work.

Last but not least, PRO is active in the field of sports sponsorship, supporting



AZS ATH Bielsko-Biała over the years. In the cultural sphere, as a long-term "Sponsor of Bielska Jesień - the Founder of the Award".

The company currently employs nearly 200 people, and our products are exported to 28 countries.

#### **DESIGN THINKING**

The competence of R&D in product development for 30 years of business is worth mentioning. The form of our measuring instruments is developed with the Design Thinking method.

Design Thinking is an approach to creating new products and services based on a deep understanding of user problems and needs.

The company observes users in their natural working conditions, noticing details that they are often unaware of.

PRO reflects these needs in ergonomics and product design. It is a very rewarding process, although difficult and expensive.

This has led to the development of, among other things, our vials, which thanks to their design act like a magnifying glass, making it easier for users to read.

In the field of design, we have received the prestigious DME (Design Management Europe) and iF Design awards.





# **ABOUT US**

#### COMPANY HISTORY

1991

Establishment of PRO manufacturing enterprise, focused on the production of screeding levels and spirit levels. 2003

Victory in the Silesian and national edition of the Polish Quality Award.

2010

Winning the "Diamond" award of the Forbes magazine, granted annually to the most dynamically developing Polish companies.

2021

PRO celebrates the anniversary of its founding. We have been producing tools trusted by professionals for 30 years.

999

Certification of the quality system according to ISO 9000 standard and then introduction of the integrated management system (ISO 9001, ISO 14000, PN-N-18001 standards).


2008

Construction of modern office and warehouse buildings and the relocation of the company's HQ from ul. Londzina to ul. Strażacka in Bielsko-Biała.

**316** 

The German iF Design Award (one of the world's most prestigious industrial design competitions)





#### **CALIBRATION CENTER**


We have a laser equipment calibration center. Our workstations are equipped with an industrial-grade collimator for the calibration of plumb lines, levels, 90-degree angles, and compensator alignment, as well as 19 cameras to facilitate efficient and precise calibration of lasers.

Before the calibration process, we perform an initial check of the equipment for any mechanical damage. Thanks to the standards of plumb lines, 90-degree angle and 360-degree level, we can assess and precisely compensate the degree of deviation of the laser from the standard.

By calibrating the components one by one, we keep an eye on the model guidelines. The goal of correct calibration is to maximize the precision of the measurements.

Each item is carefully inspected before it is released from the warehouse and shipped to the customer. In our center, we calibrate all laser elements, which makes us one of the few manufacturers on the Polish market with such a wide and specialized capabilities. All of this is to ensure that we can meet high expectations of our customers when it comes to the accuracy of our measuring equipment.

01 LEVELS
02 SCREEDING LEVELS
03 BUILDER'S SQUARES
04 OPTICAL AND LASER DEVICES
05 MEASURES AND TAPES
06 MEASURING DEVICES
08 CONSTRUCTION TOOLS
09 GARDEN TOOLS
10 HAMMERS AND AXES
11 CUTTING TOOLS
12 ACCESSORIES FOR POWER TOOLS
13 WORKSHOP TOOLS
14 H&S
15 LIGHTING
16 TECHNICAL CHEMICAL PREPARATIONS
17 EXHIBITION SYSTEMS



# SERIES PRO 1000 ENDURANCE























# DOUBLE-SIDED MILLED SURFACE

Perfectly even, precision milled surfaces for limited slippage and excellent contact with the ground.

#### THREE-CHAMBER PROFILE

The profile with intact central chamber guarantees high resistance to mechanical damage. The ribs increase the rigidity of the profile.





#### HANDLE

Makes it easier to hold the spirit level while taking measurements. The ergonomic shape fits any hand and works with gloves.

#### EASY READING ERS+ SYSTEM

OPRO EL INMINI

High-quality acrylic glass vials - larger vial chamber and higher magnification lens. The gentle shape and no sharp edges allow for easy and quick cleaning of any debris.





#### **ANTI SHOCK CAP**

A cap made of elastomer with high energy and impact force absorption in the event of a vertical drop.

#### IEW VERTICAL VIAL ERS+

Magnifying glass effect, multiplying the size of the bubble. Quick and easy to read regardless of the viewing angle.









9.1cm

# **Uncompromising** durability

Highest resistance to bending and torsion.

#### **PROFILE**

Durable, three compartment design with an intact center compartment.

Thickened walls guarantee resistance to bending and twisting. Eyelet cutouts and handles do not weaken the chamber design. The vial mounts have been designed so that the profile cut-out is as small as possible (smooth and round). More rigid structure of the tool is achieved by using a more robust embossing.

#### STRONG GRIP

Massive side ribs ensure a firm grip in the hand (STRONG GRIP). The handles make it easy to hold the level while working.

#### **ERS+ SYSTEM**

The vial was specially designed by PRO. Even larger vial chamber and higher magnification lens - ERS+ (easy reading system plus).

PRO logo embossed in acrylic vial body. The accuracy of the vial is 0.5mm/m = 0.029°. All PRO1000 ENDURANCE Series spirit levels have two vertical vials, making it possible to determine the verticality regardless of how you hold the level.

#### ANTI SHOCK CAP

Made of high energy-absorbing elastomer, the caps are designed to absorb the force of impact in the event of a vertical drop of the spirit level.

#### MILLED ON BOTH SIDES

The perfectly even, precisely milled surface on both sides ensures limited slippage and excellent contact with the ground.

#### RELIABILITY GUARANTEE

PRO provides customers with a 10-year warranty on the vials. All measuring tool profiles are tested for: vertical and horizontal bending, compression and torsion

#### PRO1000 ENDURANCE SERIES SPIRIT LEVEL

CODE	CAT NO.	LENGTH
3-01-01-B6-100	PRO-B6100	100cm
3-01-01-B6-120	PRO-B6120	120cm
3-01-01-B6-150	PRO-B6150	150cm
3-01-01-B6-180	PRO-B6180	180cm
3-01-01-B6-200	PRO-B6200	200cm
3-01-01-B6-250	PRO-B6250	250cm*

<sup>\*</sup> the product is not milled

























#### DOUBLE-SIDED MILLED SURFACE IN BLACK\* VERSION

The perfectly even, precision milled surfaces for limited slip and excellent ground contact.

#### THREE-CHAMBER PROFILE

The profile with intact central chamber guarantees high resistance to mechanical damage. The ribs increase the rigidity of the profile.





#### **HANDLE**

Makes it easier to hold the spirit level while taking measurements. The ergonomic shape fits any hand and works with gloves.



#### EASY READING ERS+ SYSTEM

High-quality acrylic glass vials - larger vial chamber and higher magnification lens. The gentle shape and no sharp edges allow for easy and quick cleaning of any debris.





#### ANTI SHOCK CAP

The cap is made of an elastomer with high energy absorption and impact force in case of a vertical fall (ANTI SHOCK CAP). Thanks to special stoppers it facilitates immobilization of the level, further creating distance from the work surface.

#### NEW VERTICAL VIAL ERS+

Magnifying glass effect, multiplying the size of the bubble. Quick and easy reading regardless of the viewing angle.









6.12cm

# 01

# SPIRIT LEVELS

# A model spirit level

Designed with users.

A perfect combination of durability and convenience. Unbreakable.

#### **PROFILE**

The three-chambered profile widened by 25% increases stability and minimizes the possibility of the level tipping over. Thickened walls guarantee resistance to bending and twisting. Cutouts for riser vials and handles do not weaken the chamber design. Vial mounts designed in a way that the profile cutout is as small as possible. The exceptionally strong yet flexible combination of vials with the aluminum body increases the resistance to loss of accuracy caused by shocks and drops of the tool.

#### STRONG GRIP

Specially embossed solid side edges provide secure grip along the entire length of the profile, additionally increasing its rigidity (STRONG GRIP). The handles make it easy to hold the level while working. The ergonomic shape fits any hand and works with gloves.

#### **ERS+ SYSTEM**

Even larger vials with a magnifying glass effect, multiplying the bubble size. Quick and easy reading regardless of the viewing angle -ERS+ (Easy Reading System Plus). Indicators made of high quality industrial grade acrylic glass for maximum clarity and illumination, while protecting it from shattering, scratching or fading. Absence of the double bubble effect in the vial. PRO logo embossed in the vial body. All PRO900 ENDURANCE Series spirit levels are equipped with two vertical vials, which makes it possible to determine the verticality regardless of how the spirit level is held.

#### ANTI SHOCK CAP

Made of high energy absorbing elastomer, the cap is designed to absorb the force of impact in the event of a vertical drop of the spirit level.

#### **MILLED ON BOTH SIDES**

In the black version, a perfectly even, precisely milled surface on both sides ensures limited slippage and excellent contact with the ground. The red version is not milled.

#### **RELIABILITY GUARANTEE**

PRO provides customers with a 10-year warranty on the vials. All measuring tool profiles are tested for: vertical and horizontal bending, compression and torsion.

# PRO900 SERIES HEAVY DUTY SPIRIT LEVEL RED

CODE	CAT NO.	LENGTH
3-01-01-D4-080	PRO-D4080	80cm
3-01-01-D4-100	PRO-D4100	100cm
3-01-01-D4-120	PRO-D4120	120cm
3-01-01-D4-150	PRO-D4150	150cm
3-01-01-D4-180	PRO-D4180	180cm
3-01-01-D4-200	PRO-D4200	200cm

# PRO900 SERIES HEAVY DUTY SPIRIT LEVEL BLACK

CODE	CAT NO.	LENGTH
3-01-01-D5-080	PRO-D5080	80cm
3-01-01-D5-100	PRO-D5100	100cm
3-01-01-D5-120	PRO-D5120	120cm
3-01-01-D5-150	PRO-D5150	150cm
3-01-01-D5-180	PRO-D5180	180cm
3-01-01-D5-200	PRO-D5200	200cm





















#### **DOUBLE-CHAMBER PROFILE**

The shape offers optimum ratio of strength to the weight.

Thickened walls significantly increase resistance to bending and twisting.





#### **HANDLE**

Makes it easier to hold the spirit level while taking measurements. The ergonomic shape fits any hand and works with gloves.







#### **ANTI SHOCK CAP**

A cap made of elastomer with high energy and impact force absorption in the event of a vertical drop.

#### **NEW VERTICAL VIAL ERS+**

Magnifying glass effect, multiplying the size of the bubble. Quick and easy to read regardless of the viewing angle.











# **Combining the** best features

A reinforced classic tool with enhanced ergonomics.



#### **PROFILE**

The shape offers an optimal strength-to-weight ratio. The PRO800 ENDURANCE Series features a dual chamber profile. The thickened walls significantly increase the resistance to bending and thickened walls are the control of the cont

#### STRONG GRIP

Stiffening ribs - additional protection against mechanical damage, secure grip in your hand (STRONG GRIP). Handles that make it easy to hold the spirit level while working.

#### **EASY READING SYSTEM +**

The vial was specially designed by PRO. Vial chamber and lens with higher magnification. Magnifying glass effect, multiplying the size of the bubble. Quick and easy reading regardless of the viewing angle - ERS+ (Easy Reading System Plus). PRO logo embossed in acrylic vial. The vial mounts are designed for the smallest possible profile cutout. All PRO800 ENDURANCE Series levels are equipped with two vertical vials, allowing you to determine the vertical regardless of how you hold the level.

#### ANTI SHOCK CAP

Made of high energy absorbing elastomer, the cap is designed to absorb the force of impact in the event of a vertical drop of the spirit

#### **RELIABILITY GUARANTEE**

PRO provides customers with a 10-year warranty on the vials. All measuring tool profiles are tested for: vertical and horizontal bending, compression and torsion.

#### PRO800 ENDURANCE SERIES SPIRIT LEVEL PAINTED

CODE	CAT NO.	LENGTH
3-01-01-BE-060	PRO-BE060	60cm*
3-01-01-BE-080	PRO-BE080	80cm
3-01-01-BE-100	PRO-BE100	100cm
3-01-01-BE-120	PRO-BE120	120cm
3-01-01-BE-150	PRO-BE150	150cm
3-01-01-BE-180	PRO-BE180	180cm
3-01-01-BE-200	PRO-BE200	200cm
3-01-01-BE-250	PRO-BE250	250cm

<sup>\*</sup> product does not have handles

#### PRO800 ENDURANCE SERIES LEVEL ANODIZED

CODE	CAT NO.	LENGTH
3-01-01-B2-060	PRO-B2060	60cm*
3-01-01-B2-080	PRO-B2080	80cm
3-01-01-B2-100	PRO-B2100	100cm
3-01-01-B2-120	PRO-B2120	120cm
3-01-01-B2-150	PRO-B2150	150cm
3-01-01-B2-180	PRO-B2180	180cm
3-01-01-B2-200	PRO-B2200	200cm
3-01-01-B2-250	PRO-B2250	250cm

<sup>\*</sup> product does not have handles



























#### **MILLED SURFACE**

Perfectly even, precision milled surface for limited slippage and excellent ground contact.

#### **DOUBLE-CHAMBER PROFILE**

The shape offers optimum ratio of strength to the weight. Thickened walls significantly increase resistance to bending and twisting.





Makes it easier to hold the spirit level while taking measurements. The ergonomic shape fits any hand and works with gloves.





#### **EASY READING ERS+ SYSTEM**

High-quality acrylic glass vials - larger vial chamber and higher magnification lens. The gentle shape and no sharp edges allow for easy and quick cleaning of any debris.





#### **ANTI SHOCK CAP**

A cap made of elastomer with high energy and impact force absorption in the event of a vertical drop.

#### **NEW VERTICAL VIAL ERS+**

Magnifying glass effect, multiplying the size of the bubble. Quick and easy to read regardless of the viewing angle.



CODE	CAT NO.	LENGTH
3-01-01-BG-040	PRO-BG040	40cm*
3-01-01-BG-050	PRO-BG050	50cm*
3-01-01-BG-060	PRO-BG060	60cm*
3-01-01-BG-080	PRO-BG080	80cm**
3-01-01-BG-100	PRO-BG100	100cm

CODE	CAT NO.	LENGTH
3-01-01-BG-120	PRO-BG120	120cm
3-01-01-BG-150	PRO-BG150	150cm
3-01-01-BG-180	PRO-BG180	180cm
3-01-01-BG-200	PRO-BG200	200cm
3-01-01-BG-250	PRO-BG250	250cm***

#### BENEFITS:

It has all the features of the PRO800 ENDURANCE Series. Additionally, it has a perfectly even, precisely milled surface for limited slip and excellent contact with the ground.

- \* the product has no handles
- \*\* the product has one handle \*\*\* the product is not milled









#### DOUBLE-SIDED MILLED SURFACE

Perfectly even, precision milled surfaces for limited slippage and excellent contact with the ground.

#### DOUBLE-CHAMBER PROFILE

The shape offers optimum ratio of strength to the weight. Thickened walls significantly increase resistance to bending and twisting.






#### HANDLE

Makes it easier to hold the spirit level while taking measurements. The ergonomic shape fits any hand and works with gloves.





10= 3 3 111 (



# **EASY READING ERS+ SYSTEM**

High-quality acrylic glass vials - larger vial chamber and higher magnification lens. The gentle shape and no sharp edges allow for easy and quick cleaning of any debris.





#### **ANTI SHOCK CAP**

A cap made of elastomer with high energy and impact force absorption in the event of a vertical drop.

#### **NEW VERTICAL VIAL ERS+**

Magnifying glass effect, multiplying the size of the bubble. Quick and easy to read regardless of the viewing angle.



CODE	CAT NO.	LENGTH
3-01-01-BJ-060	PRO-BJ060	60cm*
3-01-01-BJ-080	PRO-BJ080	80cm**
3-01-01-BJ-100	PRO-BJ100	100cm
3-01-01-BJ-120	PRO-BJ120	120cm
3-01-01-BJ-150	PRO-BJ150	150cm

CODE	CAT NO.	LENGTH
3-01-01-BJ-180	PRO-BJ180	180cm
3-01-01-BJ-200	PRO-BJ200	200cm
3-01-01-BJ-250	PRO-BJ250	250cm

PRO #

# **BENEFITS:**

It has all the features of the PRO800 ENDURANCE Series. In addition, it has a perfectly even, two-sided milled surface for limited slip and excellent contact with the ground, as well as additional rings allowing to determine a 2% slope.

<sup>\*</sup> the product has no handles
\*\* the product has one handle









PROFILE 0.6kg/m



4.9cm

# A red classic tool

The most popular spirit level in Poland. A model of precision at its lightest.

#### **PROFILE**

A series of professional spirit levels built on a rectangular profile, the shape of which offers an optimal ratio of strength to weight. Vial mounts designed to minimize the profile notch.

#### **STRONG GRIP**

Massive side ribbing provides a secure grip in the hand.

#### FRS+ SYSTEM

Vial specially designed by PRO. Even larger vial chamber and higher magnification lens - ERS+ (easy reading system plus). PRO logo embossed in acrylic vial body.

#### ANTI SHOCK CAP

Elastomer cap, designed to absorb the force of impact if the level falls vertically.  $\,$ 

#### RELIABILITY GUARANTEE

PRO provides customers with a 10-year warranty on the vials. All measuring tool profiles are tested for: vertical and horizontal bending, compression and torsion.

#### PRO600 ENDURANCE PAINTED

CODE	CAT NO.	LENGTH
3-01-01-A1-030	PRO-A1030	30cm
3-01-01-A1-040	PRO-A1040	40cm
3-01-01-A1-050	PRO-A1050	50cm
3-01-01-A1-060	PRO-A1060	60cm
3-01-01-A1-080	PRO-A1080	80cm
3-01-01-A1-100	PRO-A1100	100cm
3-01-01-A1-120	PRO-A1120	120cm
3-01-01-A1-150	PRO-A1150	150cm
3-01-01-A1-180	PRO-A1180	180cm
3-01-01-A1-200	PRO-A1200	200cm

#### PRO600 ENDURANCE ANODIZED

CODE	CAT NO.	LENGTH
3-01-01-A4-030	PRO-A4030	30cm
3-01-01-A4-040	PRO-A4040	40cm
3-01-01-A4-050	PRO-A4050	50cm
3-01-01-A4-060	PRO-A4060	60cm
3-01-01-A4-080	PRO-A4080	80cm
3-01-01-A4-100	PRO-A4100	100cm
3-01-01-A4-120	PRO-A4120	120cm
3-01-01-A4-150	PRO-A4150	150cm
3-01-01-A4-180	PRO-A4180	180cm
3-01-01-A4-200	PRO-A4200	200cm
3-01-01-A4-250	PRO-A4250	250cm

#### PRO600 ENDURANCE PAINTED WITH MAGNETS

CODE	CAT NO.	LENGTH
3-01-01-A3-030	PRO-A3030	30cm
3-01-01-A3-040	PRO-A3040	40cm
3-01-01-A3-060	PRO-A3060	60cm
3-01-01-A3-080	PRO-A3080	80cm
3-01-01-A3-100	PRO-A3100	100cm
3-01-01-A3-120	PRO-A3120	120cm
3-01-01-A3-150	PRO-A3150	150cm
3-01-01-A3-200	PRO-A3200	200cm

# PRO600 ENDURANCE PAINTED WITH 45° INDICATORS

CODE	CAT NO.	LENGTH	
3-01-01-A2-080	PRO-A2080	80cm	
3-01-01-A2-120	PRO-A2120	120cm	

#### PRO600 ENDURANCE ANODIZED WITH MAGNETS

CODE	CAT NO.	LENGTH
3-01-01-A6-030	PRO-A6030	30cm
3-01-01-A6-040	PRO-A6040	40cm
3-01-01-A6-060	PRO-A6060	60cm
3-01-01-A6-080	PRO-A6080	80cm
3-01-01-A6-100	PRO-A6100	100cm
3-01-01-A6-120	PRO-A6120	120cm
3-01-01-A6-150	PRO-A6150	150cm
3-01-01-A6-200	PRO-A6200	200cm
3-01-01-A6-250	PRO-A6250	250cm

























#### **DETERMINING SLOPES**

Additional rings to determine 2% slopes.



# ERGONOMIC PROFILE

The shape offers optimum ratio of strength to the weight. The thickened walls significantly increase the resistance to bending and twisting.



# PRO BERT

#### EASY READING ERS+ SYSTEM

High-quality acrylic glass vials - larger vial chamber and higher magnification lens. The gentle shape and no sharp edges allow for easy and quick cleaning of any debris.





#### ANTI SHOCK CAP

A cap made of elastomer with high energy and impact force absorption in the event of a vertical drop.



Magnifying glass effect, multiplying the size of the bubble. Quick and easy to read regardless of the viewing angle.



CODE	CAT NO.	LENGTH
3-01-01-AB-030	PRO-AB030	30cm
3-01-01-AB-040	PRO-AB040	40cm
3-01-01-AB-050	PRO-AB050	50cm
3-01-01-AB-060	PRO-AB060	60cm
3-01-01-AB-080	PRO-AB080	80cm

CODE	CAT NO.	LENGTH
3-01-01-AB-100	PRO-AB100	100cm
3-01-01-AB-120	PRO-AB120	120cm
3-01-01-AB-150	PRO-AB150	150cm
3-01-01-AB-180	PRO-AB180	180cm
3-01-01-AB-200	PRO-AB200	200cm

#### **BENEFITS:**

It has all the features of the PRO600 ENDURANCE Series. In addition, it can determine a 2% drop to assist in installation, construction and roadway work.

#### POCKET SPIRIT LEVELS

POCKET SPIRIT LEVEL 17 CM WITH LEVEL AND VERTICALITY **INDICATORS - ANODIZED** 



















- Handy 17cm anodized spirit level.
- Level vial (built in place of one of the vials).
- Neodymium magnet to facilitate work on steel structures.

#### **POCKET SPIRIT LEVEL PRO600 PLUS**

PRO-A6017

3-01-01-A6-017

CODE 3-01-01-AB-017





















- Handy 17cm spirit level.
- It has a horizontal and a vertical vial.
- It can determine 2% dropps

# **POCKET SPIRIT LEVEL PRO600**

CAT NO.

PRO-AB017



















- Handy 17cm spirit level.
- It has a horizontal and a vertical vial.

# MINI SPIRIT LEVEL



CODE CAT NO. 3-01-01-A1-012 PRO-A1012











- length 12 cm
- convenient and ergonomic mini spirit level PRO600 series
- 10-year warranty on vials
- vial chamber and lens with increased magnification ERS+ system (easy reading system)
- the accuracy of the vial is 0.5 mm/m
- Polish product

# **SPIRIT LEVEL**

WITH 2 HORIZONTAL AND 1 VERTICAL











- A spirit level for level determination in two axes.
- Arms with horizontal and vertical vials, joined at right angles, also allow 90° measurements.
- Product protected as an industrial design Rp 15923.

CODE	CAT NO.	DIMENSIONS	
3-01-01-A4-33	PRO-A4334	30×40cm	





15m

25m

GRADUATION mm PVC + PC

- Allows perfect leveling of distant points.
- Clear graduations for easy leveling.

CODE	CAT NO.	LENGTH
3-01-05-E1-752	PRO-PS752	15m
3-01-05-E1-754	PRO-PS754	25m

## **CASES FOR SPIRIT LEVELS**

120cm

200cm







- A case made of 600D polyester
- Rubber lining
- Available in two lengths 200 and 120 cm

CODE	CAT NO.	LENGTH
3-01-13-OR-302	PRO-OR302	120cm
3-01-13-OR-301	PRO-OR301	200cm



# MEASURING SCREEDING LEVELS









- Rectangular profile screeding level.
- Combines the function of a screeding level and a spirit level.
- Useful for leveling and smoothing large surfaces.
- Equipped with one or two measuring vials: horizontal and vertical, and optional holds

#### MEASURING SCREEDING LEVEL WITH LEVEL AND VERTICALITY INDICATORS AND HANDLES



#### MEASURING SCREEDING LEVEL WITH LEVEL AND VERTICALITY INDICATORS



#### MEASURING SCREEDING LEVEL WITH LEVEL INDICATOR





Cross-section of the measuring screeding and traversing level. Profile thickness 1.4 mm, profile weight 0.84 kg/m.

Vial specially designed for measuring screeding levels made of high quality acrylic glass

grass
- larger vial chamber and
higher magnification lens. The
gentle shape and no sharp
edges allow for easy and quick
cleaning of any debris.

Plastic handles make it easy to hold the screeding level, especially when leveling large areas.

DIMENSIONS [CM]	100	120	150	200	250	300	400
measuring screeding level with level and verticality vials and handles	3-01-02-21-100 PRO-21100	-	3-01-02-21-150 PRO-21150	3-01-02-21-200 PRO-21200	3-01-02-21-250 PRO-21250	01-02-21-300 PRO-21300	3-01-02-21-401 PRO-21401
measuring screeding level with level and verticality vials	3-01-02-20-100 PRO-20100	3-01-02-20-120 PRO-20120	3-01-02-20-150 PRO-20150	3-01-02-20-200 PRO-20200	3-01-02-20-250 PRO-20250	01-02-20-300 PRO-20300	3-01-02-20-400 PRO-20400
measuring screeding level with level vial	3-01-02-19-100 PRO-19100	-	3-01-02-19-150 PRO-19150	3-01-02-19-200 PRO-19200	3-01-02-19-250 PRO-19250	01-02-19-300 PRO-19300	3-01-02-19-400 PRO-19400

# )2

# **SCREEDING LEVELS**

# REINFORCED SCREEDING LEVEL 9CM



- Rectangular strengthened profile screeding level.
- Combines the function of a screeding level and a spirit level.
- Three times more durable.
- Useful for leveling and smoothing large areas and for making screeds.
- Equipped with one or two vials: horizontal and vertical, and optional plastic holds for easy handling of the level, especially when leveling large areas.

# 3x GREATER STRENGTH









#### SCREEDING LEVEL WITH LEVEL AND VERTICALITY INDICATORS AND HANDLES



#### SCREEDING LEVEL WITH LEVEL AND VERTICALITY INDICATORS



#### SCREEDING LEVEL WITH LEVEL INDICATOR








Profile cross-section of the measuring and traversing level.



High-quality acrylic glass viallarger vial chamber and higher magnification lens. The gentle shape and no sharp edges allow for easy and quick cleaning of any debris.



Plastic handles make it easy to hold the screeding level, especially when leveling large areas.

DIMENSIONS [CM]	200	250
screeding level with vials and handles for level and verticality	3-01-01-31-200 PRO-31200	3-01-02-31-250 PRO-31250
screeding level with level and verticality vials	3-01-02-30-200 PRO-30200	3-01-02-30-250 PRO-30250
screeding level with level indicator	3-01-02-29-200 pro-29200	3-01-02-29-250 PRO-29250

# REINFORCED SCREEDING LEVEL 8CM











- The special profile with a reduced height of 8 cm allows easier work (pulling off less material).
- Closed screeding level with very high stiffness and thickened working wall is perfect for flooring works.







Profile cross-section of the measuring and traversing level.



High-quality acrylic glass vial-larger vial chamber and higher magnification lens. The gentle shape and no sharp edges allow for easy and quick cleaning of any debris.

DIMENSIONS [CM] 200


3-01-02-33-250

PRO-33250





- Rectangular profile screeding






Profile cross-section of the traversing level.

DIMENSIONS [CM]	100	150	200	250	300	400
no vials	3-01-02-18-100	3-01-02-18-150	3-01-02-18-200	3-01-02-18-250	3-01-02-18-300	3-01-02-18-400
	PRO-18100	PRO-18150	PRO-18200	PRO-18250	PRO-18300	PRO-18400

## TRAPEZOIDAL SCREEDING LEVEL









Cross section of a 94mm × 18mm profile of a trapezoidal screeding lath.
Profile thickness 1.5 mm, profile weight 0.84kg/m.

DIMENSIONS [CM]	100	120	150	180	200	240	300	400
no vials	3-01-02-22-100	3-01-02-22-120	3-01-02-22-150	3-01-02-22-180	3-01-02-22-200	3-01-02-22-240	3-01-02-22-300	3-01-02-22-400
	PRO-22100	PRO-22120	PRO-22150	PRO-22180	PRO-22200	PRO-22240	PRO-22300	PRO-22400

# SCREEDING LEVEL TYPE "H" WITH AN OPEN PROFILE



- A screeding level made of h-shaped aluminum profile.
- Ergonomic design.





Profile cross-section of the h-shaped screeding level


LENGTH [CM]	100	120	150	200	240
h-shaped screeding level	3-01-02-23-100	3-01-02-23-120	3-01-02-23-150	3-01-02-23-200	3-01-02-23-240
	PRO-23100	PRO-23120	PRO-23150	PRO-23200	PRO-23240

# UNIVERSAL SCREEDING LEVEL



Combination of trapezoidal and h-shape level improves both stiffness of the whole level and ergonomics of work, it is perfect for "pulling" both gypsum and cement-lime plaster.





Cross section of the traversing level measuring 115mm × 30mm.

DIMENSIONS [CM]	150	200	240
code	3-01-02-35-150	3-01-02-35-200	3-01-02-35-240
	PRO-35150	PRO-35200	PRO-35240

## H-SHAPED LEVEL FOR STRIPPING PLASTER



Highly rigid I-shaped level is ideal for leveling uneven plaster work.





Profile cross-section of the level for stripping the plaster measuring 80mm × 42mm.

DIMENSIONS [CM]	150	200
code	3-01-02-36-150 PRO-36150	3-01-02-36-200 PRO-36200



#### BUILDER'S SQUARE WITHOUT INDICATORS

- Builder's squares manufactured on the basis of the PRO600 series spirit level profile.
- Composite material reinforcement provides a durable profile connection.
- High rigidity and mechanical strength protect against the so-called  $90^{\circ}$  sharpening effect.



#### **BUILDER'S SQUARE WITHOUT INDICATORS**



#### **BUILDER'S SQUARE WITHOUT INDICATORS WITH FOOT**



#### Painted builder's squares

DIMENSIONS [CM]	30 × 40	30 × 50	40 × 60	50 × 80	50 × 100	60 × 120	80 × 150
no vials	-	-	3-01-03-K1-064 PRO-K1064	3-01-03-K1-085 PRO-K1085	3-01-03-K1-105 PRO-K1105	3-01-03-K1-126 PRO-K1126	3-01-03-K1-158 PRO-K1158

#### Anodized builder's squares

DIMENSIONS [CM]	30 × 40	30 × 50	40 × 60	50 × 80	50 × 100	60 × 120	80 × 150
no vials	3-01-03-K5-043 PRO-K5043	3-01-03-K5-053 PRO-K5053	3-01-03-K5-064 PRO-K5064	3-01-03-K5-085 PRO-K5085	3-01-03-K5-105 PRO-K5105	3-01-03-K5-126 PRO-K5126	3-01-03-K5-158 PRO-K5158
no vials with foot	-					3-01-03-K6-126 PRO-K6126	

#### **BUILDER'S SQUARES WITH INDICATORS**

- Level and verticality vials to combine the functionality of a builder's square with a spirit level.







#### **BUILDER'S SQUARE WITH INDICATORS**



#### **BUILDER'S SQUARE WITH INDICATORS AND FOOT**



#### Painted builder's squares

DIMENSIONS [CM]	30 × 40	30 × 50	40 × 60	50 × 80	50 × 100	60 × 120	80 × 150
with	3-01-03-K3-043	3-01-03-K3-053	3-01-03-K3-064	3-01-03-K3-085	3-01-03-K3-105	3-01-03-K3-126	3-01-03-K3-158
level and verticality vials	PRO-K3043	PRO-K3053	PRO-K3064	PRO-K3085	PRO-K3105	PRO-K3126	PRO-K3158

#### Anodized builder's squares

DIMENSIONS [CM]	30 × 40	30 × 50	40 × 60	50 × 80	50 × 100	60 × 120	80 × 150
with	3-01-03-K7-043	3-01-03-K7-053	3-01-03-K7-064	3-01-03-K7-085	3-01-03-K7-105	3-01-03-K7-126	3-01-03-K7-158
level and verticality vials	PRO-K7043	PRO-K7053	PRO-K7064	PRO-K7085	PRO-K7105	PRO-K7126	PRO-XXXXX
with level and verticality vials and foot			3-01-03-K8-064 PRO-K8064	3-01-03-K8-085 PRO-K8085	3-01-03-K8-105 PRO-K8105	3-01-03-K8-126 PRO-K8126	-

# BUILDER'S SQUARE WITHOUT INDICATORS WITH A BEVELED CORNER





- Anodized builder's squares manufactured based on the PRO600 series spirit level profile.
- Composite plastic reinforcement to ensure durable profile connection.
- High rigidity and mechanical strength to prevent the so-called  $90^{\circ}$  sharpening effect.
- Anodized coating that does not scratch the surface.
- Beveled corner for easy work in wall corners.

DIMENSIONS [CM]	40 × 60	50 × 80	50 × 100	80 × 150	60 × 120	100 X 100	
CODE CAT NO.	3-01-03-KG-064 PRO-KG064	3-01-03-KG-085 PRO-KG085	3-01-03-KG-105 PRO-KG105		3-01-03-KG-126 PRO-KG126	3-01-03-KG-110 PRO-KG110	

# BUILDER'S SQUARE WITHOUT INDICATORS WITH A BEVELED CORNER AND REINFORCEMENT





- Anodized builder's squares manufactured based on the PRO600 series spirit level profile.
- Composite material reinforcement provides a durable profile connection.
- Builder's square designed specifically for jobs that require beating drywall to establish a right angle.
- Transverse reinforcement prevents the right angle sharpening effect of beating.
- High rigidity and mechanical strength protect against the so-called  $90^{\circ}$  sharpening effect.
- The beveled corner makes it easy to work in wall corners.

- Anodized coating that does not scratch the surface.

# 03

# **BUILDER'S SQUARES**


# BUILDER'S SQUARE WITH REINFORCEMENT






- Builder's square designed specifically for jobs that require beating drywall to establish a right angle.
- Transverse reinforcement prevents the right angle sharpening effect of beating.

DIMENSIONS [CM]	40 × 60	50 × 80	50 × 100	60 × 120	80 × 150	100 X 100
CODE	3-01-03-KA-064	3-01-03-KA-085	3-01-03-KA-105	3-01-03-KA-126	3-01-03-KA-158	3-01-03-KA-110
CAT NO.	PRO-KA064	PRO-KA085	PRO-KA105	PRO-KA126	PRO-KA158	PRO-KA110




### PLASTER BUILDER'S SQUARE WITH REINFORCEMENT





#### PLASTER BUILDER'S SQUARE WITH REINFORCEMENT AND VIAL



DIMENSIONS [CM]	80 × 80
grip and vials	3-01-03-KU-188 PRO-KU188
with vials	3-01-03-KT-188 PRO-KT188

# OPTICAL AND LASER DEVICES

# 04



# **OPTICAL AND LASER DEVICES**

# ROTATING LASER

LR-500XY, LR-500D
















	LR-500XY	LR-500D
Laser source:	semiconductor diode = 635 nm	semiconductor diode = 635 nm
Power:	< 1 mW, class II M	< 1 mW, class II M
Accuracy, horizontal: vertical:	± 1.0mm/10m (±0.1mm/1m); ±20" ±1.0mm/1.5m	± 1.0mm/10m (±0.1mm/1m); ±20" ±1.0mm/1.5m
Work range:	250m	250m
Rotational speed:	0 - 60 -120 - 300 – 600 rpm	0 - 60 -120 - 300 – 600 rpm
Scanning angle:	0 / 10° / 45° / 90° / 180°	0 / 10° / 45° / 90° / 180°
Self-leveling range:	± 5°	± 5°
Working range:	up to 500 m (diameter)	up to 500 m (diameter)
Remote control (range):	30 m (infrared)	100 m (radio)
Power supply:	Rechargeable NI-MH battery	Rechargeable NI-MH battery
Battery life:	approx. 18 hours	approx. 20 hours
Leakage class:	IP54	IP54
Dimensions:	205mm × 160mm × 190mm	205mm × 160mm × 190mm
Weight (with batteries):	3.0 kg	3.0 kg
Leveling angle:	360°	360°
Operating temperature:	-20°C ÷ 50°C	-20°C ÷ 50°C
Storage temperature:	-15°C ÷ 60°C	-15°C ÷ 60°C

CODE	CAT NO.	MODEL
3-01-06-L1-098	PRO-L1098	LR-500XY
3-01-06-L1-099	PRO-L1099	LR-500D

# 03

# LASER AND OPTICAL DEVICES













#### LR-500XY

- For outdoor and indoor use.
- IP54 rating for protection against dust and rain.
- Automatic, motor-controlled determination of both level and verticality, with the ability to manually adjust tilt independently in the two X and Y axes.
- Scan function with scan angle setting.
- Tilt alarm function, resulting from a shock or violation of the original position of the instrument, after which the instrument must be restarted manually.
- Using the remote control, you can adjust tilt, rotation speed, scan angle as well as rotate the scanning area in either direction.
- Laser receiver (detector) with two illuminated displays, acoustic signal adjustment, switching of accuracy fine or coarse.
- Class 2M laser diode, <1mW 635nm.

#### LR-500D (ADDITIONAL)

- A digital slope determination function.
- A 100m range radio remote control with display.

#### SET.

- Laser LR-500XYLR-500D;
- Case;
- Remote Control;
- Laser receiver (detector) with bracket;
- Laser targeting dial;
- Laser glasses,
- NI-MH rechargeable battery;
- Alkaline battery basket,
- Charger;
- Operating Manual.

# LASER AND OPTICAL DEVICES


# ROTATING LASER

#### **LR-200VH, LR-200VHG**























#### LR-200VH

- Rotating laser LR-200VH with visible beam.
- For outdoor and indoor use.
- IP54 rating for protection against dust and rain.
- Automatic motorized horizontal and vertical alignment, with manual tilting
- Scan function with adjustable scan angle.
- Tilt alarm function, resulting from a shock or violation of the original position of the instrument, after which the instrument must be restarted manually.
- Using the remote control, you can adjust tilt, rotation speed, scan angle as well as rotate the scanning area in either direction.
- Laser receiver (detector) with two illuminated displays, acoustic signal adjustment, switching of accuracy - fine or coarse.
- Class 2M laser diode, < 1 mW 635 nm.

#### LR-200VHG (ADDITIONAL)

- A green beam 4 times brighter than the red laser.



	LR-200VH	LR-200VHG
Laser source:	semiconductor diode = 635 nm	semiconductor diode = 515- 520 nm
Power:	< 1 mW, class II M	< 1 mW, class II M
Accuracy, horizontal: vertical:	± 1.0 mm/10 m (± 0.1 mm/1m) ± 1.5 mm/10 m (± 0.15 mm/1m)	± 1.0 mm/10 m (± 0.1 mm/1m) ± 1.5 mm/10 m (± 0.15 mm/1m)
Work range:	200m	200m
Rotational speed:	0-300-600 rpm	0-300-600 rpm
Scanning angle:	10°/30°/60°	10°/30°/60°
Self-leveling range:	±5°	±5°
Working range:	up to 400 m (diameter)	up to 400 m (diameter)
Remote control (range):	30m	30m
Power supply:	Rechargeable NI-MH battery	Rechargeable NI-MH battery
Battery life:	about 24 hours	about 18 hours
Leakage class:	IP54	IP54
Dimensions:	130 mm × 210 mm × 175 mm	130 mm × 210 mm × 175 mm
Weight (with batteries):	2.0 kg	2.0 kg
Leveling angle:	360°	360°
Operating temperature:	-10°C ÷ 40°C	-10°C ÷ 40°C
Storage temperature:	-15°C ÷ 60°C	-15°C ÷ 60°C

#### SET:

- LR-200VH laser;
- Case;
- Remote Control;
- Laser receiver (detector) with bracket:
- Reflective shield;
- Wall mount;
- NI-MH rechargeable battery;
- Charger;
- Operating Manual.


CODE	CAT NO.	MODEL
3-01-06-L1-065	PRO-L1065	LR-200VH
3-01-06-L1-089	PRO-L1089	LR-200VHG

# LASER AND OPTICAL DEVICES

#### FLOOR PLANE LASER

#### LP-360.3DG TILER







RANGE **50 m** with detector



















#### SET:

- LP-360.3DG TILER multi-line
- 3.7V Li-ion rechargeable battery (replaceable)
- IP67 rated carrying case
- remote control
- laser goggles green
- "hanger" type magnetic holder and a flat steel bar
- 360° metal base with tripod and 5/8" thread
- 5/8" adapter with joint (for bevel)
- scissor type elevator base

Laser source:	Semiconductor diode = 515-520 nm,
Power:	<1mW each beam, class II
Accuracy:	+/- 1.0 mm/5m (+/- 0.2 mm/1m)
Seir-leveling range:	+/- 3°
Line Width:	less than 3.5 mm/10m
Self-leveling system:	magnetic pendulum
Working range (radius):	Up to 20 m indoors depending on lighting and a radius of 50 m using a detector
Power supply:	3.7V 2×2,700 mAh Li-ion battery
Working time (all beams on):	Approx. 8 hours (all lines)
	135 mm x 85 mm x 140 mm
Weight (with batteries):	0.74 kg
Horizontal/Vertical line angle:	2 x 360° / 360°
Operating temperature:	-10°C ÷ 45°C
Storage temperature:	-15°C ÷ 60°C

CODE	CAT NO.
3-01-06-1 1-070	DDO-1 1070

- The LP-360.3D TILER multi-line laser generates three 360° planes, one horizontal plane and two vertical planes intersecting at 90°.
- Pulse mode for working with laser detectors increases the laser's range
- Laser plumb function (cross axis on ceiling and ground).
- Ability to designate slants.
- Self-leveling due to automatic compensator cushioning.
- Resistant to water and dust IP54 rating.
- Tilt outside the operating range ( $\pm 3^{\circ}$ ) is indicated by flashing of the laser line and an acoustic signal.
- Equipped with a patented magnetic hanger that allows the laser to be fully moved to the wall (e.g. for laying ceramic tiles).
- Easily mounts on 1/4" and 5/8" tripod or strut pole.

# LASER AND OPTICAL DEVICES

# PLANE LASER

#### LK-360.3D




























#### SET:

- LK-360.3D laser;
- 3.7V Li-ion rechargeable battery (replaceable);
- IP67 rated carrying case;
- Laser goggles red;
- Operating Manual;
- Remote control.
- "Hanger" type magnetic holder with micro adjustment and a flat steel bar;
- 360° metal base with tripod and 5/8" thread;
- Adapter 5/8" with joint (for slants).

Laser source:	semiconductor diode = 638 nm
Power:	< 1 mW each beam, class II
Accuracy:	± 1 mm/5 m (± 0.2 mm/1m)
Self-leveling range:	± 3°
Line width:	less than 3.5 mm / 10 m
Self-leveling system:	magnetic pendulum
Working range (radius):	up to 20 m indoors depending on lighting and 50 m when using a detector
Power supply:	li-ion battery
Working time (all beams on):	about 8 hours
Dimensions:	15U mm × 85 mm × 14U mm
Weight (with batteries):	0.70 kg
Vertical/horizontal line ange:	2 × 360° / 360°
Operating temperature:	-10°C ÷ 45°C
Storage temperature:	-15°C ÷ 60°C

- The LK-360.3D multi-line laser generates three 360° planes, one horizontal plane and two vertical planes that intersect at 90°.
- Pulse mode for working with laser detectors increases the laser's range
- Laser plumb function (cross axis on ceiling and ground).
- Ability to designate slants.
- Self-leveling due to automatic compensator cushioning.
- Resistant to water and dust IP54 rating.
- Inclination outside the operating range ( $\pm 3^{\circ}$ ) is indicated by flashing of the red laser lines and an acoustic signal.
- Equipped with a patented magnetic holder in the form of a hanger, which allows the laser to be fully moved to the wall (e.g. for laying ceramic tiles)
- Easily mounts on 1/4" and 5/8" tripods or strut poles.

CODE CAT NO.

3-01-06-L1-071 PRO-L1071

## **PLANE LASER**

## LK-360.3DG











**NEW 2021!** 

RANGE

50 m

WITH DETECTOR

















- LK-360.3DG laser
- 3.7 V Li-ion rechargeable battery
- A charger with a micro USB cable (5V, 2A)
- IP67 rated carrying case
- Laser goggles green
- Operating Manual
- "Hanger" type magnetic holder with micro 5-axesadjustment; with adjustment of height, 90 mm, 'elevator' type
- 360° tripod base with 3-axes micro-adjustment
- Adapter 5/8" with joint (for slants)

Laser source:	Semiconductor diode = 520 nm
Power:	< 1mW each beam, class II
Accuracy:	+/- 1.0 mm/ 5m (+/- 0.2 mm/1m)
Self-leveling range:	4° +/-1°
Line width:	Less than 3.5 mm/10 m
Self-leveling system:	Magnetic pendulum
Working range (radius):	Up to 30 m indoors depending on lighting and a radius of 50 m with a detector
Power supply:	Rechargeable Li-ion 3.7 V 5,200 mAh
Working time (all beams on):	Approx. 8 hours
Dimensions:	127 mm x 85 mm x 120 mm
Weight (with batteries):	0.70 kg
Horizontal/Vertical line angle:	2 x 360° / 360°
Operating temperature:	-10°C ÷ 50°C
Storage temperature:	-20°C ÷ 70°C

CODE	CAT NO.	REMOTE CONTROL
3-01-06-L1-083	PRO-L1083	NONE
3-01-06-L1-183	PRO-L1183	INCLUDED

- The LK-360.3DG multi-line laser generates three 360° planes, one horizontal plane and two vertical planes that intersect at  $90^\circ$ .
- Pulsed mode for the laser beam detector to increase the laser range
- Laser plumb function (cross axis on ceiling and ground).
- Marking out slants
- Self-leveling thanks to automatic compensator cushioning.
- Resistant to water and dust IP54 rating.
- Tilt change outside the operating range (+-3) is indicated by flashing of the laser lines
- Equipped with a patented magnetic holder in the form of a hanger, which allows the laser to be fully moved to the wall (e.g. for laying ceramic tiles)
- Easily mounts on 1/4" and 5/8" tripods or strut poles.

## **CROSS-LINE LASER**

**X-LINER 4.1+, X-LINER 4.1G** 









4V1H


CLASS






	X-LINER 4.1+	X-LINER 4.1G
Laser source:	semiconductor diode = 635 nm lower point 650 nm	semiconductor diode = 520 nm lower point 650 nm
Power:	< 1 mW each beam, class II	< 1 mW each beam, class II
Accuracy:	± 1 mm/7m (± 0.14 mm/1m)	± 1 mm/7m (± 0.14 mm/1m)
Self-leveling range:	± 3°	±3°
Line width:	less than 3.3 mm / 10 m	less than 3.3 mm / 10 m
Self-leveling system:	magnetic pendulum	magnetic pendulum
Working range:	up to 20 m indoors depending on lighting and 50 m with a detector	up to 45 m indoors depending on lighting and 55 m with a detector
Power supply:	lithium-ion battery 3.7V	lithium-ion battery 3.7V
Working time (all beams on):	approx. 10.5 hours	approx. 3 hours (12 hours one beam)
Dimensions:	Ø 93 mm × 190 mm	Ø 93 mm × 190 mm
Weight (with batteries):	1.1 kg	1.1 kg
Horizontal/Vertical line angle:	120° / 2 × 360°	120° / 2 × 360°
Operating temperature:	-15°C ÷ 45°C	-15°C ÷ 45°C
Storage temperature:	-20°C ÷ 60°C	-20°C ÷ 60°C

CODE	CAT NO.	MODEL
3-01-06-L1-052	PRO-L1052	4.1+
3-01-06-L1-054	PRO-L1054	4.1G











#### X-LINER 4.1

- The X-LINER 4.1 cross-line laser for horizontal and vertical leveling, and determining a common level for objects far apart.
- Generates one, two or four vertical beams, one horizontal beam and a point on the ground.
- The vertical lines form two planes that intersect at 90°.
- Self-leveling thanks to automatic compensator cushioning.
- Ribbed top bowl made from non-slip plastic (TPR) increased durability, secure grip and precise positioning.
- Smaller viewfinders with internally mounted head cover glass for better protection of the laser lens against damage.
- Modular enclosure with increased resistance to damage.
- Compact size achieved by integrating the battery and charging the system inside the case.
- 0-360° swivel design with manual operation and fine adjustment knob.
- The unit automatically signals when it exceeds the self-leveling range of  $\pm$  3 degrees.
- Useful detector function (pulse mode "OUTDOOR").

- The working range of the device is up to 30 m, with an accuracy of ±1mm/ 7m.
- Easily mounted on a tripods or poles with a 5/8" thread.

## X-LINER 4.1+ (ADDITIONAL)

- Twice the beam strength.
- Ability to designate slants.

## X-LINER 4.1G (ADDITIONAL)

- A green beam 4 times brighter than a red laser.
- Ability to designate slants.

- Cross laser
   X-LINER 4.1 / 4.1+ 4.1 G;
- Functional suitcase with belt clip;
- Shoulder strap;
- Goggles;

- Target plate;
- Charger;
- Li-ion rechargeable battery (built-in);
- Operating Manual.

## **CROSS-LINE LASER**

**LK-180 G** 


















#### SET:

- LK-180G cross line laser;
- Case with protective padding;
- Universal magnetic chuck with movable head and 1/4"thread;
- Target plate
- 3 AA batteries:
- Operating Manual.

Laser source:	semiconductor diode = 515-520 nm
Power:	< 1 mW each beam, class II
Accuracy:	± 1 mm/5 m (± 0.2 mm/1m)
Self-leveling range:	4° ±1°
Line width:	less than 3.5 mm / 10 m
Self-leveling system:	magnetic pendulum
Working range:	up to 15 m indoors depending on lighting and 40 m while using a detector
Power supply:	3 x AA alkaline battery
Working time (all beams on):	approx. 4 hours
Dimensions:	90 mm × 70 mm × 90 mm
Weight (with batteries):	400 g
Horizontal/Vertical line angle:	180°/180°
Operating temperature:	-5°C ÷ 40°C
Storage temperature:	-20°C ÷ 70°C

CAT NO.

- The LK-180G cross-line laser generates one vertical beam and one horizontal beam, both with an extended working range of 180°.
- Allows to determine the level and plumb line on opposite walls
- Green laser diodes generate high-contrast, highly visible lines, up to 5 times brighter than in a red laser of the same power.
- Laser beam detector mode to increase the laser range.
- The laser lines intersect at a 90° angle.
- Possibility to determine slants in manual mode.
- Self-leveling thanks to automatic compensator
- The laser switches to warning mode, indicated by flashing lines, when out of self-leveling range.
- The body is covered with non-slip and anti-impact rubber.
- It has 1/4" threads (laser) and 5/8" (magnetic base).
- Resistant to water and dust IP54 rating.
- Features a magnetic base with a wall-mounted clip and 1/4" and 5/8" brass threads.
- Easily mounted on tripods and poles with a 1/4" or 5/8" threads


CODE

3-01-06-L1-086

## **CROSS-LINE LASER**

## LK-2V360H, LK-2V360HG







RANGE 50 m












RANGE

**50 m** 













#### LK-2V360H (RED)

- The LK-2V360H cross-line laser generates one 360° horizontal beam and two 90° intersecting vertical beams.
- Laser beam detector mode increases working range
- Ability to designate slants.
- Mechanical pendulum locking mechanism to determine oblique lines.
- Self-leveling thanks to automatic compensator cushioning.
- Resistant to water and dust IP-54 rating.
- Tilt of the device.
- Equipped with a universal magnetic holder with movable head.
- Easily mounted on 1/4" tripods

## LK-2V360HG (GREEN)

- It has a green beam 4 times brighter than a red laser.



- Cross-line
- LK-2V360H/ LK-2V360HG;
- Case with protective padding;
- Universal magnetic chuck with movable head and 1/4" thread;
- Target plate;
- 3 AA batteries;
- Operating Manual.

CODE	CAT NO.	MODEL
3-01-06-L1-062	PRO-L1062	LK-2V360H
3-01-06-L1-087	PRO-L1087	LK-2V360HG

## **CROSS-LINE LASER LK-1V360H**

## LK-1V360H, LK-1V360H G

















RANGE 50 m WITH DETECTOR











RANGE

50 m

## LK-1V360H

- The LK-1V360H cross-line laser generates one 360° horizontal beam and one 90° intersecting vertical beam.
- Laser beam detector mode increases working range
- Mechanical pendulum locking mechanism to determine oblique lines
- Self-leveling thanks to automatic compensator cushioning.
- Inclination outside the operating range ( $\pm 3.5^{\circ})$  is indicated by flashing laser lines.
- Easily mounted to 1/4" or 5/8" tripods.

## LK-1V360H G

- 360° rotary leveling head included.
- It has a green beam 4 times brighter than a red laser.



	LK-1V360H	LK-1V360H G
Laser source:	semiconductor diode = 630-640 nm,	semiconductor diode = 515-520 nm
Power:	< 1 mW each beam, class II	< 1 mW each beam, class II
Accuracy:	± 1.5 mm/5m (± 0.3 mm/1m)	± 1.5 mm/5m (± 0.3 mm/1m)
Self-leveling range:	± 3.5°	± 3.5°
Line width:	2mm@5m; 3.5mm@10m	3mm@5m; 4mm@10m
Self-leveling system:	magnetic pendulum	magnetic pendulum
Working range:	up to 20 m indoors depending on lighting and 50 m with a detector	up to 25 m indoors depending on lighting and 50 m with a detector
Power supply:	4 x AA alkaline battery	4 x AA alkaline battery
Working time (all beams on):	more than 10 hours	approx. 4,5 hours
Dimensions:	119 mm × 62 mm × 115 mm	119 mm × 62 mm × 115 mm
Weight (with batteries):	540 g	540 g
Horizontal/Vertical line angle:	130°/360°	130°/360°
Operating temperature: Storage temperature:	-10°C ÷ 50°C -15°C ÷ 60°C	-10°C ÷ 50°C -15°C ÷ 60°C

#### SET.

- Cross-line laser LK-1V360H / LK-1V360H G;
- Case;
- 4 AA batteries;
- Operating Manual.

## LK-1V360H G (ADDITIONAL)

- 360° leveling head

CODE	CAT NO.	MODEL
3-01-06-L1-073	PRO-L1073	LK-1V360H
3-01-06-L1-063	PRO-L1063	LK-1V360HG

## **CROSS-LINE LASER**

## **SMART 1.1 HD, SMART 1.1 HD PLUS**






















**RANGE** 

50 m

## SMART 1.1 HD

- The SMART 1.1 HD (HEAVY DUTY) crossed laser generates one vertical and one horizontal beam, intersecting at  $90^\circ.$
- Continuous laser beam detector mode increases working range
- Generates strong, highly visible lines.
- Ability to determine bevels.
- Self-leveling thanks to automatic compensator cushioning.
- The laser switches to warning mode, indicated by flashing lines, when out of self-leveling range (4°± 1°).
- The body and the lock switch are covered with non-slip and anti-impact rubber.
- It has 1/4" threads (laser) and 5/8" (magnetic base).
- Resistant to water and dust IP54 rating.
- Resistant to shocks and drops from a height of up to 1 m.
- Features a universal, rotating, magnetic base with a wall-mounted clip and 1/4" and 5/8" brass threads.
- Easily mounted to 1/4" or 5/8" a tripods or strut poles.

#### **SMART 1.1 HD PLUS (ADDITIONAL)**

- Generates two points that mark the vertical line (plumb function).
- More powerful diodes (20mW) generate even brighter and more visible lines.



	SMART 1.1 HD	SMART 1.1 HD PLUS
Laser source:	semiconductor diode = 635 nm	semiconductor diode = 635 nm lower point 670 nm
Power:	< 1 mW each beam, class II	< 1 mW each beam, class II
Accuracy:	± 1 mm/5m (± 0.2 mm/1m)	± 1 mm/5m (± 0.2 mm/1m)
Self-leveling range:	4° ±1°	4° ±1°
Line width:	less than 3.5 mm / 10 m	less than 3.5 mm / 10 m
Self-leveling system:	magnetic pendulum	magnetic pendulum
Working range:	up to 30 m indoors depending on lighting and 50 m with a detector	up to 30 m indoors depending on lighting and 50 m with a detector
Power supply:	4 x AA alkaline battery	4 x AA alkaline battery
Working time	approx. 16 hours	approx. 16 hours
Dimension	114 mm × 60 mm × 97 mm	114 mm × 60 mm × 97 mm
Weight (with batteries):	490 q	490 q
Horizontal/Vertical line angle:	130°/130°	130°/130°
Operating temperature:	-10°C ÷ 50°C	-10°C ÷ 50°C
Temperature of storage:	-20°C ÷ 70°C	-20°C ÷ 70°C

- The cross-line laser SMART 1.1 HD PLUS;
- Target plate;
- Case;
- Rotating magnetic base;
- Operating Manual;
- 4 AA batteries.

CODE	CAT NO.	MODEL
3-01-06-L1-24/	PRO-L124/	SMART 1.1HD
3-01-06-L1-049	PRO-L1049	SMART 1.1HD PLUS

## **CROSS-LINE LASER**

**SMART 1.1, SMART 1.1G** 





1VH

CLASS







#### SMART 1.1

- Generates one vertical beam and one horizontal beam, intersecting at 90°.
- Mechanical pendulum locking mechanism to determine oblique lines.
- Resistant to water and dust IP-54 rating.
- Self-leveling thanks to automatic compensator cushioning.
- Tilt outside the operating range (4°) is indicated by flashing laser lines.
- Features a universal magnetic bracket with movable head and 1/4" thread.
- Easily mounted to a tripod or pole with a 1/4" thread.

# SPRO SPRO













#### SMART 1.1 G

- A green beam 4 times brighter than a red laser.

	SMART 1.1	SMART 1.1 G
Laser source:	semiconductor diode = 635 nm	diode = 515-520 nm
Power:	< 1 mW each beam, class II	< 1 mW each beam, class II
Accuracy:	± 1.5 mm/5m (± 0.3 mm/1m)	± 1.5 mm/5m (± 0.3 mm/1m)
Self-leveling range:	4° ±1°	4° ±1°
Line width:	less than 3.5 mm / 10 m	less than 3.5 mm / 10 m
Self-leveling system:	magnetic pendulum	magnetic pendulum
Operating range:	up to 15 m indoors depending on the lighting	up to 25 m indoors depending on light conditions
Power supply:	4 x AA alkaline battery	2 x AA alkaline battery
Working time (all beams on):	approx. 12 hours	approx. 4 hours
Dimensions:	76 mm × 66 mm × 76 mm	76 mm × 66 mm × 76 mm
Weight (with batteries):	270 g	270 g
Horizontal/Vertical line angle:	100°/100°	100°/100°
Operating temperature:	-10°C ÷ 50°C -10°C ÷ 50°C 3-01-06-L1-24	
Storage temperature:	-15°C ÷ 60°C	-15°C ÷ 60°C

- SMART 1.1/ SMART 1.1G cross-line laser;
- Case;
- Universal bracket with movable head and 1/4" thread;
- 2 AA batteries;
- Operating Manual.

CODE	CAT NO.	MODEL
3-01-06-L1-264	PRO-L1264	SMART 1.1 G

## **CROSS-LINE LASER**

## **SMART-X, SMART-XG**

















#### **SMART-X**

- Two high quality laser diodes, separate for horizontal and vertical plane.
- Generates one vertical beam and one horizontal beam, intersecting at 90°.
- Extremely fine lines for easier tiling work, for example.
- Mechanical pendulum locking mechanism to determine oblique lines.
- Resistant to water and dust IP-54 rating
- Self-leveling thanks to automatic compensator cushioning.
- Tilt outside the operating range is indicated by flashing laser lines.
- Easily mounted to a tripod or pole with a 1/4" thread.













## SMART-XG

- It has a green beam 4 times brighter than a red laser.

	SMART-X	SMART-XG
Laser source:	semiconductor diode = 635 nm	semiconductor diode = 505-550 nm
Power:	< 1 mW each beam, class II	< 1 mW each beam, class II
Accuracy:	± 1.5 mm/10 m (± 0.3 mm/1m)	± 1.5 mm/10 m (± 0.3 mm/1m)
Self-leveling range:	4° ±1°	4° ±1°
Line width:	less than 3.5 mm / 10 m	less than 3.5 mm / 10 m
Self-leveling system:	magnetic pendulum	magnetic pendulum
Operating range:	up to 15 m indoors depending on lighting, up to 40 m with detector	up to 25 m indoors depending on illumination, up to 40 m with detector
Power supply:	4 x AA alkaline battery	4 x AA alkaline battery
Working time (all beams on):	first setting: approx. 40 hours, tenth setting: approx. 180 hours	first setting: approx. 10 hours, tenth setting: approx. 40 hours
Dimensions:	76 mm × 66 mm × 76 mm	76 mm × 66 mm × 76 mm
Weight (with batteries):	270 g	270 g
Horizontal/Vertical line angle:	100°/100°	100°/100°
Operating temperature: Storage temperature:	-10°C ÷ 50°C -10°C ÷ 50°C 3-01-06-L1-09 -25°C ÷ 70°C	1 PRO-L1091 SMART-X -25°C ÷ 70°C

- SMART-X/ SMART-XG cross-line laser;
- Case;
- 4 AA batteries
- Operating Manual.

CODE	CAT NO.	MODEL
3-01-06-L1-092	PRO-L1092	SMART-XG

## DWL LASER BEAM DETECTOR

ACCURACY +/- 1.5mm

2 VIALS

153g



- The laser beam detector is used to find the laser beam emitted by cross-line lasers, leveling instruments and other laser devices.
- For use on its own or with a levelling staff mount.
- Expands the range of laser devices.
- LEDs on the front, side and rear of the detector indicate the position of the laser beam.
- Two vials allow for precise vertical and horizontal alignment of the detector.
- Simple and fast attachment. The detachable mount allows for quick and accurate mounting of the detector on leveling staffs
- The large adjustment range allows the detector to be used with leveling staffs of different widths.
- LED indicators show the current position of the laser plane relative to the detector zero line. The device is equipped with sets of indicators, each consisting of 3 different colored LEDs. Indicators are located on the front and back of the detector.
- The speaker emits different tones depending on the position of the beam relative to the laser line.



## **RED LASER BEAM DETECTOR DWL - 02**

Accuracy:	'precise' setting ± 1,5 mm 'medium' setting ± 2,5 mm
LEDs:	front / rear
Range:	at least 35m
Audio tones detection:	3 different for beam
Vials:	2
Power supply:	1 x 9 V 6LR61 battery
Auto shutdown:	after about 6 minutes
Dimensions:	164 mm × 52 mm × 27 mm
Weight (with battery):	40 g
Operating temperature:	5°C ÷ 45°C
Storage temperature:	-20°C ÷ 60°C

## **GREEN LASER BEAM DETECTOR DWL - 02G**

Accuracy:	'precise' setting ± 1,5 mm 'medium' setting ± 2,5 mm
LEDs:	front / rear
Range:	at least 40m
Audio tones:	3 different for beam detection
Vials:	2
Power supply:	1 x 9 V 6LR61 battery
Auto shutdown:	after about 6 minutes
Dimensions:	164 mm × 52 mm × 27 mm
Weight (with battery):	40 g
Operating temperature:	5°C ÷ 45°C
Storage temperature:	-20°C ÷ 60°C

## SET:

- Laser detector DWL-02;
- Mounting bracket;
- 9V battery;
- Operating Manual.



CODE	CAT NO.	
3-01-06-L1-139	PRO-DL139	

## SET:

- Laser detector DWL-02G;
- Mounting bracket;
- 9V battery;
- Operating Manual.



CODE CAT NO.

3-01-06-L1-159 PRO-DL159

# **TRIPODS**

## TRIPOD TR-660HD





- Heavy duty tripod with reinforced design
- 5/8"thread
- Metal head;
- Maximum working height with head: 165cm
- Carrying bag included
- Weight 2 kg

CODE CAT NO. 3-01-06-38-035

## **SURVEYING TRIPOD TR-900.2**



5/8" 155cm

- Very stable and durable
- Joints and foot spikes made of metal
- Quick and efficient "quick clamp" foot locking system
- With shoulder strap
- Does not change its shape and size under the influence of weather conditions
- Thread: 5/8" with cable bush
- Max. Height: 155 cm, folded height: 98cm
- Weight: 2.80 kg
- Application: for optical and rotary leveling instruments as well as for devices with 5/8" thread

## TRIPOD TR-3400HD

CAT NO.

CAT NO. PRO-TR034

PRO-TR123

CODE

3-01-06-38-123





- Robust, durable surveying tripod
- Height adjustment
- Comes with safety chains
- Metal head and thread
- Max working height with head 340cm
- Weight: 6 kg

## TRIPOD FOR THE POLE

3-01-06-38-034





- Allows the usage of an extension pole when it cannot be braced.
- Carrying bag included.

## **TRIPOD TR-420F**



1/4" 120cm TPR HEAD RUBBER FEET

- Camera tripod
- Thread 1/4"
- Maximum working height with head: 120cm
- Carrying bag included
- Weight 0.69 kg

## TRIPOD TR-650F

3-01-06-38-037

CAT NO.
PRO-TR037

CAT NO.

PRO-TR036

CAT NO.

PRO-TR039

CODE



1/4" 155cm TPR HEAD RUBBER FEET

- Camera tripod
- Thread 1/4"
- Symmetrical head for stability when determining bevels
- Hook for hanging a riser or load
- Maximum working height with head: 155cm
- Carrying bag included
- Weight 1.2 kg

**TRIPOD TR-450** 

3-01-06-38-036

CODE





5/8"

255cm

- Thread: 5/8" with cable bush.
- Feet: rubber.
- Head: plastic, metal thread.
- Max. working height with head: 150 cm.
- Min. working height with head: 56 cm.
- Weight: 0.96 kg
- Carrying bag included.
- Application: For lightweight cross-line lasers with 5/8"thread

## TRIPOD TR-755HD

CODE

3-01-06-38-039



- Heavy duty tripod with reinforced design
- 5/8" thread; metal head,
- Maximum working height with head: 255cm
- Cover included
- Weight: 2.7 kg

## **EXTENSION POLES**

LT-334S-2G EXTENSION POLE



- The LT-334S-2G extension pole allows to conveniently set up a cross-line laser in rooms up to 3.34m high without the need for a tripod.
- The pole height can be increased with optional 30 and 60 cm modules.
- The laser can be raised or lowered steplessly over virtually the entire length of the pole.
- Universal, thanks to 5/8" and 1/4" brass screws.
- The pole also features metric scales for easy placement of the laser at the desired height.

## SET:

- Bottom telescopic pole with a foot peg for easy wedging and a 5/8" thread on top
- Extension segments with a female thread on one end and male on the other three 60cm pieces and one 30cm piece
- Movable, universal mounting bracket with brass screws with 5/8" and 1/4" threads for placing the laser on the pole.
- A round stand, 8cm in diameter and 4cm high, used to fix the pole between the ground and the ceiling.
- Carrying bag.



CODE CAT NO.
3-01-06-38-012 PRO-TR012

**EXTENSION POLE LT-334S-2GT (WITH TRIPOD)** 



- The LT-334S-2GT extension spreader pole allows to conveniently set up a cross-line laser in rooms up to 3.34m high without the need for a tripod.
- The pole height can be increased with optional 30 and 60 cm modules.
- The laser can be raised or lowered steplessly over virtually the entire length of the pole.
- Universal, thanks to 5/8" and 1/4" brass screws.
- The pole also features metric scales for easy placement of the laser at the desired height.

#### SET:

- Lower pole piece of telescopic design, with a foot for easy wedging, with a top end with a 5/8" diameter bolt hole.
- Extension segments with a female thread on one end and male on the other three 60cm pieces and one 30cm piece
- Movable, universal mounting bracket with brass screws with  $5/8^{\rm u}$  and  $1/4^{\rm u}$  threads for placing the laser on the pole.
- A round stand, 8cm in diameter and 4cm high, used to fix the pole between the ground and the vault.
- Tripod for use in high halls and outdoors.
- Carrying bag.



**CODE CAT NO.** 3-01-06-38-014 PRO-TR014

## EXPANSION POLE MODULE





 CODE
 CAT NO.
 LENGTH (M)

 3-01-06-38-016
 PRO-TR016
 30

 3-01-06-38-017
 PRO-TR017
 60

- A piece extending the pole
- A female thread on one end and male on the other allow the pieces to be screwed together
- Comes in two lengths: 30 cm and 60 cm

## EXTENSION POLE SHELF WITH SCREW KIT







- An accessory extension pole shelf used to attach an additional laser between the ground and the vault.
- Comes with two screws with 5/8" and 1/4" threads.

## **MAGNETIC BASE P-02 WITH ADJUSTMENT**







CODE

3-01-06-38-020



- Magnetic base compatible with 1/4" lasers.
- Includes a bracket for mounting on plasterboard sheets
- An elevator to raise and lower the laser.
- Tripod mountable, thread: 5/8" and 1/4".
- 1/4" thread.

CODE CAT NO.
3-01-06-38-022 PRO-LA022



PLASTERBOARD

- Holder for fixing on a plasterboard sheet.



CODE CAT NO.
3-01-06-38-028 PRO-LA028

## ADJUSTABLE MAGNETIC LASER STAND

P-02 **MAGNETIC, ADJUSTABLE** 





PLASTERBOARD

5/8"

5/8"



- Magnetic base compatible with 1/4" lasers
- Adjustable elevator
- Tripod mountable, thread in the base: 5/8", 1/4"

## STEEL BASE (HANDLE)

CAT NO.

PRO-LA021

CODE

CODE

CODE

3-01-06-38-030

3-01-06-38-029

3-01-06-38-021

WITH HEIGHT MICRO-ADJUSTMENT

CAT NO.

CAT NO.

PRO-LA029



- Suitable also for rotating lasers

- Plasterboard sheet grip
- Adjustable elevator
- Micro height adjustment with mm scale
- 5/8" thread

**BASE (HANDLE)** 

P-06S FOR BEVELS



- The laser can be tilted between 0-90° to mark oblique lines.

SLANTS

- Magnetic base compatible with 1/4" and 5/8" lasers.
- Easily mounts on 5/8" and 1/4" tripod or strut pole.
- Magnet for mounting on steel surfaces.
- Grommets allow the use of velcro and zip ties.

## **MICROMETER BASE (ADAPTER)**

P-07S FOR BEVELS

3-01-06-LA-033



- Allows to tilt the laser from 0-90° to determine drops or slanted
- Resolution of micrometer adjustment 0.1°.
- Base compatible with 5/8" lasers.
- Can be mounted on a tripod or other accessories with



1/4"


SLANTS



2,4m ДΙ ±50cm

- Sturdy aluminum measuring staff with adjustable height and an integrated box vial for measuring the plumb
- Scale with the zero point fixed between the red and white fields (front of the staff)
- Quick-lock non-slip locking mechanism
- Color coding -
- silver "too high."
- red-"too low"

#### **LEVELING STAFF 5M LLN-500EM**



CAT NO. CODE 3-01-06-OP-105 PRO-LA105

- 5m ДΙ E SCALE mm
- Leveling staff a surveying instrument used in leveling.
- Aluminum with a rectangular cross-section, thickened walls and a height of up to 5
- The scale allows to read the precise distance from the foot of the staff to the point marked by a leveling instrument sights.
- A vial can be attached for vertical alignment of the staff.
- Telescopic 5 aluminum folding pieces. Sturdy aluminum reinforced latches.
- Bilateral scales: surveying in front (E), millimeter at the back.
- Length when extended: 5 m. Length when retracted: 1,22 m. Weight 1.6 kg.

## **LEVELING STAFF 5M** LLN-500EMX2

CODE

CODE

3-01-06-OP-107

3-01-06-OP-106



- Leveling staff a surveying instrument used in leveling. Aluminum with a rectangular cross-section, thickened walls and a height of up to 5m.
- The scale allows to read the precise distance from the foot of the staff to the point marked by a leveling instrument sights.
- A vial can be attached for vertical alignment of the staff.
- Telescopic 5 aluminum folding pieces. Sturdy aluminum reinforced latches.
- Bilateral division: surveying in front (E) and millimeter straight, back millimeter inverted. Inverted millimeter division allows to quickly measure the height of an object (e.g. a room, car, overpass). Simply extend the staff and read the height on it.
- Length when extended: 5 m. Length when retracted: 123 cm. Weight: 2.3 kg.

#### **LEVELING STAFF 7M LLN-700EM**

CAT NO.

PRO-LA107

CAT NO.



- Leveling staff a surveying instrument used in leveling.
- Aluminum with a rectangular cross-section, thickened walls and a height of up to 7m.
- The scale allows to read the precise distance from the foot of the staff to the point marked by a leveling instrument sights.
- A vial can be attached for vertical alignment of the staff.
- Telescopic 5 aluminum folding pieces. Sturdy aluminum reinforced latches.
- Bilateral division: surveying in front (E), millimeter at the back.
- Length when extended: 7m.
- Length when retracted: 163.5cm
- Weight: 1.95 kg.

## **ADAPTERS**

#### **ADAPTER 5/8"/5/8"**







- Adapter for cross-line lasers, 5/8" thread 5/8".
- For attaching the laser to a strut pole.
- Height: 5.5 cm.
- Weight: 60 g.

CODE	CAT NO.	
3-01-06-38-011	PRO-I 4011	

## **ADAPTER 5/8"/1/4" SHORT ADAPTER 1/4"/ 5/8" HEX**





- Adapter for cross-line lasers, 5/8" thread - 1/4".
- For attaching a 1/4" threaded device to a 5/8" tripod or pole.
- Galvanized steel.

CODE	CAT NO.	
3-01-06-38-019	PRO-LA019	

## GALVANIZED

1/4"



- Adapter for cross-line lasers, 1/4" / 5/8" thread.
- Galvanized steel.
- HEX, 17 mm

CODE	CAT NO.		
3-01-06-38-027	PRO-LA027		

mm

## TARGET PLATE FOR LASERS

## FOR RED LASERS



CODE	CAT NO.
3-01-06-38-25	PRO-LA025

## FOR GREEN LASERS



CODE	CAT NO.
3-01-06-38-26	PRO-I A026

## - Improves beam visibility of line, spot and rotation

- The target plate is perfect for dry construction measurements using a laser beam.
- Freestanding with a retractable leg.
- Built-in magnet for steel components.
- Scale in centimeters and inches.
- Left-hand scale in millimeters: 70mm
- Right-hand scale in inches: 3"
- Dimensions: 105 x 75 mm.

# LASER GOGGLES

## RED LG-R



## **GREEN LG-G**





- Improves the visibility of laser beams.
- Adjustable temple length: 4 steps.

## **OPTICAL LEVELS**



- An optical leveling instrument can measure height and distance differences, determine direction, slope and angles.
- 32x magnification for the longest range and highest accuracy when taking readings.
- Compensator with magnetic damping.
- Clear and sharp image even when measuring over long
- The metal housing protects the level against dust and water -
- The compensator lock used in the instrument provides protection during transportation of the instrument.
- Eyepiece with adjustable focus.
- A collimator for quick and comfortable aiming at the patch.
- Large, bright lens for clear visibility.
- Smooth angle adjustment by slip clutch; rubber coated screws.
- Robust and lightweight construction.

3-01-06-OP-24 PRO-OP024 NO-24 3-01-06-OP-32 PRO-OP032 NO-32	CODE	CAT NO.	TYPE
3-01-06-OP-32 PRO-OP032 NO-32	3-01-06-OP-24	PRO-OP024	NO-24
	3-01-06-OP-32	PRO-OP032	NO-32







TYPE	NO-24	NO-32
Magnification	24 ×	32 ×
Standard error per 1km of double leveling	2.0mm	1.00mm
Image	Sin	nple
Lens diameter	36mm	38mm
Field of vision	1°20' (2.3	m/100m)
Smallest focal length	0.3m	
Multiplication constant	100	
Addition constant	0	
Compensator range	± 15'	
Accuracy of compensator	± 0,6"	
Vial sensitivity	8' / 2 mm	
Division of the horizontal circle	360° (every 1°)	
Waterproof	IP54	
Heart screw thread	5/8"	
Operating temperature:	-20°- 50°	
Storage temperature:	-40°- 70°	
Weight	1.8	kg

#### SET:

- Optical leveling instrument;
- Telescope cover;
- Rectifying needle;
- String riser;
- Transport case;
- Operating Manual.

## LASER RANGEFINDER

## **DL-40M5 WITH 5M MEASURING TAPE**



CODE	CAT NO.
0.04.0014.004	DDO DI SO I



- The DL-40M5 laser rangefinder is used for distance measurement.
- Operation up to 5m with integrated reel measure with reverse brake and up to 40m with laser module.
- Laser measuring accuracy is +-2 mm, steel coiled measure in II accuracy class.
- An additional scale on the back of the tabletop allows for more convenient vertical measurement.
- Hook with magnet.
- Features a metal belt clip.

## LASER RANGEFINDER

DL-X, DL-XG























- They are used to measure distance, area and volume of the selected object.
- It has the following functions: indirect measurement (enhanced with the possibility of sum and difference calculation), continuous and dynamic measurement.
- Allows operation from 0.05 m to 40, 60, 80 or 100 m.
- The measurement accuracy is ± 2 mm.
- Three measurement reference points: front panel, rear panel of the unit, and 1/4"socket.
- Built-in digital protractor.
- Backlit LCD screen.
- Expanded memory allows to store measurements (up to 99) and perform addition and subtraction operations.
- Degree of protection IP54.
- Non-slip buttons.
- 1/4"tripod mount.



- DL-X/DL-XG distance meter;
- Case;
- Strap;
- 3 x battery;
- Target plate;
- Operating Manual.





TYPE	DL-40X	DL-60X	DL-80X	DL-100X	DL-50XG	DL-70XG	DL-100XG	
Measuring range 0.05-40 m 0.05-60 m 0.05-80 m 0.05-100 m 0.05-50 m 0.05-70 m 0.05-100 m								
Laser color	red				green			
Resolution	0.001 m					0.001 m		
Accuracy of measurement	± 2 mm				± 2 mm			
Measurement time	0.5 s				0.5 s			
Laser type	635 nm, Class 2, < 1 mW				520 nm, Class 2, < 1 mW			
Power supply	3 x AAA 1.5V batteries				3 x AAA 1.5V batteries			
Battery life	approximately 8 000 measurements				approxim	nately 8 000 me	asurements	
Dimensions		118 mm × 52 mm × 27 mm				nm × 52 mm × 2	27 mm	
Operating temperature	0°C ÷ 40°C					0°C ÷ 40°C		
Storage temperature	-20°C + 60°C					-20°C ÷ 60°C		
Automatic shutdown		laser after 20 s,	rangefinder after	150 s	laser afte	er 20 s, rangefii	nder after 150 s	

CODE	CAT NO.	MODEL
3-01-06-L1-078	PRO-DL078	DL-100X
3-01-06-L1-077	PRO-DL077	DL-80X
3-01-06-L1-076	PRO-DL076	DL-60X
3-01-06-L1-075	PRO-DL075	DL-40X
3-01-06-DL-111	PRO-DL111	DL-100XG
3-01-06-DL-110	PRO-DL110	DL-70XG
3-01-06-DL-109	PRO-DL109	DL-50XG

## **DL-40R WITH MEASURING WHEEL**





- The DL-40R laser distance meter is used for distance measurements up to 40 m.
- Integrated measuring wheel for measuring irregular shapes, circuits.
- Measurement in metric and imperial system.
- Built-in Li-ion battery, micro USB charging cable included.

CODE	CAT NO.
3-01-06-L1-081	PRO-L1081

**DL-20** 



ACCURACY +/- 3MM



MEASUREMENT TIME **0.5s** 



LASER RANGE **20M**  **1** MEASUREMENT REFERENCE POINTS

- The DL-20 laser distance meter is used for distance measurements up to 20 m.
- Measurement in metric and imperial system.
- Battery indicator.

CODE	CAT NO.
3-01-06-L1-088	PRO-DL088





## **FEATURES OF STEEL TAPES**

## HIGHQUALITY TAPES

PRO uses high grade carbon steel ensuring uniform tape thickness throughout. This has been achieved through advanced cold rolling process and heat treatment techniques. The result is very high durability and resistance to kinking and bending

## **ROUND EDGES**

Sharp edges are usually a source of corrosion and rust. All sharp edges of PRO reel tapes are filed to avoid corrosion and cracking. We think about the users by working on even such invisible details.

## NYLON COATING

The nylon coating on the tapes minimizes rapid wear and scratching. Special embossed finish provides better protection

and reduces light reflection. Anti-corrosion layer of the nylon coating protects the entire surface of the tape ensuring long-lasting legibility and high

#### REVERSE BRAKE

The reverse brake is a mechanism that brakes the tape. It adopts an automatic ejector lock. The tape does not retract on its own. The tape is retracted by pressing the brake release button.

## TAPE IMPACT ABSORBER

Built-in tape impact absorber reduces the impact of the tape clip on the cassette during retraction.

## HOOK AND TAPE PROTECTOR

Stainless steel tape clip protected against corrosion. Sliding hitch fully adaptable to internal and external measurements. The stainless steel tape protector prevents the tape from being pulled away and enlarging the holes where the rivets are attached.

## **MAGNETS**

The tape measures with magnets make it easy to take measurements without a second person. Magnets hold the measure firmly on iron and steel surfaces in both horizontal and vertical planes.

The springs were subjected to a fatigue test. The tape was extended 3000 times beyond the measuring range by 1.8 cm without permanent damage to the spring. The metal parts and the tape were placed in 5% NaCl solution for more than two hours. After removing the components

there was no rust found. Drop test from a height of 1.2 m without damage to the function and without change to the shape of the

## ACCURACY

Thanks to their advanced technology, PRO tape measures meet the stringent EC Class I and EC Class II tolerance requirements set by the European System of Weights and Measures. Tolerances were specified at 20° C.

CLASS		1M	2M	3M	5M	8M	10M	20M	30M	50M	100M
I	mm	±0.2	±0.3	±0.4	±0.6	±0.9	±1.1	±2.1	±3.1	±5.1	±10.1
II	mm	±0.5	±0.7	±0.9	±1.3	±1.9	±2.3	±4.3	±6.3	±10.3	±20.3
Ш	mm	±1.0	±1.4	±1.8	±2.6	±3.8	±4.6	±8.6	±12.6	±20.6	±40.6



# **FOLDING MEASURES**

## **PRO MILESTONE**



CODE	CAT NO. LENG	TH TAPE WIDTH
3-01-04-25-603	PRO-MZ183 3 m	16 mm
3-01-04-25-605	PRO-MZ185 5m	25mm
3-01-04-25-608	PRO-M7188 8 m	25 mm







- High tape rigidity for long unsupported reach
- up to 50% of the total length of the measure.
- Ergonomic cassette made of high quality ABS (thermopolymer) with TPR (thermoplastic rubber) coating.
- Shape and marking of the cassette enable length measurement from the rear wall of the tape housing.
- Movable, reinforced tape clip fastened with three rivets.
- The tape measure is equipped with a bumper to absorb the impact of the tape during retraction.
- Durable metal tape clip.
- Graduation in accuracy class II.

#### **PRO MEASURE**

PR-60-01





CODE	CAT NO.	LENGTH	TAPE WIDTH
3-01-04-26-103	PRO-MZ143	3 m	19 mm
3-01-04-26-105	PRO-MZ145	5m	25 mm
3-01-04-26-108	PRO-MZ148	8 m	25 mm

- High tape rigidity for long unsupported overhang, up to 50% of total gauge length.
- Ergonomic cassette made of high quality ABS (thermopolymer) with TPR (thermoplastic rubber) coating.
- Shape and marking of the cassette enable length measurement from the
- wall of the tape housing.
- Modern precision ratchet brake for high ergonomics.
- Movable, reinforced tape clip mounted on three rivets, additionally equipped with two strong magnets, facilitates the use of the measure during work on steel structures.
- The tape measure is equipped with a bumper to absorb the impact of the tape during retraction.
- Durable metal tape clip.
- Graduation in accuracy class II.







CODE	CAT NO.	LENGTH	TAPE WIDTH
3-01-04-25-003	PRO-MZ133	3 m	16 mm
3-01-04-25-005	PRO-MZ135	5m	19mm
3-01-04-25-008	PRO-MZ138	8 m	25 mm

- The measuring tape is equipped with three brakes: top, side and bottom.
- The cassette made of high quality plastic.
- Cassette body with TPR (thermoplastic rubber).
- Movable tape clip mounted on two rivets in 3m, 5m measures (on three rivets in 8m measures).
- The tape measure is equipped with a bumper to absorb the impact of the tape during retraction.
- High tape rigidity for long unsupported overhang, up to 50% of total gauge length.
- Durable steel tape clip and convenient wrist strap.
- Graduation in accuracy class II.

#### **MEASURING TAPE PR-60-02**











CODE	CAT NO.	LENGTH	TAPE WIDTH
3-01-04-25-703	PRO-MZ113	3m	16mm
3-01-04-25-705	PRO-MZ115	5m	25mm
3-01-04-25-708	PRO-MZ118	8m	25mm

- Measuring cassette made of high quality ABS (thermopolymer).
- Additional elements made of TPR (thermoplastic rubber), providing high comfort during work and secure grip.
- The measuring tape is equipped with one clamping brake (top).
- Movable tape clip attached by two or three rivets.
- Durable steel tape clip and convenient wrist strap.
- The measuring tape has a functional hook with a hole for nails and screws.
- Graduation in accuracy class II.

#### **MEASURE PR-70-01 X-ROCKER**



CODE	CAT NO.	LENGTH	TAPE WIDTH
3-01-04-24-905	PRO-MZ905	5 m	32 mm
3-01-04-24-908	PRO-MZ908	8 m	32mm















- Reverse brake the tape is automatically locked when extended.
- Ergonomic metal cassette with stainless steel protective lid.
- Additional TPR (thermoplastic rubber) coating for high comfort while working. Non-slip measuring body.
- Nylon tape protective coating for increased scratch and rust resistance.
- Movable, reinforced tape clip equipped with two strong magnets, mounted on four rivets in 5m, 8m measures (on three rivets in 3m measures).
- The tape measure is equipped with a bumper to absorb the impact of the tape during retraction.
- Highly precise mechanism when the release button is gently moved, the measuring tape is retracted very slowly.
- Durable metal tape clip and convenient wrist strap.
- Graduation in accuracy class II.

#### **MEASURING TAPE PR-60-03**



CODE	CAT NO.	LENGTH	TAPE WIDTH
3-01-04-26-203	PRO-MZ163	3m	16mm
3-01-04-26-205	PRO-MZ165	5m	19mm
3-01-04-26-208	PRO-MZ168	8m	25mm







- Measuring cassette made of high quality ABS (thermopolymer).
- The measuring tape is equipped with two brakes: upper and lower.
- Movable tape clip attached by two or three rivets.
- Durable steel tap clip and convenient wrist strap.
- The measuring tape has a functional hook with a hole for nails and screws
- Graduation in accuracy class II.

## PR-60-05



CODE	CAT NO.	LENGTH	TAPE WIDTH
3-01-04-25-313	PRO-MZ173	3 m	16 mm
3-01-04-25-315	PRO-MZ175	5 m	25mm



REVERSE BRAKE





- Reverse brake the tape automatically locks when extended.
- Ergonomic metal cassette with stainless steel protective lid.
- Additional TPR (thermoplastic rubber) coating for high comfort while working. Non-slip measuring body.
- Nylon tape protective coating for increased scratch and rust resistance.
- Movable, reinforced tape clip equipped with two strong magnets, mounted on four rivets in 5m, 8m measures (on three rivets in 3m measures)
- The tape measure is equipped with a bumper to absorb the impact of the tape during retraction.
- Highly precise mechanism when the release button is gently moved, the measuring tape is retracted very slowly.
- Durable metal tape clip and convenient wrist strap.
- Graduation in accuracy class II.

#### PR-60-06



CODE	CAT NO.	LENGTH	TAPE WIDTH
3-01-04-25-403	PRO-MZ103	3 m	16 mm
3-01-04-25-405	PRO-MZ105	5m	25mm
3-01-04-25-408	PRO-MZ108	8 m	25 mm

- CLASS CLASSIC BRAKE NYLON COAT CASETTE
- Graduated measuring tape in accuracy class I.
- Ergonomic metal cassette with chrome-plated protective coating.
- Additional rubber covering for increased comfort while working.
- Non-slip, chrome-plated measuring tape body.
- Nylon tape protective coating for increased scratch and rust resistance.
- Movable, reinforced hook thickened by 20% attached to the tape with three rivets in the measuring tapes of 3 m, 5 m, 8 m.
- A strong, non-slip brake to ensure the tape is held in the desired position.

KLAISA

- The tape measure is equipped with a bumper to absorb the impact of the tape during retraction.
- Durable metal tape clip.
- Convenient wrist strap.

#### PR-60-10N



CODE	CAT NO.	LENGTH	TAPE WIDTH
3-01-04-25-702	PRO-MZ910	10 m	32 mm



1

- Cassette made of high quality plastic with a touch of TPR (thermoplastic rubber).
  Upper clamping brake.
- Specialized large hook (hole for screws and bolts), fastened with four rivets
- Double sided wide (32mm) nylon coated tape.
- Durable metal tape clip.
- Graduation in accuracy class II.

## PR-60-11



CODE	CAT NO.	LENGTH	TAPE WIDTH
3-01-04-25-623	PRO-MZ193	3 m	16 mm
3-01-04-25-624	PRO-MZ195	5m	19mm
3-01-04-25-625	PRO-MZ196	5 m	25 mm



- Reverse brake the tape automatically locks when extended.
- Ergonomic cassette made of high quality plastic.
- Non-slip measuring body.
- Additional TPR (thermoplastic rubber) covering for high comfort during work.

CLASS

- Nylon tape protective coating for increased scratch and rust resistance.
- Movable, reinforced tape clip mounted on three rivets in 5m, 8m measuring tapes (on two rivets in 3m measuring tapes).
- The tape measure is equipped with a bumper to absorb the impact of the tape during retraction.
- Double-sided printing (scale on both sides of the tape).
- Durable metal tape clip.
- Nail and screw attachment.
- Graduation in accuracy class II.

## PR-40-01



CODE	CAT NO.	LENGTH	TAPE WIDTH
3-01-04-24-103	PRO-MZ123	3m	16mm
3-01-04-24-105	PRO-MZ125	5m	19mm
3-01-04-24-108	PRO-MZ128	8m	25mm







- Ergonomic cassette made of TPR (thermoplastic rubber) material for high comfort during work.
- Two functional brakes: ratchet and bottom brake.
- Shape and marking of the cassette enable length measurement from the rear
- wall of the tape housing.
- Movable reinforced tape clip.
- The measuring tape comes with a bumper to absorb the impact of the tape during retraction.
- Durable metal tape clip.
- Nail and screw attachment.
- Convenient rubber wrist strap.
- Graduation in accuracy class II.

#### PR-60-



CODE	CAT NO.	LENGTH	TAPE WIDTH
3-01-04-26-003	PRO-MZ203	3m	16mm
3-01-04-26-005	PRO-MZ205	5m	19mm
3-01-04-26-006	PRO-MZ206	5m	25mm
3-01-04-26-008	PRO-MZ208	8m	25mm



- Reverse brake the tape is automatically locked when extended.
  Ergonomic cassette made of high quality ABS plastic (thermopolymer).
- Additional non-slip TPR (thermoplastic rubber) covering for high comfort during work.
- Nylon tape protective coating for increased scratch and rust resistance.
- Movable, reinforced tape clip fastened with three rivets in 3 m, 5, and 8 m measuring tapes.
- Durable metal tape clip.
- Convenient wrist strap.
- Nail and screw attachment.
- Scale in accuracy class II.

## PR-45-12



 CODE
 CAT NO.
 LENGTH
 TAPE WIDTH

 3-01-04-26-018
 PRO-MZ902
 2 m
 12.5 mm

CLASS KLASA





TPR

1 BRAKE

- High quality ABS (thermopolymer) cassette with TPR (thermoplastic rubber) finish.
- Upper clamping brake.
- Graduation in accuracy class II.
- Movable tape clip fastened with 3 rivets.
- Single-sided tape (12.5 mm).
- Convenient and compact design with key ring.

## STEEL TAPES

PR-62-01

CODE CAT NO. LENGTH TAPE WIDTH

3-01-04-25-020 PRO-TS020 20m 12.5mm

CLASS

3x FOLDING SPEED

6x

FOLDING SPEED

ABS

NYLON COAT

STEEL TAPE

TPR


STEEL TAPE


- High quality steel tape.
- Coated with a polymer layer to increase the durability of the tape.
- Robust, bolted ABS (thermopolymer) housing with additional TPR (thermoplastic rubber) elements for protection against damage and ensuring a firm grip.
- Modern mechanism with three times the speed of tape retraction.
- Handle retractable in housing.
- Metal measuring clip.
- Graduation in accuracy class II.
- Compliant with the European MID directive.

## PR-63-02



CODE	CAT NO.	LENGTH	TAPE WIDTH
3-01-04-24-040	PRO-MZ040	30m	13mm
3-01-04-24-250	PRO-MZ250	50m	13mm





- The top made of high quality carbon steel covered with a layer of acrylic polymer treated to eliminate the risk of corrosion, rust and cracking.
- Offset by 10cm the beginning of the tape scale.
- Tape equipped with a steel positioning tip, with retracting and extending functionality.
- $\mbox{-}$  Drum construction designed to protect the tape top from damage.
- Durable rubber rollers inside the cassette, guiding the tape top to prevent retracting.

CLASS ||

- Functional belt clip with an anti-slip element.
- Compliant with the European MID directive.

## PR-64-01



CODE	CAT NO.	LENGTH	TAPE WIDTH
3-01-04-25-330	PRO-MZ330	30 m	13 mm
3-01-04-25-350	PRO-MZ350	50m	13mm

- Highly durable housing made of drop resistant ABS
- thermopolymer

   Ergonomic TPR non-slip rubber coated handle provides a secure and comfortable grip
- Double-sided top made of high quality carbon steel, covered with a layer of special nylon, which is characterized by maximum resistance to rust, and various types of acids.
- Tape width 13 mm
- Functional belt clip made of plastic, additionally equipped with a metal hook.
- II accuracy class.
- Compliant with the European MID Directive



PR-62-11



CLASS 3X FOLDING SPEED STEEL TAPE

- High quality steel strap.
- Coated with a polymer layer to increase the durability of the tape.
- Modern mechanism with three times the speed of tape retraction.
- Robust, bolted ABS (thermopolymer) housing with additional TPR (thermoplastic rubber) elements for protection against damage and for a firm grip.
- Handle retractable in housing.
- Metal gauge clip.
- Graduation in accuracy class II.
- Compliant with the European MID directive.

CODE	CAT NO.	LENGTH	TAPE WIDTH
3-01-04-25-120	PRO-MZ120	20 m	19 mm
3-01-04-25-130	PRO-TS030	30 m	19 mm

## **FIBERGLASS TAPES**





3x FOLDING SPEED FIBER-GLASS TAPE

- Ergonomic grip provides a secure and comfortable hold.
- Faultless tape retraction mechanism with flat folding handle.
- Robust and lightweight ABS (thermopolymer) housing with positioning tip for easy measurement.
- Low stretch, high quality fiberglass tape with clear graduations.
- III accuracy class.
- Compliant with the European MID directive.

CODE	CAT NO.	LENGTH	TAPE WIDTH
3-01-04-24-130	PRO-TW030	30m	13mm
3-01-04-24-150	PRO-MZ150	50m	13mm

## PR-63-03



- High quality fiberglass tape.

- Coated with a polymer layer to increase the durability of the tape.

 Robust, bolted ABS (thermopolymer) housing with additional TPR (thermoplastic rubber) elements for protection against damage and for a firm grip.

- Modern mechanism with three times the speed of tape retraction.
- Handle retractable in housing.
- Metal gauge clip.
- Graduation in accuracy class III.
- Compliant with the European MID directive.

CODE	CAT NO.	LENGTH	TAPE WIDTH
3-01-04-24-020	PRO-TW020	20 m	13 mm

PR-64-02





- Three times the winding speed
- Highly durable housing made of drop resistant ABS thermopolymer
- TPR anti-slip rubber coated tape cassette
- Ergonomic handle provides a secure and comfortable grip
- Tape made of high quality glass fibre, low stretch with clear graduations, printed on both sides
- Tape width 15 mm
- Functional tape clip made of plastic, additionally equipped with a metal hook
- II accuracy classThe measure complies with the European MID, PAH and REACH directives

CODE	CAT NO.	LENGTH	TAPE WIDTH
3-01-04-25-430	PRO-MZ430	30 m	15 mm
3-01-04-25-450	PRO-MZ450	50m	15mm



WITH MARKING CHALK AND STRING LEVEL







- Ergonomic housing made of high quality ABS
   / PC along with a rubber cover.
- String length 30m
- A strong cotton/polyester cord ending in a stainless steel hook.
- 3:1 string winding ratio
- Multifunctional string tensioning mechanism
- Includes a 200g container of marker chalk.
- The set includes: a chalk line, 200g chalk and a string level for auxiliary measurements.

CODE	CAT NO.	PRODUCT
3-01-12-27-401	PRO-ST401	chalk line + blue chalk
3-01-12-27-404	PRO-ST404	blue chalk
3-01-12-27-402	PRO-ST402	chalk line + red chalk
3-01-12-27-403	PRO-ST403	red chalk

## FOLDING WOODEN MEASURE

TYP





CODE	CAT NO.	LENGTH	TAPE WIDTH
3-01-04-26-001	PRO-MS001	1 m	16 mm
3-01-04-26-002	PRO-MS002	2 m	16mm

- B1 series folding measures are made of beech wood.
- They have a two-sided scale in millimeters.
- The scale is coated with a layer of water-based paint and a double layer of lacquer resistant to scratches, abrasion, splashes and adverse effects of negative temperatures and UV rays.
- The measure is characterized by rigid, steel, additionally lubricated joints.
- It has ends protected against corrosion with brass coating.
- Steel joints provide a secure and durable connection of the measuring arms.
- Clear graduation in accuracy class III.
- Slats thickness 3,2 mm.
- Top width 16 mm.

## **TYPE B7**





CODE	CAT NO.	LENGTH	TAPE WIDTH
3-01-04-26-011	PRO-MS011	1 m	16 mm
3-01-04-24-150	PRO-MZ150	2 m	16 mm



WATER RESISTANT

- B7 series folding measures are made of beech wood.
- They have a two-sided scale in millimeters.
- The scale is coated with a layer of water-based paint and a double layer of lacquer resistant to scratches, abrasion, splashes and adverse effects of negative temperatures and UV rays.
- They come with plastic joints and ends protected against corrosion with brass coating.
- The hinges are built into the measure profile so that a continuous line can be drawn without any bends.
- A protractor is placed on the extreme joints to angle the arms: 15°, 30°, 45°, 60°, 75° and 90°.
- Clear graduation in accuracy class III.
- Slats thickness 3,2 mm.
- Top width 16 mm.

## FOLDING ABS MEASURE

TYPE B3 ABS





CODE	CAT NO.	LENGTH	TAPE WIDTH
3-01-04-26-031	PRO-MS031	1 m	13 mm
3-01-04-26-032	PRO-MS032	2 m	15 mm

- B3 series folding measures are made of special,
- wear-resistant ABS plastic (thermopolymer).
- They have a two-sided scale in millimeters.
- Possibility to determine an angle of  $90^{\circ}$  arm lock.
- Flexible and elastic ABS (thermopolymer) allowing measurements on arcs and circles.
- The hinges are built into the measure profile so that a continuous line can be drawn without any bends.
- Clear graduation in accuracy class III.
- ABS folding measure 1 m top width 13 mm.
- ABS folding measure 2 m top width 15 mm.



## DIGITAL CALLIPERS

## **CALLIPER IP 54**



TYPE	IP 54 150		IP 54 300 MM
Measurement range:	0 - 150 mm		0 - 300 mm
Resolution:	0.01mm		0.01mm
Accuracy:	± 0.02 mm(<100 mm) ± 0.03 mm (>100-150 mm	n)	± 0.02 mm(<100 mm) ± 0.03 mm (>100-150 mm) ± 0.04 mm (>150-300 mm)
Repeatability of measurement:	± 0.01 mm		± 0.01 mm
Maximum measurement time:	1.5 s		1.5 s
Method of measurement:	linear-capacitive		linear-capacitive
Power supply:	1.5 V battery		
Display:	LCD		LCD
Operating temperature:	0° to 40° C		0° to 40° C
Ambient humidity:	less than 80% with no eff operation of a calliper	fect on	less than 80% with no effect on operation of a calliper
DIMENSIONS [MM]	150	300	

3-01-05-E1-408 PRO-SW408





- The digital caliper is used for internal, external, depth and height measurements.
- A variable reference point allows mixed measurements to be made.
- Dual scale allows measurement in a metric and inch system.
- Guide bar made of high quality stainless steel.
- Metal housing of the digital module.
- Resistant to dust and splashes of water IP 54 rating.

#### SET:

- Digital caliper;
- Functional case;
- Spare battery;
- Operating manual.



BATTERY 1,5 V

## **CALLIPER 007**

DIMENSIONS [MM] Slide Calliper 007

Calliper IP 54



3-01-05-E1-409 PRO-SW409

TYPE	007 150 MM	007 300 MM
Measurement range:	0 - 150 mm	0 - 300 mm
Resolution:	0.01mm	0.01mm
Accuracy:	± 0.02 mm(<100 mm) ± 0.03 mm (>100-150 mm)	± 0.02 mm(<100 mm) ± 0.03 mm (>100-150 mm) ± 0.04 mm (>150-300 mm)
Repeatability of measurement:	± 0.01 mm	± 0.01 mm
Maximum time of measurement:	1.5 s	1.5 s
Method of measurement:	linear-capacitive	linear-capacitive
Power supply:	1.5 V battery	
Display:	LCD	LCD
Operating temperature:	0° to 40° C 0° to 40° C	
Ambient humidity:	less than 80% with no effect on operation of a calliper	less than 80% with no effect on operation of a calliper

3-01-05-E1-407 PRO-SW407 3-01-05-E1-410 PRO-SW410



- The digital caliper is used for internal, external, depth and height measurements.
- A variable reference point allows mixed measurements to be made.
- Dual scale allows measurement in a metric and inch system
- Guide bar made of high quality stainless steel.
- Digital module housing made of plastic.

- Digital caliper;
- Functional case;
- Spare battery;
- Operating manual.



## VERNIER CALLIPERS

## **VERNIER CALLIPER 004**



ТҮРЕ	VERNIER CALLIPER 004 150 MM		VERNIER CALLIPER 300 MM	004
Meas. range:	0 - 150 mm		0 - 300 mm	
Accuracy:	0.02 mm		0.02 mm	
Meas. deviation:	± 0.04 mm (0-200 mm) ± 0.05 mm (200 - 300 mm)		± 0.04 mm (0 ± 0.05 mm (2 mm)	
Method of measurement:	visually		visually	
Operating temperatu	re: all conditions all co	nditions		
Ambient humidity:	without affecting the operation of the calliper		without affecting operation of the	
DIMENSIONS [MM]	150	300		
Slide Calliper 004	3-01-05-E1-415 PRO-SW415	3-01-05 PRO-S	-E1-413 W413	



- Vernier caliper is used for external, internal, depth and mixed measurements.
- Dual scale allows measurement in both metric and inch systems.
- Made entirely of high quality stainless steel.
- All parts hardened.
- Matt chrome plated graduation.
- Vernier length 49 mm with an accuracy of 0.02 mm and 0.001".
- Main scale and vernier in satin chrome.
- The entire caliper body is heat treated.
- Slider that moves when the clamping screw is released.
- Additionally hardened measuring faces.

#### SET:

- Digital caliper;
- Functional case;
- Operating manual.



STAINLESS STEEL

0-300 mm

## **VERNIER CALLIPERS 005**

DIMENSIONS [MM]
Slide Calliper 005



ТҮРЕ	VERNIER CALLIPER 005 150 MM	VERNIER CALLIPER 005 300 MM
weas. range:		
Accuracy:	0.02mm	0.02mm
Meas. deviation:	± 0.04 mm (0-200 mm) ± 0.05 mm (200 - 300 mm)	± 0.04 mm (0-200 mm) ± 0.05 mm (200 - 300 mm)
Method of measurement:	visually	visually
Operating temperatu	re: all conditions	all conditions
Ambient humidity:	without affecting the operation of the calliper	without affecting the operation of the calliper

3-01-05-E1-411 PRO-SW411 3-01-05-E1-414



- Vernier caliper is used for external, internal, depth and mixed measurements.

0-150 mm

- Dual scale allows measurement in both metric and inch systems.
- Made of high quality stainless steel.
- All parts hardened.
- Matt chrome plated graduation.
- Vernier length 49 mm with an accuracy of 0.02 mm and 0.001".
- Main scale and vernier in satin chrome.
- The entire caliper body is heat treated.
- A slider that moves when the automatic brake is released.
- Contact surfaces additionally hardened.

- Digital caliper;
- Functional case;
- Operating manual.



## DIAL CALLIPERS

#### **001 DIAL CALLIPER**



Measurement range:	0 - 150 mm
Accuracy:	0.02mm
Measurement deviation:	± 0.04 mm (0-200 mm) ± 0.05 mm (200-300 mm)
Measurement method: Operating temp:	Visual all conditions

Ambient humidity: no effect on calliper performance

CODE	CAT NO.
3-01-05-E1-016	PRO-SW016

# SHOCK PROOF

0-150 mm SCALE mm inches STAINLESS STEEL

- The dial caliper is used to take external, internal measurements.
- Dual scale allows measurement in both metric and inch systems.
- Made entirely of high quality stainless steel All parts hardened. Matt chrome plated graduation.
- The entire caliper body is heat treated.
- Slider that moves when the clamping screw is released.
- Additionally hardened measuring faces. Made in compliance with DIN 862.

#### SET:

- Clock calliper;
- Functional case;
- Operating manual.



## **BUILDER'S SQUARES**

#### **ALUMINUM BUILDER'S SQUARE WITH BASE**



3-01-05-E1-906	PRO-PK906
CODE	CAT NO.







- Embossed inch scale and conversion table for rafters.
- Protractor 0-90°.
- Can be used as a drafting square for measuring and cutting circular saws.
- Engraved graduations.
- Equipped with a foot for precise positioning of the square in relation to the measured element.

#### Allows:

- Fast and precise drawing of parallel lines.
- Fast determination of 45° and 90° angles.
- Determining angles in the range 0 90°.
- Trimming rafters in roof trusses.
- Setting angles in angle saws.
- Comfortable saw guidance along the arm.

## CARPENTRY SQUARE MADE OF ABS WITH BASE



180 mm




CODE CAT NO.
3-01-05-E1-908 PRO-PK908

- Square made of durable ABS.
- Easy to read tilt angles.
- Conversion tables.
- The base allows for easy marking and cutting.

## **CARPENTRY SQUARE WITH BASE**



0-90°



- Made of aluminum alloy, strong and durable.
- Scale clear, accurate and easy to read.
- The square is perfect for all general construction, carpentry or roofing projects.
- Quickly determines 45° and 90° angles and angles from 0-90°.
- Convenient cutting and trimming in roof trusses possible.
- Can be used as a saw guide for measuring angles and cuts.
- Ergonomic and comfortable design.

CODE	CAT NO.
3-01-05-E1-601	PRO-PK601

## **CARPENTRY SQUARE**









- Perfect for 3D marking, 45 and 90 degree measurement.
- Can be used as an indicator to mark parallel lines.
- With the angle scale, you can find a specific angle and mark it on the wood and quickly trace a dovetail, for example.
- Bright, engraved metric scales that are accurate and easy to read.
- Holes to determine the diameter of a drill bit or screw
- 3D Japanese square is widely used in furniture making, DIY, household, woodworking, by carpenters, roofers or joiners.
- Made of aluminum alloy, wear resistant.
- Ergonomic and comfortable design
- dimensions: 72 x 155 x 215 x 62 mm

CODE	CAT NO.
3-01-05-E1-607	PRO-PK607

## **ALUMINUM ANGLE**











300 mm

400 mm

500 mm



- Carpentry square made entirely of aluminum.
- Square length 250, 300, 400 or 500 mm.
- Durable, strong construction.
- Strong 3-point angle connection.
- The rigid angle section for easier accuracy check of the angle representation.
- Easy to read metric scale.
- Use as 90° and 45° angle.

CODE	CAT NO.	SIZE
3-01-05-E1-510	PRO-PK510	250mm
3-01-05-E1-511	PRO-PK511	300mm
3-01-05-E1-512	PRO-PK512	400mm
3-01-05-E1-513	PRO-PK513	500mm

## **ADJUSTABLE SQUARE**











- Lightweight tool with steel and aluminum structure.
- Cased scriber.
- 1 vial readings visible from all sides.
- Clear and durable graduation scale.
- Metric scale, double-sided.
- The square can be used as an angle gauge, depth and height measuring device.
- Gauge length 300 mm.
- It can measure 90° and 45°.
- The shorter side slides along the scale and can be locked with the built-in knob.
- Thumb screw for adjustment.
- A vial for auxiliary measurements.

CODE	CAT NO.
3-01-05-E1-501	PRO-PK501

#### T-TYPE ADJUSTABLE SQUARE





- T-type square for plasterboards.
- Square length 1200 mm.
- Durable, strong construction.
- Marked angles allow to cut at any angle

CODE	CAT NO.
3-01-05-E1-202	PRO-PK202

#### **CARPENTRY ADJUSTABLE SQUARE**













- Adjustable square with screw for precise angle adjustment.
- Comfortable and ergonomic handle made of durable ABS.
- The gauge is made of SS 201 stainless steel.
- Used in carpentry, roofing and general construction work.

CODE	CAT NO.	SIZE
3-01-05-E1-205	PRO-PK205	200mm
3-01-05-E1-206	PRO-PK206	250mm
3-01-05-E1-207	PRO-PK207	300mm

## **MEASURING DEVICES**

#### ADJUSTABLE TEMPLATE






- Made of durable ABS.
- Measuring dimensions 25 × 12 cm.
- Screws for smooth and precise adjustment.
- Allows to transfer the square to any plane.
- Perfectly adapts to unusual shapes.

CODE	CAT NO.
3-01-05-E1-504	PRO-PK504

#### ADJUSTABLE HEXAGONAL SQUARE WITH SLOTTED HOLES





- Universal template marking tool. Accurately marks the place of the hole to be cut.
- Made of aluminum alloy, strong and durable in use. Scale clear, accurate and easy to read.
- Ideal for precise and accurate measurements. The 6 adjustable arms allow to create a custom template on any surface.
- Diameter (bore gauge): 75mm, 55mm, 45mm, 40mm, 25mm

#### HOW TO USE ?

- Place the tool on any surface and adjust to the desired shape or position to mark the hole location
   Tighten the metal screws to secure the angle.
- 3. Use the shape/desired angle as a template
- 4. Once the template is complete, loosen the screws and fold it.

CODE	CAT NO.
3-01-05-E1-504	PRO-PK504

## **ALUMINUM GAUGE**





- The gauge made of hardened aluminum.
- Measuring scale length 300 mm or 600 mm.
- Millimeter graduation permanently marked in black.
- Chamfered working edge for easy and precise reading.
- Hanging hole.

CODE	CAT NO.	SIZE
3-01-05-E1-221	PRO-PK221	300mm
3-01-05-E1-222	PRO-PK222	600mm

## **MEASURING DEVICES**

### TILE TEMPLATE WITH A MAGNET

250×30 mm 125×30 mm






- The template allows you reflect the shapes easily and transfer them to the workpiece to determine the exact cutting line.
- For easy and accurate reading of shapes and transferring them to the workpiece.
- Designed for easy mapping of the target shape, drawing and cutting out, for example, a semicircle for a pipe or a frame shape.
- A contour-locking mechanism allows safe contour transfer and scribing on the workpiece.
- Durable plastic construction.
- Neodymium magnets allow the contour to be used on steel structures and during sheet metal and ironwork.

CODE	CAT NO.	SIZE
3-01-05-E1-611	PRO-PK611 20	5×30 mm
3-01-05-E1-610	PRO-PK610	125×30 mm

# TEMPLATE FOR CUTTING OUT HOLES







- Made of engineering plastic.
- Two level and verticality vials for auxiliary measurements.
- Precise positioning holes.

CODE	CAT NO.
3-01-26-AG-009	PRO-AG009

### **MEASURING WHEEL "KOJAK"**





9999,9 M





- The measuring wheel is intended to measure length in a straight line and along arc, for outdoor and indoor use.
- A wheel with a diameter 320 mm made of plastic covered with rubber.
- Counter housing made of stainless steel.
- Legs and stand made of carbon steel.
- Measuring range of the wheel 99999,9 m, with a measurement accuracy of 1 cm for every 50 m. The meter has a zero and lock function.
- It comes with a convenient and handy carrying case for easy transport and storage.
- The wheel can be folded.
- Weight: 2 kg.

TYPE	CODE	CAT NO.
Measuring wheel with carrying case	3-01-04-26-102	PRO-KP102
Cover for a measuring wheel	3-01-10-24-100	PRO-KP100



FACHMAYER

## **FOAM GUNS**

The installation foam gun is designed to apply single-component foam available in pressurized containers. The gun makes it easy to do jobs such as:

- sealing, installation of windows and doors,
- filling gaps in insulation,
- sealing and insulating partition walls
- insulation of walls and roofs.

Locking the gun with the flow control knob on the back of the tool, while the foam container is attached, allows the gun to be reused for up to 20 days without cleaning.


#### FOAM GUN BT-01T

- Two-component handle.
- Ergonomic nickel-plated trigger.
- Teflon-coated, brass check valve.
- Teflon-coated copper needle.
- Teflon-coated aluminum adapter.
- Nickel-plated aluminum body.
- Ergonomic adjustment knob. Anti-dry foam system and adjustable spray rate.
- Nozzles for easy work in hard-to-reach places.
- Complete emptying of the foam container.
- No need to clean the gun for up to 20 days.
- Weight: 0.515 kg



#### **FOAM GUN BT-02TDC**

- Very lightweight construction.
- Two-component handle.
- Ergonomic Teflon-coated trigger.
- Teflon-coated, brass check valve.
- Teflon-coated, brass nozzle and needle.
- Teflon-coated aluminum adapter and body.
- Teflon-coated adjustment knob. Anti-dry foam system and adjustable spray rate.
- Nozzles for easy work in hard-to-reach places.
- Complete emptying of the foam container.
- No need to clean the gun for up to 20 days.
- Weight: 0.44 kg



AL ADAPTER CuZn

#### **FOAM GUN BT-03**

- Two-component handle.
- Ergonomic nickel-plated trigger.
- Teflon-coated, brass check valve.
- Teflon-coated, brass needle.
- Aluminum adapter.
- Nickel-plated aluminum body.
- Ergonomic, precise adjustment knob. Anti-dry foam system and adjustable spray rate.
- Nozzles for easy work in hard-to-reach places.
- Complete emptying of the foam container.
- No need to clean the gun.
- No need to clean the gun and adapter for up to 20 days.
- Weight: 0.506 kg.



#### FOAM GUN BT-04TDC-3R

- Teflon-coated body made of aluminum alloy.
- Teflon-coated brass nozzle, needle and check valve.
- Ergonomic Teflon-coated trigger and aluminum alloy Teflon-coated adapter.
- One-component ergonomic handle. Very lightweight construction.
- Teflon-coated precision adjustment sleeve.
- Anti-drying foam system.
- Ability to swivel the nozzle 30° in either direction for easy work in hard to reach areas. Adjustable jet intensity with a knob for onehanded operation.
- Complete emptying of the foam container.
- No need to clean the gun for up to 20 days.
- Weight: 0.505 kg

#### - FOAM GUN BT-05

- One-component handle, ergonomic, nickel-plated trigger.
- Brass check valve. Teflon-coated brass needle.
- Teflon-coated aluminum adapter and powder-coated aluminum body. Ergonomic adjustment knob (SATE).
- Anti-dry foam system and adjustable spray rate.
- Additional bottom adapter to allow operation with large capacity cylinders.
- Complete emptying of the foam container. No need to clean the gun for up to 20 days.
- Comes with a screw and wrench to connect a large capacity foam container
- Weight: 0.70 kg.







NOZZLE

100CM

#### **FOAM GUN BT-06**

- Teflon-coated body made of aluminum alloy. Brass nozzle (length 100cm) and Teflon-coated needle.
- Ergonomic Teflon-coated trigger. Teflon coated, brass check valve. Made of aluminum alloy, Teflon coated adapter. Onecomponent ergonomic handle.
- Very lightweight construction. Teflon-coated precision adjustment
- Anti-drying foam system. Nozzle can be tilted  $30^\circ$  in either direction. Spray rate adjustment.
- Complete emptying of the foam container. No need to clean the gun for up to 20 days. Weight: 0.90 kg



CODE	CAT NO.
3-01-17-00-006	PRO-BT006

#### **FOAM GUN BT-07**

- Easy to use
- Nozzle made of nickel-plated brass (CuZn) and stainless steel (SS)
- Aluminum adapter with Teflon (PTFE) coating.
- Nickel-plated aluminum (AI) body.
- Ergonomic, precise adjustment knob, for 1-hand operation.
- Anti-drying foam system.
- Complete emptying of the foam container.
- Special barrel design to prevent foam from staying on the barrel easy cleaning.
- Weight: 0.455 kg








PTFE



#### **FOAM GUN BT-08T**

- Two-component handle
- Ergonomic nickel-plated trigger.
- Teflon-coated copper check valve and needle
- Aluminum adapter.
- Nickel-plated aluminum body.
- Ergonomic, precise adjustment knob.
- Anti-drying foam system.
- Spray rate adjustment.
- Nozzles for easy work in hard-to-reach places.
- Complete emptying of the foam container.
- No need to clean the gun. Up to 20 days without cleaning the adapter.
- Weight: 0.31 kg.



#### **FOAM GUN BT-09PN**

- Body and handle of structural plastic
- Equipped with a plastic knob that allows to adjust the volume of the foam stream.
- Application for sealing, setting windows, doors, window sills, filling holes, cracks in concrete, masonry, sealing the culverts for water and sewer pipes, etc.
- Weight: 0.195 kg.



## **GLUE GUNS**

- Professional hot melt glue gun.
- Ergonomic housing made of ABS thermopolymer, resistant to high temperatures.
- The gun has a built-in fuse to prevent overheating and burning.
- Thanks to the temperature holding function, the gun draws about 50% less electricity from the mains once it has warmed up.
- Gun warm-up time is 3-5 min.
- The gun is equipped with two feet, one made of ABS plastic and the other made of steel. They allow to safely put the gun down while working.



3-5 min ABS

ø 7mm

CODE	CAT NO.	TYPE
3-01-18-00-01	PRO-GG001	30W 7mm
3-01-18-00-004	PRO-GG004	100W 11mm

### **HOT-MELT TRANSPARENT GLUE**

- Professional hot melt cartridge for glue guns.
- Package contains 10 pieces or 1 kg.
- 7mm or 11mm diameter adhesive.
- Softening point ≥88°C.
- Operating temperature 120-180°C.

CODE	CAT NO.	DIAMETER	NUMBER
3-01-18-00-021	PRO-GS001	7mm	10 pcs
3-01-18-00-022	PRO-GS002	11mm	10 pcs
3-01-18-00-025	PRO-GS005	11mm	1 kg





### **UPHOLSTERY STAPLER**

#### **UPHOLSTERY STAPLER BZ-01W**



1,2 mm











# 0,7

mm



**UPHOLSTERY STAPLER BZ-02W** 





- The upholstery stapler is designed to join elements using staples of different sizes and lengths.
- It is used to fix wood, aluminum, carpet, upholstery, leather, drywall, fiberboard, laminate flooring, MDF, PVC and many other materials.
- 4-in-1 function (4 different types of staples).
- Made entirely of high-grade steel.
- Non-slip grip.
- Adjustment of driving force.
- Anti-jamming system.
- Durable chrome finish.
- Easy and quick staple refill.
- Compatible with G (4/11/140) and J (8/300/E) staples.

- Upholstery stapler is designed to join elements using staples of different sizes and lengths.
- It is used to fix wood, aluminum, carpet, upholstery, leather, drywall, fiberboard, laminate flooring, MDF, PVC and many other materials.
- Made entirely of high-grade steel.
- Non-slip grip.
- Adjustment of driving force.
- Anti-jamming system.
- Durable chrome finish.
- Easy and quick staple refill.
- Compatible with A (5/53/530) staples.

UPHOLSTERY STAPLER TYPE BZ	-01W
Staple length:	4 mm to 14 mm (5/32"-9/16")
For use with:	film, cardboard, paper, fabric, board, etc.
Tray capacity (pcs.):	124
Type of work:	Manual
Type of staples:	rectangular and letter-shaped: T, U, I
Staple thickness / width:	1.2 mm / 10.6 - 11.3 mm
Weight (kg):	0.5
Dimensions L × W × H (mm):	160 × 140 × 27
Force adjustment: adjusting screw	

#### **UPHOLSTERY STAPLER TYPE BZ-02W**

Staple length:	4 mm to 14 mm (5/32"-9/16")
For use with:	film, cardboard, paper, fabric, board, etc.
Tray capacity (pcs.):	124
Type of work:	manual
Staple type:	rectangular
Staple thickness / width:	0.7 mm / 11.3 mm
Weight (kg):	0.5
Dimensions L × W × H (mm):	160 × 140 × 27
Force adjustment: adjusting serous	

#### SET:

- Upholstery stapler;
- Operating manual;
- Staples type I 1.2 × 10 mm 500 pcs;
- Staples type U 6.2 × 12 mm 500 pcs;
- Staples, rectangular 1.2 × 8 mm 500 pcs.



CODE	CAT NO.
3-01-09-7T-001	PRO-B7001

### SET:

- Upholstery stapler;
- Operating manual;
- Square staples 0.7 × 8 mm 3 × 500pcs.



CODE	CAT NO.	
3-01-09-7T-002	PRO-B7002	

### **UPHOLSTERY STAPLER**

#### BZ-04-LD









- Lightweight upholstery stapler designed to join elements with staples of various sizes and lengths.
- Suitable for soft wood, aluminum, plasterboard, MDF, PVC, assembly
- of carpets, rugs, upholstery, leather and many other materials.
- Made of ABS (thermopolymer).
- Durable steel handle.
- Compatible with staples from 6 to 10mm high and 0.7mm thick.
- Includes 800 rectangular staples.
- Easy and quick staple refill.

### UPHOLSTERY STAPLER ABS

#### BZ-05-LD













- The lightweight upholstery stapler is designed to connect elements with staples of different sizes and lengths.
- Suitable for soft wood, aluminum, plasterboard, MDF, PVC, assembly of carpets, rugs, upholstery, leather and many other materials.
- Made entirely of high impact ABS (thermopolymer) that is resistant to damage.
- Equipped with a special belt holder or pocket.
- Compatible with staples from 4 to 8mm high and 0.7mm thick.
- Includes 200 rectangular staples.

UPHOLSTERY STAPLER TYPE BZ-04-LD			
Staple length: from 6 mm to 10 mm			
For use with:	soft wood, aluminum, paper, board		
Tray capacity (pcs.):	100 Tray capacity (pcs.):		
Type of work:	manual		
Staple type: rectangular	Staple type: rectangular		
Staple thickness / width:	0.7mm		
Weight (kg):	0.18		
Dimensions L × W × H (mm):	150 × 185 × 25		

#### UPHOLSTERY STAPLER TYPE BZ-05-LD

Staple length: from 4 mm to 8 mm

For use with: soft wood, aluminum, fabric, board, etc.

100

Type of work: manual

Staple thickness / width: 0.7mm

Weight (kg): 0.26

Dimensions L × W × H (mm): 155 × 95 × 25

#### SET:

- Upholstery stapler;
- Square staples 0.7 mm 800 pcs.

#### SET:

- Upholstery stapler;
- Square staples 0.7 mm 200 pcs.

CODE	CAT NO.
3-01-09-ZT-006	PRO-BZ006

CODE	CAT NO.
3-01-09-ZT-007	PRO-BZ007

### **UPHOLSTERY STAPLER**

#### **BZ-03WHD**

1.2

mm



0.7

mm









### **HAMMER STAPLER**

#### **BZ-10W**

0.7 mm 10 mm







- The upholstery stapler is designed to join elements using staples of different sizes and lengths.
- It is used to work in wood, aluminum and to attach carpets, rugs, upholstery, leather, drywall, fiberboard, MDF, PVC and many other materials.
- 4-in-1 function (4 different types of staples).
- Made entirely of high-grade steel.
- Non-slip grip.
- Adjustment of driving force (switch).
- Anti-jamming system.
- Easy and quick staple refill.
- Compatible with staples from 6 to 14 mm.

- The hammer stapler is designed to join elements using staples of different sizes and lengths.
- It is used to work in wood, aluminum and to attach carpets, rugs, upholstery, leather, drywall, fiberboard, MDF, PVC and many other materials.
- Made entirely of high-grade steel.
- Non-slip, 2-component handle.
- Anti-jamming system.
- Durable chrome finish.
- Easy and quick staple refill.
- Compatible with 0.7mm thick/10mm long rectangular staples.

UPHOLSTERY STAPLER TYPE BZ-03WHD			
Staple length: 6 mm to 14 mm			
For use with:	film, cardboard, paper, fabric, board, etc.		
Tray capacity (pcs.):	124		
Type of work:	manual		
Type of staples:	rectangular and letter-shaped: T, U		
Staple thickness / width:	P: 0.7 - 1.2/ 10.6 - 11.3; T: 2, U: 7.5		
Weight (kg):	0.65		
Dimensions L × W × H (mm):	185 × 110 × 35		
Force control:	switch		

CODE	CAT NO.
3-01-09-ZT-004	PRO-BZ004

ŀ	HAMMER STAPLER TYPE BZ-10W			
	Staple length:	10mm		
	For use with:	film, cardboard, paper,	fabric, board, etc.	
	Tray capacity (pcs.):	100		
	Type of work:	manual		
	Type of staples:	rectangular		
	Staple thickness / width:	0.7 mm / 10 mm		
	Weight (kg):	0.47		
	Dimensions L × W × H (mm):	300 × 30 × 45		
		Force control:	none	

CODE	CAT NO.
3-01-09-ZT-003	PRO-BZ003

### HAMMER STAPLER

BZ-10W-P
























#### RECTANGULAR STAPLES BZZ-P

TYPE	CODE	CAT NO.	LENGTH	DIMENSIONS	Q. IN PCKG
BZZ-P6-10	3-01-09-ZZ-001	PRO-ZZ001	6mm	1.2 × 10.6 × 6	1000
BZZ-P8-10	3-01-09-ZZ-002	PRO-ZZ002	8mm	1.2 × 10.6 × 8	1000
BZZ-P10-10	3-01-09-ZZ-003	PRO-ZZ003	10mm	1.2 × 10.6 × 10	1000
BZZ-P6-11	3-01-09-ZZ-004	PRO-ZZ004	6mm	0.7 × 11.3 × 6	1000
BZZ-P8-11	3-01-09-ZZ-005	PRO-ZZ005	8mm	0.7 × 11.3 × 8	1000
BZZ-P10-11	3-01-09-ZZ-006	PRO-ZZ006	10mm	0.7 × 11.3 × 10	1000
BZZ-P12-11	3-01-09-ZZ-007	PRO-ZZ007	12mm	0.7 × 11.3 × 12	1000
BZZ-P14-11	3-01-09-ZZ-008	PRO-ZZ008	14mm	0.7 × 11.3 × 14	1000

- The hammer stapler is designed to join elements using staples of different sizes and lengths.
- It is used to work in wood, aluminum and to attach carpets, rugs, upholstery, leather, drywall, fiberboard, MDF, PVC and many other materials.
- Upholstery, leather, drywall, fiberboard, MDF, PVC and many other materials.
- Non-slip, 2-component handle.
- Anti-jamming system.
- Durable chrome finish.
- Easy and quick staple refill.
- Compatible with rectangular staples 1.2mm thick / 10mm long.

#### **UPHOLSTERY STAPLER TYPE BZ-01W**

Staple length:	from 6 mm to 10 mm
For use with:	soft wood, aluminum, paper, board
Tray capacity (pcs.):	100
Operation type:	manual BZZ-T14
Staple type:	rectangular
Staple thickness / width:	1.2 / 10 mm
Weight (kg):	0.18
Dimensions L × W × H (mm):	150 × 185 × 25
Force adjustment:	no

CODE	CAT NO.
3-01-09-ZT-005	PRO-BZ005

#### STAPLES TYPE U BZZ-U

TYPE	CODE	CAT NO.	LENGTH	Q. IN PCKG
BZZ-U12-6	3-01-09-ZZ-009	PRO-ZZ009	12mm	1000
BZZ-U14-6	3-01-09-ZZ-010	PRO-ZZ010	14mm	1000
BZZ-U12-7.5	3-01-09-ZZ-013	PRO-ZZ013	12mm	500

#### STAPLES TYPE T BZZ-T

TYPE	CODE	CAT NO.	LENGTH	Q. IN PCKG
	3-01-09-ZZ-011	PRO-ZZ011	14mm	1000

#### STAPLES TYPE I BZZ-I

TYPE	CODE	CAT NO.	LENGTH	Q. IN PCKG
BZZ-I14	3-01-09-ZZ-012	PRO-ZZ012	14mm	1000

## **LEVER RIVETER**



CODE 3-01-19-NT-103

PRO-NT103

STEEL HANDLE

CrMo JAWS

2.4-6.4 mm

300mm

- The two-handed riveter is designed for service work, mainly for joining together profiles made of different materials.
- It has a patented, very robust and strong design made of aluminum, while the handle is made of carbon steel.
- The shock-resistant design eliminates vibration on the handle from the impact created when a rivet breaks.
- Three-piece puller jaws made of CrMo chrome molybdenum alloy steel for long service life.
- The special feature is the way of fixing the rivets and the easy resizing of the fixing heads, which does not require additional wrenches.
- Ergonomic handle with 3 mm wall thickness for easy handling and
- Handle with double hinges to increase leverage during rivet
- Maximum working stroke 9 mm, effective stroke 7 mm.
- Designed for large range of breakout rivets from 2.4 to 6.4 mm.
- Equipped with five types of tips, selected according to the type of rivets: 2.4 (3/32"); 3.2 (1/8"); 4.0 (5/32"); 4.8 (3/16"); 6.4 (1/4").
- Works with rivets made of stainless steel, steel, copper and
- The broken rivet pins go into a container between the riveting machine arms.
- Weight 1,200 g

### RIVET NUT DRIVER



CAT NO. 3-01-19-NT-105 PRO-NT105

STEEL HANDLE

M3, M4 M5, M6

200mm

- One-handed riveting machine with four adapter sets for each
- It has a patented, very robust and strong design made of aluminum, while the handle is made of carbon steel, which saves 20% of energy during operation.
- Shockproof design eliminates vibration on the handle from the impact created during work.
- For crimping the threaded sleeve on thin-walled parts with simultaneous joining.
- Ergonomic handle with 2.5 mm wall thickness for easy handling and extended life.
- Maximum working stroke 9 mm, effective stroke 7 mm.
- Equipped with four types of tips, selected according to the size of the rivet nuts: M3, M4, M5, M6.
- Weight 500.

## **HAND RIVETER**



3 CrMo JAWS

260

mm

(mm)

2,4; 3,2; 4,0; 4,8

200m

- The hand riveter is designed for service work, mainly for joining together profiles made of different materials.
- It has a patented solid aluminum structure and a carbon steel handle.
- The shock-resistant design eliminates vibration on the handle from the impact created when a rivet breaks.
- Three-piece puller jaws made of CrMo chrome molybdenum alloy steel for long life.
- An ergonomically designed handle with 2.5 mm wall thickness for easy handling and extended life.  $\,$
- Maximum working stroke 7 mm, effective stroke 5-6 mm.
- Designed for large range of breakout rivets from 2.4 to 4.8 mm.
- The small size of the riveter allows it to be used in hard to reach places.
- Equipped with four types of tips, selectable depending on the type of rivet: 2.4 (3/32"); 3.2 (1/8"); 4.0 (5/32");
- Works with rivets made of stainless steel, steel, copper and aluminum.
- Weight 500 g

AL BODY

HAND RIVETER

CODE

3-01-19-NT-001



CAT NO. PRO-NT001

CODE CAT NO. 3-01-19-NT-102 PRO-NT102

2.4-AL BODY STEEL HANDLE 4.8

- The hand riveter is designed for service work, mainly for joining together profiles made of different materials.
- It has a solid structure made of aluminum, while the handle is made of carbon steel.
- The shock-resistant design eliminates vibration on the handle from the impact created when a rivet breaks.
- Three-piece puller jaws made of CrMo chrome molybdenum alloy steel for long life.
- An ergonomically designed handle with 2.5 mm wall thickness for easy handling and extended life.
- Maximum working stroke 7 mm, effective stroke 5-6 mm.
- Designed for large range of breakout rivets from 2.4 to 4.8 mm.
- The small size of the riveter allows it to be used in hard to reach places.
- Equipped with four types of tips, selectable depending on the type of rivet: 2.4 (3/32"); 3.2 (1/8"); 4.0 (5/32"); 4.8 (3/16").
- Works with rivets made of stainless steel, steel, copper and aluminum.
- Weight 500 g

**BLIND RIVETS** 





50 PCS.

- Made of aluminum.
- Packaging with 50 pieces.

TYPE	CATALOG NUMBER	CAT NO.	DIMENSIONS	QUANTITY IN PACKAGING
BII-32-064	3-01-19-NI-001	PRO-NT011	3.2 × 6.4	50
BII-40-096	3-01-19-NI-002	PRO-NT012	4.0 × 9.6	50
BII-40-127	3-01-19-NI-003	PRO-NT013	4.0 × 12.7	50
BII-48-096	3-01-19-NI-004	PRO-NT004	4.8 × 9.6	50
BII-48-127	3-01-19-NI-005	PRO-NT005	4.8 × 12.7	50

### **CAULKING GUNS**

#### **PLASTIC CAULKING GUN BW-1P**











- Very strong and lightweight structural plastic.
- Ergonomic, soft and comfortable handle.
- Hardened piston.
- Knife for opening the tray
- Thruster pin.
- For lightweight materials.
- The no-drip system

#### **INDUSTRIAL PLASTIC CAULKING GUN BW-2P**









- Very strong and lightweight structural plastic.
- Ergonomic, soft and comfortable handle.
- Hardened piston.
- For light compounds (silicones, acrylics).

#### **CAULKING GUN BW-071HD**









310 ml

- Durable aluminum alloy body structure.
- Reinforced aluminum alloy cap.
- Perfectly fitted trigger mechanism. Ergonomic aluminum handle.
- Rotating bearing. Round piston cross-section.
- Overall length 350 mm (with retracted piston). For use with 300 ml containers
- Weight 577 g

#### **CAULKING GUN BW-072HD**











- Durable aluminum alloy body structure.
- Reinforced aluminum alloy cap.
- Perfectly fitted trigger mechanism. Ergonomic aluminum handle.
- Rotating bearing. Round piston cross-section.
- Overall length 490 mm (with retracted piston). For use with 600 ml containers.

А3

- Weight 680 g

#### INDUSTRIAL PLASTIC TUBE CAULKING GUN BW-71P











- Durable structure made of PA6+30%GF plastic.
- Caps made of aluminum.
- Piston made of A3 galvanized steel.
- Built-in dispenser cutter and needle for tray unclogging.
- Tray capacities up to 600 ml.

### CYLINDRICAL CAULKING GUN

#### **CAULKING GUN BW-01**











- Steel body.
- Gear ratchet mechanism.
- Circular piston section.
- Thruster pin.
- Handle covered with non-slip material.
- Overall length 350 mm (with retracted piston).
- For use with 300 ml containers.
- Weight 520 g

### SKELETON CAULKING GUN








#### **CAULKING GUN BW-02**



- Steel body.
- Ratchet mechanism.
- Hexagonal piston cross-section.
- Overall length 350 mm (with retracted piston).
- For use with 300 ml containers.
- Weight 297 g

#### **CAULKING GUN BW-03**
















- Ratchet mechanism with drip protection.
- Hexagonal piston cross-section.
- Overall length 350 mm (with retracted piston).
- For use with 300 ml containers.
- Weight 395 g

#### **CAULKING GUN BW-04**

3-01-15-01-403









- Steel body, reinforced.
- Ratchet mechanism.
- Hexagonal piston cross-section.
- Thruster pin.
- Overall length 350 mm (with retracted piston).
- For use with 300 ml containers.
- Weight 375 g

### **CAULKING GUNS FOR MODELING PASTES**



#### **CAULKING GUN BW-05**



- Durable, reinforced body structure.
- Perfectly fitted trigger mechanism.
- Ergonomic aluminum handle.
- Steel piston and rotating bearing.
- Round piston cross-section.
- Thruster pin.
- Overall length 350 mm (with retracted piston).
- For use with 300 ml containers.
- Weight 640 g

#### **CAULKING GUN BW-06**





- Durable body structure.
- Perfectly fitted trigger mechanism.
- Ergonomic aluminum handle.
- Steel piston and rotating bearing.
- Round piston cross-section.
- Thruster pin.
- Overall length 350 mm (with retracted piston).
- For use with 300 ml containers.
- Weight 560 g

### CYLINDRICAL CAULKING GUNS



CODE



- ø55
- 360 mm

380 ml

- Reinforced steel body.
- Double guide for precise piston guidance.
- Wide piston pusher to handle dense materials.
- Ergonomic piston grip.
- Piston lock.
- Aluminum alloy handle.
- Total length 360mm (with piston inserted).
- For use with containers up to 380ml.
- Piston diameter 55mm

#### **CAULKING GUN BW-08**









- Reinforced steel body.
- Double guide for precise piston guidance.
- Wide piston pusher to handle dense materials.
- Ergonomic piston grip.
- Piston lock.
- Aluminum alloy handle.
- Overall length 360 mm (with retracted piston).
- For use with 300 ml containers.
- Standard piston diameter
- Weight 892 g

#### **CAULKING GUN BW-10B**



310 ml



- Durable body structure.
- Perfectly fitted trigger mechanism.
- Durable trigger mechanism 1 cm thick.
- Ergonomic aluminum handle.
- Steel piston and rotating steel bearing.
- Round piston cross-section.
- Overall length 365 mm (with retracted piston).
- For use with containers up to 310ml.

#### **CAULKING GUN BW-11BHD**









- Reinforced AM60 lightweight magnesium steel body and handle.
- A piston coupled to a guide to stabilize the tray.
- Hardened piston and heavy duty 9mm trigger mechanism.
  Ergonomic piston and stabilizer grip.
- Piston lock.
- Overall length 360 mm (with retracted piston).
- For use with containers up to 345ml.

### **APPLICATOR TIP FOR CAULKING GUN BWK-07**



- Replacement tip for sealant caulking guns.

REPAIR KIT FOR HD TUBE CAULKING GUNS







The repair kit includes: aluminum cap, plastic pressure plate, application tip.

CODE CAT NO. 3-01-15-01-421 PRO-BW421

08





# STIRRERS FOR PAINTS, MORTARS, PLASTERS, COMPOUNDS







#### STIRRER BX-01



- Double helix stirrer, for heavy and dense materials.
- M14 thread attachment.
- Aeration stirrer.

TYPE	BX-01-04	BX-01-05
length	600mm	600mm
diameter	120mm	135mm
material amount	15-25kg	15-30kg
code	3-01-15-00-101	3-01-15-00-102
CAT NO.	PRO-BX101	PRO-BX102

#### STIRRER BX-02









- Double helix stirrer for paints, mortars and mixtures.
- Hex mount.
- Aeration stirrer.

TYPE	BX-02-02	BX-02-03
length	400mm	400mm
diameter	70mm	90mm
material amount	5-10kg	5-10kg
code	3-01-15-00-103	3-01-15-00-104
CAT NO.	PRO-BX103	PRO-BX104

#### STIRRER BX-03









- Spiral stirrers for paints, gypsum, plaster and mortar.
- Hex mount.
- Aeration mixer.

TYPE	BX-03-01	BX-03-02	BX-03-03
length	320 mm	400 mm	500 mm
diameter	60mm	80mm	90mm
material amount	4-7kg	4-9kg	6-18kg
code	3-01-15-00-105	3-01-15-00-106	3-01-15-00-107
CAT NO.	PRO-BX105	PRO-BX106	PRO-BX107

#### STIRRER BX-05









- Basket stirrer with stiffening, for paints, varnishes and mortars.
- Hex mount.
- It does not aerate the materials.

TYPE	BX-05-03
length	600 mm
diameter	100mm
material amount	10-25kg
code CAT NO.	3-01-15-00-109 PRO-BX109

#### STIRRER BX-06









- Basket stirrer for paints, gypsum, screed and mortar.
- Hex mount.
- The stirrer does not aerate the materials.

TYPE	BX-06-01	BX-06-02	BX-06-03		
length	400 mm 470 mm				
diameter	60mm	80mm	100mm		
material amount up to 5kg 10-20kg 10-20kg					
code CAT NO.	3-01-15-00-110 PRO-BX110	3-01-15-00-111 PRO-BX111	3-01-15-00-112 PRO-BX112		

#### STIRRER BX-07









- Double helix stirrer for mortar and grout.
- SDS mount.
- Aeration stirrer.

TYPE	BX-07-02	BX-07-03	BX-07-04
length	400 mm	600 mm	600 mm
diameter	80mm	100mm	120mm
material amount	5-10kg	10-20kg	15-25kg
code	3-01-15-00-114	3-01-15-00-115	3-01-15-00-116
CAT NO.	PRO-BX114	PRO-BX115	PRO-BX116

#### STIRRER BX-08









- Basket stirrers for adhesives and plaster.
- SDS mount.
- It does not aerate the materials.

TYPE	BX-08-01	BX-08-02	BX-08-03
length	400mm	400mm	400mm
diameter	60mm	80mm	100mm
material amount	5-10kg	10-20kg	10-20kg
code	3-01-15-00-117	3-01-15-00-118	3-01-15-00-119
CAT NO.	PRO-BX117	PRO-BX118	PRO-BX119

#### STIRRER BX-09









- Paint stirrer.
- Galvanized.
- Fixed by a round bar φ 6.
- Aeration stirrer.

TYPE	BX-09-01	BX-09-02	BX-09-03
length	320 mm	400 mm	500 mm
diameter	60mm	80mm	100mm
material amount	up to 5kg	5-10kg	10-25kg
code	3-01-15-00-121	3-01-15-00-122	3-01-15-00-123
CAT NO.	PRO-BX121	PRO-BX122	PRO-BX123

#### TROWELS


- Trowels are constructions tools used to apply and spread mortar.
- They can also be used during manual plastering to spread mortar.
- There are triangular trowels, trapezoidal trowels and stucco trowels for specialized, precision work such as grouting or filling joints in brick.

#### CHARACTERISTICS OF A GOOD PRO TROWEL

- PRO trowels are made of hardened steel and stainless steel
- They have an electroplated cap.
- Perfect welding ensures a molded, closed joint between the top and handle for maximum loads and unlimited life.
- Correct positioning of the handle relative to the top ensures optimal functionality.
- Trowels are manufactured in accordance with DIN 6440, DIN 6441, DIN 6397 and DIN 7253.

#### HIGH QUALITY MARK

- Stainless steel top and bail, clean welded, 0.7mm and 1mm thick.
- Glossy top layer.
- Special round weld.
- Galvanized cap on top.
- Blue metallic coated hardwood handle or 2-component handle
- Steel top, oil-hardened and elastically ground, bail and top cleanly welded, 1.4 mm thick.
- Bail and top finished with a special round weld.
- Galvanized cap.
- Blue metallic coated hardwood handle or 2-component handle.







WOOD

0,7

CODE	CAT NO.	HANDLE	DIMENSIONS	TOP THICKN.
3-01-07-01-000	PRO-BK000	wood	100 × 60 mm	0.7mm
3-01-07-01-001	PRO-BK001	wood	128 × 80 mm	0.7mm
3-01-07-01-002	PRO-BK002	wood	128 × 100 mm	0.7mm
3-01-07-01-003	PRO-BK003	wood	128 × 120 mm	0.7mm



C	ODE	CAT NO.	HANDLE	DIMENSIONS	TOP THICKN.
	3-01-07-01-004	PRO-BK004	wood	125 × 80 mm	1.4mm
	3-01-07-01-005	PRO-BK005	wood	125 × 100 mm	1.4mm
	3-01-07-01-006	PRO-BK006	wood	125 × 120 mm	1.4mm







CODE	CAT NO.	HANDLE	DIMENSIONS	TOP THICKN.
3-01-07-01-011	PRO-BK011	2-component	125 × 80 mm	1.4mm
3-01-07-01-012	PRO-BK012	2-component	125 × 100 mm	1.4mm
3-01-07-01-13	PRO-BK013	2-component	125 × 120 mm	1.4mm





2 COMPONENT

CODE	CAT NO.	HANDLE	DIMENSIONS	TOP THICKN.
3-01-07-01-14	PRO-BK014	wood	140 x100×70 mm	1mm
3-01-07-01-015	PRO-BK015	wood	160×115×75 mm	1mm
3-01-07-01-016	PRO-BK016	wood	180×120×80 mm	1mm





WOOD

CODE	CAT NO.	HANDLE	DIMENSIONS	TOP THICKN.
3-01-07-01-017	PRO-BK017	wood	160 × 115 × 75 mm	1.4 mm
3-01-07-01-018	PRO-BK018	wood	180 × 120 × 80 mm	1.4mm

### TRAPEZOIDAL BRICK TROWELS

PRO-BK019, PRO-BK020







CODE	CAT NO.	HANDLE	DIMENSIONS	TOP THICKN.
3-01-07-01-019	PRO-BK019	2-component	160 × 115 × 75 mm	1 mm
3-01-07-01-020	PRO-BK020	2-component	180 × 120 × 80 mm	1mm

CAT NO.

PRO-BK021

PRO-BK022 wood

3-01-07-01-021

3-01-07-01-022





DIMENSIONS

180 × 170 mm



TOP THICKN.
1.4mm

220 × 210 mm 1.4mm

## FLOATS

- Smooth trowels with a metal top are used for application of plaster, e.g. gypsum plaster, adhesives (carpet, nonwoven, cork flooring, styrofoam insulation). Come with a stainless steel top with 2-component and wooden handle.
- Top thickness 0,6mm or 0,7mm.
- Structure floats are used for grinding, smoothing, applying and floating of plasters, finishing coats, mortars and adhesives.
- Floats are used for applying and spreading floor and wall covering adhesives, as well as tiles. Teeth sizes 6x6, 8x8 are used for smaller tiles, while 10x10 are used for large tiles with side lengths over 30 cm.
- Floats with sponge or special rubber backing are used for tiling work, and can also be used for plastering work.
- The floats are manufactured in accordance with DIN 6440, DIN 6441, DIN 6397 and DIN 7253.

## PLASTER FLOATS



- For the application of gypsum plaster and mortars and adhesives.
- Working part made of stainless steel.
- Ergonomic wooden or two-component handle.

CODE	CAT NO.	HANDLE	DIMENSIONS	TOP THICKN.
3-01-07-01-100	PRO-PC100	wood	280 × 130mm	0.7mm
3-01-07-01-104	PRO-PC104	2-component	280 × 130 mm	0.7mm

PRO-PC101, PRO-PC102, PRO-PC103, PRO-PC105, PRO-PC106, PRO-PC107, PRO- PC324, PRO-PC327





- For applying and spreading adhesive mortars.
- Various tooth dimensions.
- Working part made of stainless steel.
- Ergonomic wooden or two-component handle.



CODE	CAT NO.	HANDLE	DIMENSIONS	TOP THICKN.
3-01-07-01-101	PRO-PC101	wood	280 × 130mm 6 × 6mm	0.7mm
3-01-07-01-102	PRO-PC102	wood	280 × 130mm 8 × 8mm	0.7mm
3-01-07-01-103	PRO-PC103	wood	280 × 130mm 10 × 10mm	0.7mm
3-01-07-01-105	PRO-PC105	2-component	280 × 130mm 6 × 6mm	0.7mm
3-01-07-01-106	PRO-PC106	2-component	280 × 130mm 8 × 8mm	0.7mm
3-01-07-01-107	PRO-PC107	2-component	280 × 130mm 10 × 10mm	0.7mm
3-01-07-01-324	PRO-PC324	wood	280 × 130mm 12 × 12mm	0.7mm
3-01-07-01-327	PRO-PC327	2-component	280 × 130mm 12 × 12mm	0.7mm

PRO-PC011, PRO-PC112, PRO-PC114, PRO-PC115, PRO- PC116





- For the application of gypsum plaster, adhesives and mortars and insulation work.
- Various teeth dimensions. - Working part made of stainless steel.
- Beechwood handle.



CODE	CAT NO.	HANDLE	DIMENSIONS	TOP THICKN.
3-01-07-01-111	PRO-PC111	wood	380 × 130mm 8 × 8mm	0.7mm
3-01-07-01-112	PRO-PC112	wood	380 × 130mm 10 × 10mm	0.7mm
3-01-07-01-114	PRO-PC114	wood	480 × 130mm 8 × 8mm	0.7mm
3-01-07-01-115	PRO-PC115	wood	480 × 130mm 10 × 10mm	0.7mm
3-01-07-01-116	PRO-PC116	wood	580 × 130 mm	0.7mm

PRO-PC110, PRO-PC113



###ODD

- For the application of gypsum plaster, adhesives and mortars and insulation work.
- Working part made of stainless steel.
- Beechwood handle.



CODE	CAT NO.	HANDLE	DIMENSIONS	TOP THICKNESS
3-01-07-01-110	PRO-PC110	wood	380 × 130 mm	0.7 mm
3-01-07-01-113	PRO-PC113	wood	480 × 130 mm	0.7 mm

## SMOOTH FLOATS





HYBRO RUBBER

HYDRO SPONGE

HYDRO SPONGE

CUT

#### PRO-PC209



- For gypsum stucco.
- Rounded corners with curved edges.
- Working part made of stainless steel with low carbon content.
- Does not leave streaks while working.
- Ergonomic two-component handle on aluminum foot.

CODE	CAT NO.	HANDLE	DIMENSIONS	TOP THICKNESS
3-01-07-01-209	PRO-PC209	2-component	240 mm	0,7 mm

### PLASTIC FLOATS







- Plastic float.
- Ergonomic 2-component handle.
- Hydrorubber top for floating wet stucco.

CODE	CAT NO.	UNDERCOAT	DIMENSIONS
3-01-07-01-317	PRO-PC317	hydrorubber	280 × 140 × 8 mm
3-01-07-01-318	PRO-PC318	hydrorubber	280 × 140 × 18 mm

#### PRO-PC319





- Plastic float.
- Ergonomic 2-component handle.
- Top with sponge for increased water absorption.
- For rinsing tiles after grouting.

CODE	CAT NO.	UNDERCOAT	DIMENSIONS
3-01-07-01-319	PRO-PC319	hydrosponge	280 × 140 × 30 mm

#### PRO-PC320





- Plastic float.
- Ergonomic 2-component handle.
- Top with sponge for increased water absorption.
- For rinsing tiles after grouting.
- Thanks to the notches, it collects dirt from the cleaned surface more efficiently.

CODE	CAT NO.	UNDERCOAT	DIMENSIONS
3-01-07-01-320	PRO-PC32	0 hydrosponge cut	280 × 140 × 30mm

#### PRO-PC321







- Plastic float.
- Ergonomic 2-component handle.
- Top with dense sponge with small pores for rinsing tiles after grouting.

CODE	CAT NO.	UNDERCOAT	DIMENSIONS
3-01-07-01-321	PRO-PC321 white sponge 280 x 140 x		140 × 25 mm

#### PRO-PC322







- Plastic float.
- Ergonomic 2-component handle.
- Black rubber top does not crumble or stain the joints.
- Designed for grouting ceramic tiles.

CODE	CAT NO.	UNDERCOAT	DIMENSIONS
3-01-07-01-322	PRO-PC322	rubber	280 × 140 × 8 mm

#### PRO-PC323







- Plastic float.
- Ergonomic 2-component handle.
- Work surface with high quality felt does not swell or delaminate.
- For floating cement-lime plasters.

CODE	CAT NO.	UNDERCOAT	DIMENSIONS
3-01-07-01-323	PRO-PC323	felt	280 × 140 × 10 mm

#### PRO-PC325







- ABS plastic trowel increased durability of the working part.
- Top thickness: 3 mm.
- Ergonomic, contoured and balanced handle.
- For floating and texturing of structural plasters.

CODE	CAT NO.	UNDERCOAT	DIMENSIONS
3-01-07-01-325	PRO-PC325	ABS	280 × 140 × 3 mm

### PROFI JOINTING FLOAT WITH RUBBER







#### PRO-PC31



- Plastic float.
- Ergonomic 2-component handle.
- Replaceable rubber insert.
- Rubber beveled on the sides at different angles for more accurate grout filling in hard-to-reach areas.
- The float is designed for grouting with cement and epoxy grouts.

CODE	CAT NO.	DIMENSIONS
3-01-07-01-137	PRO-PC137	250 × 95 mm

#### PROFI STYROFOAM FLOAT







- PROFI styrofoam floats designed for smoothing and leveling plaster.
- Made of hard material, long service life and abrasion resistance .

CODE	CAT NO.	HANDLE	DIMENSIONS
3-01-07-01-126	PRO-PC126	styrofoam	270 × 130 mm
3-01-07-01-127	PRO-PC127	styrofoam	320 × 130 mm
3-01-07-01-128	PRO-PC128	styrofoam	450 × 130 mm
3-01-07-01-129	PRO-PC129	styrofoam	600 × 130 mm
3-01-07-01-130	PRO-PC130	styrofoam	750 × 130 mm
3-01-07-01-131	PRO-PC131	styrofoam	900 × 130 mm

### **BUTTERFLY SANDING FLOAT**







- Butterfly sanding float 215 × 100 mm.
- Allows sanding of all surfaces, designed for papers, abrasives and grids.
- Rubber backing thickness 3 mm.
- The sanding grid is mounted with thumb screws.

CODE	CAT NO.	UNDERCOAT	DIMENSIONS
3-01-07-01-132	PRO-PC132	rubber	210 × 100 mm

## VELCRO SANDING FLOAT









- Plastic float.
- Ergonomic two-component handle prevents hand fatigue.
- Quick and easy sanding paper attachment with Velcro.
- Trowel designed for grinding and smoothing plaster surfaces.
- Quickly and effectively removes excess sanding material.

CODE	CAT NO.	DIMENSIONS	
3-01-07-01-326	PRO-PC326	98 × 225 mm	

### STYROFOAM RASP FLOAT









- Styrofoam rasp floats.
- Scraper for trimming, scraping, shaping, smoothing styrofoam boards.
- Working part made of galvanized sheet metal with holes

CODE	CAT NO.	DIMENSIONS
3-01-07-01-133	PRO-PC133 270 mm	
3-01-07-01-134	PRO-PC134	400mm

### PROFI POLYSTYRENE RASP FLOAT







- Plastic: PS polystyrene.
- Working part made of galvanized sheet metal.
- Ergonomic, two-component (G-16) and contoured handle.
- The pass-through working part ensures easy cleaning and longer tool life.
- For thermal insulation works, e.g. leveling of styrofoam boards.

CODE	CAT NO.	DIMENSIONS
3-01-07-01-136	PRO-PC136	375 mm

### METAL SCRAPER FLOAT FOR PLASTER









- Metal scraper float for plaster.
- Designed for leveling or stripping lime and gypsum plaster and old paint coatings.
- Ergonomic two-component handle.

CODE	CAT NO.	DIMENSIONS
3-01-07-01-135	PRO-PC135	270 × 130 mm

## PROFI PAINT TROWELS











- Stainless steel trowels.
- Used for basic construction and finishing works.

CODE	CAT NO.	SIZE
3-01-07-01-204	PRO-PC204	40mm
3-01-07-01-205	PRO-PC205	60mm
3-01-07-01-206	PRO-PC206	80mm
3-01-07-01-207	PRO-PC207	100mm

### PROFI FACADE TROWELS







- Stainless steel facade trowels.
- Aluminum, rubber grip.
- Thanks to the aluminum guide it is used for plastering.
- Perfectly straight working part , "wiping" evenly during the work.

CODE	CAT NO.	SIZE
3-01-07-01-216	PRO-PC216	250/60mm
3-01-07-01-220	PRO-PC220	350/60mm
3-01-07-01-224	PRO-PC224	450/60mm
3-01-07-01-228	PRO-PC228	550/60mm

### **SCREED TROWELS WITH KNIFE**

PVC

0.35 mm





#### SCREED TROWELS

KNIVES	FOR	SCREED	FLOATS

CODE	CAT NO.	SIZE			
OODL	OAT NO.	OILL	CODE	CAT NO.	SIZE
3-01-07-01-401	PRO-PC401	25cm	3-01-07-01-411	PRO-PC411	25cm
3-01-07-01-402	PRO-PC402	40cm	3-01-07-01-412	PRO-PC412	40cm
3-01-07-01-403	PRO-PC403	60cm	3-01-07-01-413	PRO-PC413	60cm
3-01-07-01-404	PRO-PC404	80cm	3-01-07-01-414	PRO-PC414	80cm
3-01-07-01-405	PRO-PC405	100cm	3-01-07-01-415	PRO-PC415	100cm
3-01-07-01-406	PRO-PC406	120cm	3-01-07-01-416	PRO-PC416	120cm

- Lightweight and ergonomic design of durable PVC.
- The 0.35mm thick stainless steel blade is flexible and makes it easy to apply smoothing compounds. In addition, the rounded corners of the blade ensure fast work without scratching the surface. The blades can be conveniently replaced with new ones by removing the screws and sliding out the side protection.
- The trowels can be equipped with a special telescopic extension, which is perfect for luting higher surfaces, e.g. ceilings. Each blade is protected with an individual shield.

### THREADED TROWEL HOLDER



- Adapter for PRO plastering trowel.
- Made of durable plastic.
- Quick adjustment of the working
- Simple installation to the trowel.

CODE	CAT NO.
3-01-07-01-430	PRO-PC430

M18

# TELESCOPIC POLE WITH



M18 1.16- 2.0
------------------





CODE	CAT NO.
3-01-07-01-431	PRO-PC431

- The telescopic pole is made of aluminum alloy, it is durable and lightweight.
- The telescopic pole consists of 2 parts and can be extended to 2.0 m.
- The pole has an ergonomic soft grip for comfortable and safe
- Telescope wall thickness 1.0mm, 2 telescopic extension pieces with diameters of 26mm and 32mm

### PENCILS FOR VARIOUS SURFACES

- The color of the pencil indicates what type of surface it is
- intended for:
- red carpenter pencil,
- green stone pencil,
- yellow pencil for glass and metal,
- blue pencil for wet surfaces.
- PRO pencils are made of linden wood, characterized by lightness, softness and cleavage.
- They are of a barrel shape, rectangular cross-section and are 240 mm or 300 mm long .
- They can be sharpened easily without the risk of breaking the filling.

CODE	CAT NO.	COLOR	LENGTH	HARDNESS	QUANTITY
3-01-12-27-011	PRO-BL011	red	240mm	НВ	100 pcs
3-01-12-27-211	PRO-BL211	red	300mm	НВ	100 pcs
3-01-12-27-013	PRO-BL013	yellow	240mm	-	100 pcs
3-01-12-27-016	PRO-BL016	green	240mm	10H	100 pcs
3-01-12-27-212	PRO-BL212	green	300mm	10H	100 pcs
3-01-12-27-014	PRO-BL014	blue	240mm	-	100 pcs





#### **CARPENTER'S PENCIL**





## **HOLE MARKER**

- Marker for holes and hard-to-reach places.
- Extra long (25 mm) thin stainless steel tip.
- Special ergonomic shape to prevent the tip from slipping .
- Waterproof on almost any surface.
- Packaged in 20 pieces.

CODE	CAT NO.	QUANTITY
3-01-12-27-101	PRO-BL101	1 pc
3-01-12-27-114	PRO-BL114	20 pcs (display)





### PERMANENT MARKERS

- Marker for permanent marking and writing on almost any surface (cardboard, plastic, metal, glass, rubber, wood). Non-fading and quick-drying.
- Low odor with no xylene or toluene.
- Round tip 1.5 3 mm.

3-01-12-27-302

- Packaged in 10 pieces.

CODE	CAT NO.	QUANTITY	COLOR
3-01-12-27-102	PRO-BL102	1 pc	red
3-01-12-27-103	PRO-BL103	1 pc	black



#### PERMANENT MIX MARKER MP-MIX80

PRO-BL302



- RED GREEN BLACK BLUE WATER ESISTANT 10 pcs. 10 pcs.

- The package contains 80 pieces

#### MP-MIX4

CODE

CODE

3-01-12-27-304

3-01-12-27-303



4 PCS. WATER RESISTANT QUICK

- Marker for permanent marking and writing on almost any surface.
  - Non-fading and quick-drying.
  - Low odor with no xylene or toluene.
  - The package contains 4 pieces

### PERMANENT BLACK MARKER

CAT NO.

PRO-BL303

CAT NO.

PRO-BL304

**DISPLAY 36 PIECES** 



QUICK DRY



- Hard fiber stick, round tip, 1.2-2.4mm.
- 2-component structure.
- Non-toxic ink, free of xylene and toluene.
- Waterproof, quick drying, refill option.
- Product not suitable for children under 3 years old.

## PERMANENT MARKER BLACK AND RED

**DISPLAY 36 PIECES** 



QUICK DRY





CODE CAT NO.
3-01-12-27-305 PRO-BL305

- Hard fiber stick, round tip, 1.2-2.4mm.
- 2-component structure.
- Non-toxic ink, free of xylene and toluene.
- Waterproof, quick drying, refill option.
- Product not suitable or children under 3 years old.

### OIL MARKER WHITE

**DISPLAY 12 PIECES** 

X MORE INK

WATER ESISTANT QUICK DRY





CODE CAT NO.
3-01-12-27-310 PRO-BL310

- Durable acrylic stick, round tip, 1.8-2.2mm.
- Fast drying, non-toxic, water and fade resistant.
- Suitable for wood, metal, glass and paper and works at extreme temperatures.
- High-volume ink for 2x longer life.

## CONSTRUCTION

## RASABLE MARKER









3-01-12-27-106	PRO-BL106	1 pc.	blue
CODE	CAT NO.	QUANTITY	COLOR
3-01-12-27-113	PRO-BL113	20 pcs. (display) blue	e, orange
3-01-12-27-107	PRO-BL107	1 pc	orange

- Abrasive marker for marking on almost all surfaces such as leather, metal, glass, plastic, cardboard, tiles, etc.
- The marker leaves a rubber-like mark that can be easily removed from smooth surfaces, even with a finger.
- Waterproof, special removable ink.
- Spherical tip.
- In two colors: blue and orange.
- Packaged in 10 pieces.
- Line thickness 4 mm



CODE	CAT NO.	QUANTITY
3-01-12-27-105	PRO-BL105 1	рс
3-01-12-27-115	PRO-BL115	20 pc (display)

INDUSTRIAL MARKER







- Quality paint marker for professional use in industry.
- For strong opaque marking on almost all materials such as metal, glass, plastic, stone, cardboard, glaze, wood.
- For marking and inscribing particularly dark surfaces.
- Waterproof and quick-drying lacquer.
- When the felt tip is worn out : remove the felt, rotate and
- In two colors: white and yellow.
- Line thickness 2-4 mm





CODE	CAT NO.	COLOR
3-01-12-27-108	PRO-BL108	red
3-01-12-27-109	PRO-BL109	blue
3-01-12-27-110	PRO-BL110	yellow
3-01-12-27-116	PRO-BL116	white













- Lumber crayon a type of crayon made from compressed, colored wax-based chalk.
- For dry and wet marking on wood, paper, cardboard, metal, stone, concrete, tiles, plastics.
- Resistant to abrasion and weathering.
- Hexagonal, diameter 12 mm, length 120 mm.
- Available in four colors: red, blue, white and yellow.
- 12 pieces in the packaging.

## **LUMBER CRAYON HOLDER**









- Holder for round and hexagonal lumber crayons with a diameter of 11-12 mm.
- Equipped with a retaining clip.
- Body made of aluminum, impact resistant.

CODE

## EVELING SYSTEMS









- Leveling systems are a modern method of tiling, allowing for perfect tile placement while saving time and increasing productivity.
- Minimum joint width 1mm (white) 1.5mm (black, grey)
   White clips designed for 7-15mm tiles, grey for 6-14mm tiles, black for 4-10mm tiles.
- Number of pieces needed per square meter depending on tile

30 × 30 33 × 33 40 × 40 45 × 45 50 × 50 60 × 60 60 × 30 80 × 80								
30 ^ 30   33 ^ 33   40 ^ 40   49 ^ 43   30 ^ 30   60 ^ 60   60 ^ 30   60 ^ 60	30 × 30	33 × 33 40 × 40	45 × 45	50 × 50	60 × 60	60 × 30	80 × 80	100 × 30

42 pc 36 pc 20 pc 16 pc 16 pc 10 pc 22 pc 10 pc 16 pc

CODE	CAT NO.	NAME	QUANTITY
3-01-26-ZA-001 PRO	D-SP001 wedges	100 pcs.	
3-01-26-ZA-002 PRO	D-SP002 gray clip	os 4 × 25 mm	100 pc
3-01-26-ZA-003 PRO	O-SP003 mix gray	y clips/clamps 100 (50/50) pcs.	
3-01-26-ZA-004 PRO	D-SP004 mix gray	y clips/clips	400 (300/100) pcs.
3-01-26-ZA-005 PRO	O-SP005 mix gray	v clips 400 pcs.	
3-01-26-ZA-202 PRO	D-SP202 white cl	ips	100 pc
3-01-26-ZA-203 PRO	D-SP203 mix whit	te clips/ wedges 100 (50/50) pcs.	
3-01-26-ZA-204 PRO	D-SP204 mix whi	te clips / wedges	400 (300/100) pcs.
3-01-26-ZA-205 PRO	0-SP205 white cli	ps 400 pcs.	

### **DISTANCE CROSSES**




- They allow to create an even joint between ceramic tiles.

CODE	CAT NO.	NAME	QUANTITY
3-01-26-ZA-010	PRO-SP010	distance crosses 1	100 pc
3-01-26-ZA-011	PRO-SP011	distance crosses 1.5	200 pc
3-01-26-ZA-012	PRO-SP012	distance crosses 2	200 pc
3-01-26-ZA-013	PRO-SP013	distance crosses 2.5	200 pc
3-01-26-ZA-014	PRO-SP014	distance crosses 3	150 pc
3-01-26-ZA-015	PRO-SP015	distance crosses 4	100 pc
3-01-26-ZA-016	PRO-SP016	distance crosses 5	75 pc
3-01-26-ZA-017	PRO-SP017	distance crosses 6	50 pc
3-01-26-ZA-018	PRO-SP018	distance crosses 8	30 pc
3-01-26-ZA-019	PRO-SP019	distance crosses 10	30 pc
3-01-26-ZA-020	PRO-SP020	distance crosses T6	50 pc
3-01-26-ZA-021	PRO-SP021	distance crosses T8	30 pc
3-01-26-ZA-022	PRO-SP022	distance crosses T10	30 pc
3-01-26-ZA-023	PRO-SP023	dist. crosses with handle 1.5	125 pc
3-01-26-ZA-024	PRO-SP024	dist. crosses with handle 2	125 pc
3-01-26-ZA-025	PRO-SP025	dist. crosses with handle 2.5	100 pc
3-01-26-ZA-026	PRO-SP026	dist. crosses with handle 3	100 pc
3-01-26-ZA-027	PRO-SP027	dist. crosses with handle 4	50 pc

## **WEDGES**





CODE	CAT NO.	NAME	QUANTITY
3-01-26-ZA-029	PRO-SP029	large wedge	50 pc







- Made of durable polypropylene.
- Used to tighten wedges on clips in tiling leveling systems.

CODE	CAT NO.
3-01-26-ZA-0	PRO-SP032

PP

## CLAMPS

#### **QUICK CLAMP**









#### **SPRING COMPRESSION**







- Spring compressor made of engineering plastic.
- Strong spring with movable flat pressure tips.
- For light carpentry or finishing work. Helpful for gluing, drilling, riveting
- Spring compressor made of engineering plastic.
- Strong spring with movable flat pressure tips.
- For light carpentry or finishing work. Helpful for gluing, drilling, riveting.

CODE	CAT NO.	DIMENSIONS
3-01-05-SC-001	PRO-SC001 4"	/100 mm
3-01-05-SC-002	PRO-SC002	6"/150 mm
3-01-05-SC-003	PRO-SC003	12"/300 mm
3-01-05-SC-004	PRO-SC004	18"/450 mm
3-01-05-SC-005	PRO-SC005	24"/600 mm

CODE	CAT NO.	DIMENSIONS
3-01-05-SC-007	PRO-SC007 2"/50 mm	
3-01-05-SC-008	PRO-SC008	3"/75 mm
3-01-05-SC-009	PRO-SC009 4"/100 mm	

## QUICK CARPENTRY CLAMP QUICK CARPENTRY CLAMP FOR DOOR FRAMES


















- The head is made of damage-resistant plastic.
- The rail is made of carbon steel, with a large quick clamp locking tongue.
- Spreader function after moving the head.
- Body made of durable plastic.
- For compression or spreading in carpentry and assembly work.
- Clamping force up to 500N (60kg)

CODE	CAT NO.	DIMENSIONS	
3-01-05-SC-020	PRO-SC020	6"/150 mm	
3-01-05-SC-021	PRO-SC021	12"/300 mm	
3-01-05-SC-022	PRO-SC022	18"/450 mm	



- Spreader function after moving the head (e.g. when installing door frames).
- Body made of durable plastic.
- For compression or spreading in carpentry and assembly work.
- Quick and comfortable operation due to the right ratio of trigger power to clamping operation.
- Clamping force up to 1500N (150kg).

CODE	CAT NO.	DIMENSIONS
3-01-05-SC-015	PRO-SC015	900mm
3-01-05-SC-016	PRO-SC016	1200mm

### F-TYPE CARPENTRY CLAMP





- Thick, stable rail stiffened with additional ribbing.
- Arms made of high pressure cast steel, powder coated.
- Screw with special thread.
- Pressure plate mounted on a ball joint, easily adapting to the surface.
- Soft plastic covers to protect the compressed material.
- Two-component, non-slip handle.

CODE	CAT NO.	DIMENSIONS	CODE	CAT NO.	DIMENSIONS
3-01-05-SC-051	PRO-SC051	50 × 150 mm	3-01-05-SC-056	PRO-SC056 8	0 × 500 mm
3-01-05-SC-052	PRO-SC052	50 × 250 mm	3-01-05-SC-057	PRO-SC057	120 × 300 mm
3-01-05-SC-053	PRO-SC053	50 × 300 mm	3-01-05-SC-058	PRO-SC058 1	20 × 500 mm
3-01-05-SC-054	PRO-SC054	80 × 200 mm	3-01-05-SC-059	PRO-SC059	120 × 800 mm
3-01-05-SC-055	PRO-SC055	80 × 300 mm	3-01-05-SC-060	PRO-SC060 1:	20 × 1000 mm

### LEVER CLAMP





QUICK DJUSTMENT



- The ratchet mechanism allows gradual, fast and vibration-resistant clamping.
<ul> <li>Rail made of high-quality carbon steel with a profile that enables uniform clamping force generation.</li> </ul>

- Fixed arm and presser foot with high resistance to torsion
- Sturdy and well-fitting handle made of engineering plastic.
- Ergonomic clamping and loosening lever.
- A lever clamp used for clamping workpieces during gluing, drilling and other material processing operations.
- Clamping force up to 1200N (120kg).

CODE	CAT NO.	DIMENSIONS
3-01-05-SC-081	PRO-SC081	80 × 160 mm
3-01-05-SC-082	PRO-SC082	80 × 200 mm
3-01-05-SC-083	PRO-SC083	80 × 250 mm
3-01-05-SC-084	PRO-SC084	80 × 300 mm

## SILICONE JOINT SCRAPER






- A tool to make walling and tearing silicone grout easierA tool to facilitate the application and smoothing of fresh
- A tool to facilitate the application and smoothing of fresh silicone or acrylic compound.

## PLASTIC FLOATS

PLASTIC

2 PCS.



Set of 2 plastic floats of different shape and size of teeth.The floats are made of plastic.

- They are used to apply the appropriate layer of mortar, depending on the tile format.

CODE CAT NO.
3-01-26-AG-014 PRO-AG014

### SILICONE SPATULA



PLASTIC

4 PCS.



CODE CAT NO.

3-01-26-AG-012 PRO-AG012

- Professional sealant spreading blocks.
- Packaged in 4 pieces of different shapes for easy insertion and shaping of the joint before curing.
- 0 mm cube for removing uncured sealant.
- 2-5 mm cube for standard joints with little mobility adaptation.
- 8-10 mm cube for standard flexible joints e.g. baths, kitchen worktops, shower trays, ceramic tiles.
- 14-20mm cube for large and deep joints e.g. floor ceramic tiles, floor- wall.

JAPANESE SPATULAS



CODE ART. NO.
3-01-26-AG-013 PRO-AG013

- Set of 4 Japanese spatulas

- The spatulas are made of plastic.
- Spatula widths: 50mm, 80mm, 100mm, 120mm.
- They are used, among other things, for spreading and mixing paint, plaster, applying compounds, etc., as well as for simple finishing works, smoothing walls and filling in defects, scraping dirt from surfaces, etc.

### **PVC INSULATING TAPE**









CODE	CAT NO.	COLOR
3-01-12-27-201	PRO-BA201	black
3-01-12-27-202	PRO-BA202	white
3-01-12-27-203	PRO-BA203	red

- Insulating tape, self-extinguishing, made of plasticized PVC.
- Excellent insulating properties due to plasticizers and rubber-based adhesive.
- High adhesion to steel.
- Flexible and stretchable, with electrical strength up to 5000 volts.
- Color: black, red or white.
- The package contains 10 pieces

## PTFE WHITE TAPE









CODE CAT NO.
3-01-12-27-206 PRO-BA206

- Teflon tape for sealing of threaded joints in water installations (metal and plastic).
- Thickness 0.075 mm; density 0.35 g/cm.
- Designed for diameters < 3/4".
- With stands temperatures from -60°C to + 260°C and pressures up to 15 bar.

## MITRE BOX







 CODE
 CAT NO.
 DIMENSIONS

 3-01-16-00-020
 PRO-SC120 250 x 50 x 35 mm

 3-01-16-00-021
 PRO-SC121
 300 x 90 x 55 mm

- The mitre box is made of HIPS.
- Angled cutting:  $45^\circ,\,90^\circ$
- dimensions 250 x 50 x 35 mm or 300 x 90 x 50 mm.



#### **GUN SPRINKLER 8 FUNCTIONS**









- Gun sprinkler with 8-function head.
- Made of durable ABS plastic covered with thermoplastic rubber (TPR).
- Continuous operation lock.
- Gradual adjustment of water jet type in 8 different positions.

CODE	CAT NO.
3-01-14-OG-001	PRO-GA001

# STRAIGHT GUN SPRINKLER WITH STEPLESS REGULATION





TPR





- Straight gun sprinkler.
- Steplessly adjustable water jet.
- Handle coated with two-tone thermoplastic rubber (TPR).
- Made of durable ABS and aluminum (AI).

CODE	CAT NO.
3-01-14-OG-003	PRO-GA003

# 8 FUNCTION GUN SPRINKLER WITH STEPLLESS ADJUSTMENT











- Gun sprinkler with 8-function head.
- Steplessly adjustable water jet.
- Double rubber coated.
- Made of durable ABS and aluminum (AI) plastic covered with thermoplastic rubber (TPR).

CODE	CAT NO.
3-01-14-OG-002	PRO-GA002

#### STRAIGHT GUN SPRINKLER











- Straight gun sprinkler with trigger.
- Adjustment of water jet strength by pressing the trigger.
- Made of durable ABS plastic covered with thermoplastic rubber (TPR).

CODE	CAT NO.
3-01-14-OG-005	PRO-GA005

#### **GUN SPRINKLER 8 FUNCTIONS**



**ABS** 

**TPR** 





- Gun sprinkler with 8-function head.
- Made of durable ABS plastic covered with thermoplastic rubber (TPR).
- Continuous operation lock.
- Gradual adjustment of water jet type in 8 different

CODE	CAT NO.
3-01-14-OG-004	PRO-GA004

#### 4 ELEMENTS MULTI-PURPOSE SPRINKLER + QUICK CONNECTORS AND 1/2" ADAPTER





4 ELEMENTS

3/4-1 ADAPTER





ABS

**TPR** 



#### SET:

- Gun sprinkler with 8-function head.
- 1/2" quick release coupling and 1/2" alloy quick release coupling
- Adjustment of water jet strength by pressing the trigger
- Made of durable ABS plastic covered with thermoplastic rubber (TPR)

CODE	CAT NO.
3-01-14-OG-012	PRO-GA012

#### 4 ELEMENTS STRAIGHT SPRINKLER + QUICK CONNECTORS AND 1/2" ADAPTER





#### SET:

- Straight gun sprinkler with trigger
- 1/2" quick release coupling and 1/2" alloy quick release coupling
- Adapter 3/4-1
- Adjustment of water jet strength by pressing the trigger
- Made of durable ABS covered with thermoplastic rubber (TPR)

#### **ROTARY SPRINKLER**











CODE CAT NO.
3-01-14-0G-023 PRO-GA023

- Rotary sprinkler with two arms.
- Made of durable ABS.
- Hose end connection by means of quick couplings.
- 360 degree sprinkler rotation.
- Manual adjustment of water jet angle.
- Maximum sprinkling diameter of up to 7m.

# TWO ARM ROTARY SPRINKLER



3-8 BAR





- Rotary sprinkler with two arms.
- Made of durable ABS.
- The plastic spike allows for easy and convenient placement in the lawn bed.
- The sprinkler can be connected in a series with other sprinklers.
- Hose end connection by means of quick couplings.
- Maximum sprinkling diameter of up to 7m.

#### GARDEN PULSATING SPRINKLER





3-8 BAR ABS



- Rotary pulsating sprinkler.
- The adjustable pulsating head gives you the ability to spray a diffused mist of varying intensity.
- Made of durable ABS.
- The plastic spike allows for easy and convenient placement in the lawn bed.
- The sprinkler can be connected in a series with other sprinklers.
- Hose end connection by means of quick couplings.
- Automatic rotation from 45 to 360 degrees.
- Maximum sprinkling diameter of up to 17m.

# CONNECTION ADAPTER 1"-3/4"

1"

3/4"

ABS

30 PCS.







- Made of durable ABS.
- Size: 1"-3/4".
- Packaging with 30 pieces.

#### 1" ADAPTER CONNECTION



ABS

30 PCS.





- Made of durable ABS.
- Size: 1"
- Packaging with 30 pieces.

**CODE CAT NO.** 3-01-14-OG-032 PRO-GA032



#### **CONNECTION ADAPTER 1"-3/4"-1/2"**

1" 3/4"

1/2"

ABS

30 PCS.





- Made of durable ABS.

- Size: 1"-3/4"-1/2".

- Packaging with 30 pieces.

**CODE** 3-01-14-OG-033 CAT NO.

-033 PRO-GA033

# **CONNECTION ADAPTER 1/2"**

1/2"

ABS

30 PCS.



CODE CAT NO.
3-01-14-OG-035 PRO-GA035



- Made of durable ABS.
- Size: 1/2".
- Packaging with 30 pieces.

**CONNECTION ADAPTER 1/2"** 

1/2"

ABS

30 PCS.



CODE CAT NO.
3-01-14-OG-034 PRO-GA034



- Made of durable ABS.
- Size: 1/2".
- Packaging with 30 pieces.

# **GARDENING**

# 3/4" QUICK CONNECTOR



3/4"

ABS

30 PCS.





- Made of durable ABS.

- Size: 3/4".

- Packaging with 30 pieces.

CODE CAT NO.
3-01-14-OG-044 PRO-GA044

# 1/2" QUICK CONNECTOR



1/2"

ABS

30 PCS.



CODE CAT NO.
3-01-14-OG-041 PRO-GA041



- Made of durable ABS.
- Size: 1/2".
- Packaging with 30 pieces.

# 1/2" QUICK RELEASE COUPLING





1/2"



30 PCS.



CODE CAT NO.
3-01-14-OG-042 PRO-GA042



- Made of durable ABS.
- Size: 1/2".
- Automatic water stop function.
- Packaging with 30 pieces.

# **GARDENING**

# 3/4" QUICK RELEASE COUPLING





3/4"

ABS







- Made of durable ABS.
- Size: 3/4".
- Automatic water stop function.
- Packaging with 30 pieces.

3-01-14-OG-045 PRO-GA045

CAT NO.



3/4"

ABS

30 PCS.



CODE



**CODE CAT NO.** 3-01-14-OG-048 PRO-GA048



- Made of durable ABS.
- Size: 3/4".
- Packaging with 30 pieces.

CONNECTOR 1/2



1/2"

ABS

30 PCS.



CODE CAT NO.
3-01-14-OG-047 PRO-GA047



- Made of durable ABS.
- Size: 1/2".
- Packaging with 30 pieces.

# **SHOVELS**

CODE

CODE

3-01-14-02-108

#### **PROFILED SAND SHOVEL**



HRC 1050Mn

STEEL 40-48



- Metal handle, profiled. - Handle of construction plastic.
  - Tool size 1200 mm.

    - Steel thickness of head 1.8 mm.
    - Powder coating.
    - 1050 Mn steel.
    - Hardness HRC 40-48.

#### SAND SHOVELLONG PROFILED

CAT NO.

PRO-BU108

120 cm

HRC 1050Mn STEEL 40-48



- Metal handle, profiled.
- Handle construction plastic.
- Extended head.
- Tool size 1200 mm.
- Steel thickness of head 1.8 mm.
- Powder coating.
- 1050 Mn steel.
- Hardness HRC 40-48.

#### UNIVERSAL SHOVELWITH WOODEN HANDLE

CAT NO.

PRO-BU107

125 cm

100cm

HRC 1050Mn

STEEL 40-48



- Lacquered wooden handle type "T" 100 cm.
- Tool size 1250 mm.
- Steel thickness of head 1.8 mm.
- Powder coating.
- 1050 Mn steel.
- Hardness HRC 40-48.

#### **MULTI-PURPOSE PROFILED SHOVEL**

CAT NO.

PRO-BU101

3-01-14-02-101

PRO-BU111

120

HRC 1050Mn STEEL 40-48



- Metal handle, profiled.
- Handle construction plastic.
- Tool size 1200 mm.
- Steel thickness of head 1.8 mm.
- Powder coating.
- 1050 Mn steel.
- Hardness HRC 40-48.

#### POINTED SURVIVAL SHOVEL

71 HEATHIC 2mm

127

125

120

HEAD THICKNESS 2mm

C

SHANK OF WOOD

100cm

HRC 1050Mn STEEL 40-48

STEEL

38-45

STEEL

40-48

STEEL

40-48



- Pointed survival shovel.
- Profiled metal handle.
- Handle construction plastic.
- Powder coating.
- 1050 Mn steel.
- Hardness HRC 40-48.

ODE	CAT NO.
01-14-02-104	PRO-BU104

HRC

1050Mn

#### **PROFILED CARBON SHOVEL**



- Profiled carbon shovel.
- Profiled metal handle.
- Handle structure plastic.
- Powder coating.
- 1050 Mn steel.
- Hardness HRC 38-45.

CODE	CAT NO.
3-01-14-02-109	PRO-BU109

HRC

1050Mn



#### FLAT SPADE WITH WOODEN HANDLE



- Wooden handle "T" 100 cm.
- Hardened head.
- 1050 Mn steel.
- Hardness HRC 40-48.

CODE	CAT NO.
3-01-14-02-110	PRO-BU110

HRC

1050Mn

#### PROFILED FLAT SPADE



- Flat spade, profiled.
- Metal handle.
- Handle construction plastic.
- Powder coating.
- 1050 Mn steel.
- Hardness HRC 40-48.

CODE	CAT NO.
3-01-14-02-102	PRO-BU102

#### POINTED SPADE



120

HEAD THICKNESS 2mm HRC 1050Mn STEEL 40-48



- Pointed spade.
- Metal handle.
- Handle construction plastic.
- Powder coating.
- 1050 Mn steel.
- Hardness HRC 40-48.

CODE	CAT NO.
3-01-14-02-103	PRO-BU103



#### **FORK WITH 4 TINES**



4 TIN HRC 1050Mn STEEL 40-48

- Fork with 4 tines.
- Metal handle, profiled.
- Handle construction plastic.
- Hardened head.
- Head: 1050 Mn steel.
- Hardness HRC 40-48.

CODE	CAT NO.
3-01-14-02-105	PRO-BU105







- Digging fork, profiled.
- Metal handle, profiled.
- Hardened head.
- Head: 1050 Mn steel.
- hardness HRC 40-48.

CODE	CAT NO.
3-01-14-02-106	PRO-BU106

1050Mn

STEEL

40-48

STEEL



#### **GARDEN RAKE**



- Garden rake.
- Metal handle.
- Head: 1050 Mn steel.
- Hardness HRC 40-48. - Tool size: 1500 mm.
- 14 tines

CODE	CAT NO.
3-01-14-02-112	PRO-BU112

#### **LEAF RAKE**



- Metal handle.
- Head: 1050 Mn steel.
- Hardness HRC 40-48.
- Tool size: 1500 mm.
- 22 tines.

TIN	1050Mn	40-48

HRC



CODE CAT NO. 3-01-14-02-113 PRO-BU113

#### LEAF RAKE WITH STEEL HANDLE AND PLASTIC



150

150

TINE

PLASTIC

CARBON STEEL



- Made of durable carbon steel, powder coated.
- Ergonomic lightweight design
- Ultralight plastic head.
- The fan shape allows to collect the leaves effectively.

CODE	CAT NO.

# **GARDEN HOE**



33

HRC 1050Mn STEEL 40-48



- Garden hoe.
- Metal handle.
- Head: 1050 Mn steel. - Hardness HRC 40-48.
- Tool size: 1500 mm.

CODE	CAT NO.
3-01-14-02-114	PRO-BU114

2 PONENT

# FLAT GARDEN SHOVEL WITH TEETH



- A shovel for replanting plants and small gardening jobs.
- Made of hardened steel powder coated with an ergonomic two-component handle.
- Lightweight and very convenient to use.

CODE	CAT NO.	
3-01-14-02-303	PRO-BU303	

#### **HEDGE CLIPPERS**

23 cm

Cr

Αl

STEEL



- Hedge and branch pruning clippers
- 23cm scissors blade made of high-quality steel and anodized chrome plated.
- Constructed of lightweight and durable aluminum.
- The pruning shears have practical and ergonomic handles made of plastic.

CODE CAT NO. 3-01-14-02-321 PRO-GA321

#### **ALUMINUM TELESCOPIC HEDGE CLIPPER**



arms to 97 cm

arms Αl

2

COMPONEN

STEEL



CODE CAT NO. 3-01-14-02-323 PRO-GA323

- Telescopic pruning shears for larger and higher hedges.
- Fully hardened shear blades made of high-quality steel, chromeplated and anodized with Teflon.
- The arms are made of light aluminum and can be extended by 24 cm (max. length = 97cm).
- Two-component ergonomic handles.

# ALUMINUM TELESCOPIC PRUNING LOPPER



arms Αl

STEE



CODE CAT NO. 3-01-14-02-331 PRO-GA331

- Telescopic lopper for cutting thicker and harder branches (up to 3.8 cm in diameter).
- Shears blades made of high-quality steel and anodized chrome
- Three-stage ratchet mechanism for efficient and easy use.
- The arms are made of lightweight and durable aluminum and can be extended by 38 cm.
- Two-component ergonomic handles.
- Easy cleaning.

# PRUNING SHEAR FOR BRANCHES

arms **Al**  HANDLE OF PLASTIC

SK5



- Classic pruning shears with blades made of durable Sk5 steel.
- Arms made of lightweight and durable aluminum.
- The lever design makes it easy to cut even thick branches (up to 3.8 cm in diameter).
- The pruning shears have practical and ergonomic handles made of plastic.

CODE CAT 3-01-14-02-332 PRO

CAT NO.
PRO-GA332

# GARDEN PRUNING SHEAR BLACK PP

Cr

TEFLON

2 OMPONENT

STEEL SK5



**CODE CAT NO.** 3-01-14-02-341 PRO-GA341

- Pruning shear blades made of SK5 steel additionally chromium-plated to prevent corrosion.
- Blades additionally coated with Teflon.
- Two-component pruning shear handle.

# GARDEN PRUNING SHEAR BLACK PP2

Cr

TEFLON

2 IMPONENT

STEEL SK5



- Pruning shear blades made of SK5 steel additionally chromium-plated to prevent corrosion
- Blades additionally coated with Teflon.
- Two-component pruning shear handle.

**CODE CAT NO.** 3-01-14-02-342 PRO-GA342

#### **GARDEN PRUNING SHEAR WITH COMFORT GUARD**

Cr

TEFLON

arms **Al** 

2 COMPONENT STAINLESS



- Pruning shear blades made of SK5 steel additionally chromiumplated to prevent corrosion

- Blades additionally coated with Teflon.

- Two-component pruning shear handle.

- Handle made of lightweight and durable aluminum.

**CODE** 3-01-14-02-343 CAT NO. PRO-GA343

# **ENDURANCE PRUNING SHEAR**

Cr

TEFLON

arms **Al**  STAINLESS



- Pruning shear blades made of SK5 steel additionally chromium-plated to prevent corrosion.

- Blades additionally coated with Teflon.

- Ergonomic handle design finished with non-slip plastic insert.

- Constructed of lightweight and durable aluminum.

CODE CAT NO.
3-01-14-02-347 PRO-GA347

# **FOLDABLE HANDSAW**

blade 25 cm

CARBON STEEL

BLADE LOCK



- High quality carbon steel cutting blade.

- The teeth of the blade are ground on three sides.

- Blade lock.

- Blade length: approx. 25 cm.

CODE CAT NO.
3-01-14-02-361 PRO-PK361



#### **ENDURANCE HAMMERS**

#### **ENDURANCE MONOBLOCK SHOEMAKER'S HAMMER PRO-BM201**


- MONOBLOK shoemaker's hammer, made of one piece of material, forged entirely as a one-piece.
- Specially patented design to reduce vibration and shock generated during operation.
- Pointed end made of high quality carbon steel.
- Additional hardening of the hammer face.
- Two-component handle with non-slip TPR (thermoplastic rubber) coating.
- Magnetic nail gripper.

# CODE CAT NO. WEIGHT 3-01-14-00-201 PRO-BM201 450 g

PCV TPR HANDLE

#### **ENDURANCE CARPENTRY MONOBLOCK HAMMER PRO-BM203**

- Carpentry MONOBLOK hammer, made of one piece of material, forged entirely as a one-piece.
- Specially patented design to reduce vibration and shock generated during operation.
- Pointed end made of high quality carbon steel.
- Additional hardening of the hammer face.
- Two-component handle with non-slip TPR (thermoplastic rubber) coating.
- Magnetic nail gripper.



#### MASON'S HAMMER ENDURANCE PRO-BM205

- MONOBLOK club hammer, made of one piece of material, forged entirely as one-piece.
- Specially patented design to reduce vibration and shock generated during operation.
- Face made of high quality carbon steel
- Additional hardening of the hammer face.
- Two-component non-slip coated handle
- TPR (thermoplastic rubber) coating.



# CARPENTRY HAMMERS

#### CARPENTRY HAMMERMONOBLOCK PRO-BM322

- MONOBLOK hammer, made of one piece of material.
- Hammer face made of forged, high-grade carbon steel
- Additional hardening of the hammer face.
- Magnetic nail gripper.
- Ergonomically shaped handle made of PVC and TPR composite.



#### **CARPENTRY HAMMERPRO-BM320**

- Hammer face made of high quality carbon steel.
- Additional hardening of the hammer face.
- Two-component handle with non-slip TPR coating.
- 70% of the shaft volume is a vibration-absorbing fiberglass core
- Magnetic nail gripper.
- Very durable epoxy resin bonding of the head to the hammer handle



#### **SHOEMAKER'S HAMMERS**

#### PRO-BM317

- Hammer face made of high quality carbon steel.
- Additional hardening of the hammer face.
- Two-component handle with non-slip TPR coating.
- 70% of the shaft volume is a vibration-absorbing fiberglass core
- Very durable epoxy resin bonding of the head to the hammer handle





HIGH-QUALITY CARBON STEEL

#### PRO-BM314, PRO-BM-315

- MONOBLOK hammer, made of one piece of material.
- Hammer face made of forged, high-grade carbon steel
- Additional hardening of the hammer face.
- Ergonomically shaped handle made of PVC and TPR composite.






# MASONRY HAMMERS

#### RHENISH MASONRY HAMMER PRO-BM316

- MONOBLOK hammer, made of one piece of material.
- Hammer face made of forged, high-grade carbon steel.
- Additional hardening of the hammer face.
- Ergonomically shaped handle made of PVC and TPR composite.



#### **RHENISH MASONRY HAMMER PRO-BM321**



- Hammer face made of high quality carbon steel.
- Additional hardening of the hammer face.
- Two-component handle with non-slip TPR coating.
- 70% of the handle is a vibration-absorbing fiberglass core.
- Very durable epoxy resin bonding of the head to the hammer handle.

#### **BERLINER MASONRY HAMMER PRO-BM319**



- MONOBLOCK hammer, made of high quality carbon steel.
- Additional hardening of the hammer face.
- Shank and head made from one piece of metal.
- Two-component handle with non-slip TPR coating.





# LOCKSMITH HAMMERS

# HAMMER PRO-BM306, PRO-BM307, PRO-BM308, PRO-BM327, PRO-BM328, PRO-BM329, PRO-BM330



- Hammer shank of forged, high-grade carbon steel
- Additional hardening of the hammer face.
- Fiberglass stem core (70% of stem volume).
- Permanent epoxy resin connection between head and stem.
- PVC and TPR composite handle.

# HAMMER PRO-BM309, PRO-BM310, PRO-BM311, PRO-BM312, PRO-BM331, PRO-BM332



- Hammer shank of forged, high-grade carbon steel.
- Additional hardening of the hammer face.
- The handle is made of ash wood.
- Permanent epoxy resin bonding of the head to the hammer handle.



CODE	CAT NO.	WEIGHT
3-01-14-00-306	PRO-BM306	300 g
3-01-14-00-307	PRO-BM307	500 g
3-01-14-00-308	PRO-BM328	1500 g
3-01-14-00-327	PRO-BM327	1000 g
3-01-14-00-330		
3-01-14-00-329	PRO-BM329	2000 g



CODE	CAT NO.	WEIGHT
3-01-14-00-309	PRO-BM309	300 g
3-01-14-00-310	PRO-BM310	500 g
3-01-14-00-311	PRO-BM311	800 g
3-01-14-00-312	PRO-BM312	1000 g
3-01-14-00-331	PRO-BM331	1500 g
3-01-14-00-332	PRO-BM332	2000 g

# <del>-</del>

# HAMMERS AND AXES

## **CLUB HAMMERS**

#### HAMMER PRO-BM313, PRO-BM334, PRO-BM334

- Hammer shank made of forged carbon steel
- Additional hardening of the hammer face.
- Fiberglass stem core (70% of stem volume).
- Permanent epoxy resin bonding of the head to the hammer handle.
- PVC and TPR composite handle.

CODE	CAT NO.	WEIGHT
3-01-14-00-313	PRO-BM313	1000 g
3-01-14-00-333	PRO-BM333	2000 g
3-01-14-00-334	PRO-BM334	3000 g

# CISISO

2000 3000

1000

 $\square$ IN

6475

HIGH-QUALITY CARBON STEL FIBER GLASS HANDLE

#### HAMMER PRO-BM343, PRO-BM342

- Hammer shank made of forged carbon steel
- Additional hardening of the hammer face.
- The handle is made of ash wood.
- Permanent epoxy resin bonding of the head to the hammer handle.

		/	/	
1	W		- C C	

2000 1500 DIN 6475





#### **RUBBER CAP FOR CLUB HAMMER**

- Rubber cap for club hammer 1kg.



CODE	CAT NO.
3-01-14-00-301	PRO-BM301


# **RUBBER HAMMERS**

#### HAMMER PRO-BM023, PRO-BM024, PRO-BM025

- Rubber hammer, for various surfaces.
- Lacquered ash wood handle.
- Additional reinforcement of the handle.
- The white part of the hammer does not stain or scratch the surface.

CODE	CAT NO.	WEIGHT
3-01-14-00-023	PRO-BM023	370 g
3-01-14-00-024	PRO-BM024	580 g
3-01-14-00-025	PPO-RM025	780 a





CLUB HAMMER

RUBBER

#### **MŁOTEK PRO-BM-336**


- Rubber hammer, for various surfaces.
- Lacquered ash wood handle.
- Additional reinforcement of the handle.




#### RECOILLESS HAMMER

#### **MŁOTEK PRO-BM026**

- Recoilless hammer with monolithic structure.
- The lead grain-filled shank dampens vibrations during



#### **INSTALLATION METALWORKING HAMMER**



- Total length 350 mm.
- Handle made of hickory wood.
- The joint is additionally protected with synthetic resin.

CODE	CAT NO.	WEIGHT	DIAMETER
3-01-14-00-036	PRO-BM036	300 g	25mm
3-01-14-00-337	PRO-BM337	500 g	35mm
3-01-14-00-038	PRO-BM038	800 g	45mm
3-01-14-00-339	PRO-BM339	1000 g	60mm



# **AXES**

#### **AXE PRO-BM320**

CODE	CAT NO.	WEIGHT	
3-01-14-00-320	PRO-BM320	800 a	



Ф60 mm

HICKORY

HANDLE

ENDS



#### **AXE PRO-BS010, PRO-BS011, PRO-BS012**



#### **SPLITTING AXE PRO-BS030**


- Splitting axe with wedge for fast splitting of stumps.
- Handle made of ash wood, non-responsive to vibration and rebound cracking, durable.
- The axe head is made of high quality additionally hardened steel.
- Permanent resin bonding between face and handle.

CODE	CAT NO.	WEIGHT	
3-01-14-00-030	PRO-BS030	2000 g	

#### **ENDURANCE AXE ENDURANCE SPLITTING AXE**



- Head forged from high quality carbon steel, Teflon coated.
- The arc-shaped blade is hardened in accordance with DIN 7287 to a hardness of HRC 47-55 up to 30 mm from the edge.
- Shock-absorbing nylon trouser, lighter and stronger than steel.
- Perfectly balanced structure
- The modern handle structure, which is additionally coated with TPR, ensures better control of the axe.







- CARBON HRC 47-55 PTFE SHANK OF NYLON
- Head forged from high quality carbon steel, Teflon coated.
- The arc-shaped blade is hardened in accordance with DIN 7287 to a hardness of HRC 47-55 up to 30 mm from the edge.
- Shock-absorbing nylon trouser, lighter and stronger than steel.
- Perfectly balanced structure.
- The modern handle structure, which is additionally coated with TPR, ensures better control of the axe.



# **GARDEN MACHETE**



- The machete blade is made of 1050 C50 carbon steel.
- Machine sharpened and made from one piece of steel.
- Handle made of PP plastic, covered with soft TPR thermoplastic rubber.
- Blade weight: 540 g. Handle length 180 mm. Blade length 267 mm. Blade width 135 mm.
- The machete, a stump puller, 450mm, will work well for limbing branches from trees and felling very small trees.
- Thanks to the specially curved blade, branches can be quickly and easily trimmed right up to the tree trunk.

CODE CAT NO.
3-01-14-02-401 PRO-BS401

#### STEEL WEDGE

- Made of high quality forged steel.
- Used for splitting wood, stumps.
- Weight: 2 kg





CODE	CAT NO.	WEIGHT
3-01-14-01-130	PRO-BS130	2000 g

# NYLON WEDGE

- Made of durable and lightweight nylon.
- Used for splitting wood, stumps.
- Weight: 300 g or 470 g
- Dimensions: 230 x 70 x 30 mm

CODE	CAT NO.	WEIGHT
3-01-14-01-133	PRO-BS133	300 g
3-01-14-01-134	PRO-BS134	470 g







#### **MULTI-PURPOSE KNIVES**

#### NÓŻ PR-90-01



CODE	CAT NO.	BLADE WIDTH
2 04 00 25 004	DDO NILIO01	10 mm

SK5 STEEL

> SK5 STEEL

BLADE

3 BLADES

BLADES

BLADE

LOCK

BLADE LOCK

BLADE

LOCK

Zn

BODY

- Universal knife made of materials that guarantee long-term use.
- Sturdy housing with rubber parts for a secure grip while working.
- Innovative handle design with storage for 2 spare blades.
- Blade lock in knob on side of housing.
- Blade width 18 mm.
- 3 blades included.

#### **KNIFE PR-90-02**



- Universal knife made of materials that guarantee long-

- Sturdy housing with rubber parts for a secure grip while working.
- Innovative handle design with storage for 4 spare blades.
- Blade lock in slider on side of housing.
- Blade width 18 mm.
- 5 blades included.

#### **KNIFE PR-92-03**



 CODE
 CAT NO.
 BLADE WIDTH

 3-01-08-25-010
 PRO-NU010
 18 mm

- Zinc (Zn) housing, solid and very durable.

- Comfortable and ergonomic handle design, with non-slip rubber insert for comfort combined with safety.
- Steel guide bar and locking knob for safety and tool life.
- Blade made of high-grade carbon steel for three times longer life.
- Blade width 18 mm.
- 1 blade included.

#### **KNIFE PR-92-04**



SK5 STEEL BLADE LOCK BODY

- Zinc (Zn) housing, solid and very durable.
- Comfortable and ergonomic handle design, with extra notches for comfort, combined with safety in use.
- Steel guide bar and locking slide for safety and tool life.
- Blade made of high-grade carbon steel for three times longer life.
- Blade width 18 mm.

#### KNIFE PR-80-01



BI ADE

LOCK

BLADE

BLADE

BLADE

ARBON STEEL BODY

STEEL

BODY





CODE	CAT NO.	BLADE WIDTH
3-01-08-25-012	PRO-NU012	9mm
3-01-08-25-013	PRO-NU013	18mm

- Lightweight and very durable housing made of ABS.
- Comfortable and ergonomic handle design for convenience, combined with safe use.
- Multi-position safety zipper.
- Blade made of high-grade carbon steel for three times longer life.
- The knife is also equipped with a retaining clip.
- Blade width 9 or 18 mm.
- 1 breakaway blade included.
- Knives 9 mm, 36 pieces, knives 18 mm, 24 pieces.

#### **KNIFE PR-80-10**





CAT NO.	BLADE WIDTH
PRO-NU019 9 i	mm

PRO-NU020 18mm

- Carbon steel housing, sturdy and very durable.

- Comfortable and ergonomic handle design for convenience combined with safe use.
- Steel guide bar for safety and durability of the tool.
- AUTOLOCK function locks the blade.
- Blade made of high-grade carbon steel for three times longer life.
- 1 blade included.

#### **KNIFE PR-92-05**

CODE 3-01-08-25-019 3-01-08-25-020





CODE	CAT NO.	BLADE WIDTH
3-01-08-25-017	PRO-NU017	18mm

- Universal knife made of materials that guarantee long-
- Steel case, sturdy and very durable.
- Comfortable and ergonomic handle design for convenience combined with safe use.

STEEL

- Steel guide bar and locking knob for safety and tool life.
- Quick-change blade system.
- Blade width 18 mm.
- Blade made of high quality carbon steel.

KNII	 DD	_0	n_	NΕ



SK5 STEEL

BLADE LOCK

BLADE

PLASTIC BODY



CODE	CAT NO.	BLADE WIDTH	
3-01-08-25-018	PRO-NUM18	25 mm	

- Plastic housing, sturdy and very durable.
- Comfortable and ergonomic handle design, with a non-slip rubber finish for comfort combined with safety.
- Steel guide bar and locking slide for safety and tool life.
- Blade made of high-grade carbon steel for three times longer life.
- Blade width 25 mm.
- 1 blade included.

#### **KNIFE PRO-NU130**



 CODE
 CAT NO.
 BLADE WIDTH

 3-01-08-25-130
 PRO-NU130
 18mm

12 SOFT STEEL SK2

- Made of materials that guarantee long-term use.
- Made of durable ABS soft thermopolymer giving a pleasant feel.
- Automatic blade lock.
- Precise plastic slider for smooth blade operation
- Convenient blade exchange thanks to the ergonomic snap lock.

#### **KNIFE PR-91-01**



 CODE
 CAT NO.
 BLADE WIDTH

 3-01-08-25-007
 PRO-NU007
 18mm

BLADE

- Lightweight and very durable housing.
  - Comfortable and ergonomic handle design with anti-slip rubber finish for comfort, combined with safety of use.
  - Blades made of high-grade carbon steel for 3x extended life.
  - 1 blade included.

# FLEXIBLE KNIFE FOR FINISHING



CODE CAT NO. BLADE WIDTH
3-01-08-25-029 PRO-NU029 12.5 mm



LASER SHARPENEI

STEEL

SUPER FLEXIBLE

SK2 STEEL

SK5

STEEL

SK5 STEEL

- Made of durable ABS thermopolymer for long use.
- Blade made of SK2 steel, laser sharpened to a thickness of 0.2mm.

BLADE

- Super flexible, one-piece blade with exceptional durability. Automatic blade lock.
- Precision plastic slider for smooth blade operation.

#### KNIFE PR-93-01





 CODE
 CAT NO.
 BLADE WIDTH

 3-01-08-25-008
 PRO-NU008

- Very durable aluminum (Al) alloy housing.
- A button located in its body allows to fold the knife.
- The knife is also equipped with a retaining clip.
- Comfortable and ergonomic handle for convenience, combined with safe use.
- Knife structure entirely made of stainless steel.
- Blade made of high-grade carbon steel for 3x extended life.
- 1 blade included.

#### **KNIFE PR-93-05**



CODE CAT NO. BLADE WIDTH
3-01-08-25-021 PRO-NU021

STAINLESS STEEL GUIDE SK5 BLADE

BI L

BLADE

BLADE LOCK Zn BODY

- Zinc and solid case with a very durable rubber coating.
- Comfortable and ergonomic handle design, with non-slip rubber insert for comfort combined with safety.
- Steel guide bar for safety and durability of the tool.
- AUTOLOCK function locks the blade.
- Blade made of high-grade carbon steel for three times longer life.

#### KNIFE PR-93-06E



CODE	CAT NO.	BLADE WIDTH
3-01-08-25-027	PRO-NU027	18mm













- Made of materials that guarantee long-term use. The housing is solid steel and very durable.
- Comfortable and ergonomic handle design for convenience, combined with safe use.
- Steel guide and slider for safety and durability of the tool.
- Blade thickness 0,7mm, made of SK2 steel, laser sharpened.

#### **KNIFE PR-80-03**



CODE	CAT NO.	BLADE WIDTH
3-01-08-25-125	PRO-NU125	18 mm

1 BLADE

ABS

TPR

SK5 STEEL

- Made of durable ABS plastic covered with thermoplastic rubber (TPR) for long-lasting use
- Automatic blade lock.
- Plastic slider for smooth blade operation.
- To replace the blade, move the slider with the blade down.

#### **KNIFE PR-80-04**



CODE CAT NO. BLADE WIDTH
3-01-08-25-126 PRO-NU126 18mm



ABS

TPR

SK5 STEEL

- Made of durable ABS plastic covered with thermoplastic rubber (TPR) for long use
- Automatic blade lock.
- Plastic slider for smooth blade operation.
- To replace the blade, move the slider with the blade down.

# SAFETY KNIVES





CODE	CAT NO.	BLADE WIDTH
3-01-08-25-014	PRO-NU014	

1 BLADE SLIDE

AL BODY

SK5 STEEL

- Safety knife, you need to move the slider to eject the blade.
- The blade automatically retracts when the slider is released.
- Very durable aluminum alloy housing.
- The knife is also equipped with a clip.
- Comfortable and ergonomic handle combined with safety thanks to additional non-slip elements.
- Rough knife design for added safety.
- Slider with non-slip element for increased control during operation.
- Blade made of high-grade carbon steel for three times longer life.

#### PR-00-02







TPR

BLADE MAGAZINE 4 BLADES



- Automatically retracts blade when the slider is released.
- Very durable aluminum alloy (AI) housing.
- Comfortable and ergonomic handle provides comfort and safe use with additional anti-slip features. Thermoplastic rubber (TPR) coated zipper for increased control during use.
- Blade made of high quality carbon steel (SK5).
- 4 blades included (3 in tray).
- Blade storage in the handle.
- Blade can be replaced by pressing the "padlock".

#### PLASTIC FOLDING KNIFE

PR-93-



- 12 SK5 ABS pcs.
- Comfortable and ergonomic handle made of durable ABS plastic for convenient use.
- Button for folding the knife.
- Blade made of high-grade carbon steel (SK5) for three times longer life.
- The package contains 12 pieces

CODE	CAT NO.
3-01-08-25-024	PRO-NU024

#### **PAINT SCRAPERS**

PR-SC-100





- For removing old paint and wallpapers.
- Convenient handle made of durable ABS and 300mm total length.
- Aluminum structure
- Secure blade attachment with screws.

CODE	CAT NO.
3-01-08-25-101	PRO-WA101

PR-SC-90











90

10 PCS.

- For removing old paint and wallpapers.
- Convenient two-component handle.
- Carbon steel blade.
- Secure retracting and extending the blade.

CODE	CAT NO.
3-01-08-25-100	DDO-1/1/100

5 BLADES

#### REPLACEMENT BLADE FOR PAINT SCRAPER 90MM

PR-SCB-90



- Replacement blade for paint scraper.
- Blade width 90 mm.
- Carbon steel blade.
- 5 pieces.

CODE	CAT NO.
3-01-08-25-110	PRO-WA110

#### REPLACEMENT BLADES FOR KNIVES





- Blade made of SK2 steel, laser sharpened.
- Blade thickness 0.2 mm. Blade width 12.5 mm.
- Super flexible, one-piece blade with exceptional durability.
- 10 pieces per pack

CODE	CAT NO.
3-01-08-25-030	PRO-NU030

PR-92-20



- Hook blades with trapezoidal shape for multi-purpose knives.
- SK5 STEEL

CARBON STEEL

10 PCS.

10 PCS.

10

PCS.

10 PCS.

- 10 pieces per package.
- Blades made of carbon steel, for three times longer tool life.
- Designed for cutting materials available in sheets, such as floor coverings, plastic sheets, etc.

CODE	CAT NO.
3-01-08-25-009	PRO-NU009

#### PR-90-03, PR 92-25



- 10 pieces per package.

- Blades made of carbon steel for three times longer tool life.

CODE	CAT NO.	BLADE WIDTH
3-01-08-25-003	PRO-NU003	18mm
3-01-08-25-025	PRO-NU025	25mm

SK5 STEEL

#### PR-90-04



- 10 pieces per package.

- Blades made of carbon steel for three times longer tool life.

CODE	CAT NO.	BLADE WIDTH
3-01-08-25-015	PRO-NU015	9mm

SK5 STEEL

#### PR-92-10



- 10 pieces per package.

- Blades made of carbon steel for three times longer tool life.

CODE	CAT NO.
3-01-08-25-005	PRO-NU005

CARBON STEEL

#### SK2-BLACK









SK5 STEEL



10

PCS.

- Blade thickness: 0.7mm
- Made of SK2 steel, laser sharpened.
- There are 10 blades in the package.

CODE	CAT NO.	BLADE WIDTH
3-01-08-25-028	PRO-NU028	18 mm

#### SK5-BLACK



- Replacement blades for knives.

CODE	CAT NO.	BLADE WIDTH
3-01-08-25-026	PRO-NU026	18mm

#### PLASTERBOARD CUTTER







BLADE

150mm





CODE CAT NO.
3-01-16-02-001 PRO-NS001

- Ergonomic handle made of ABS.
- Handle finished with TPR anti-slip rubber.
- Precision triple ground teeth.
- Impulse-hardened teeth require no sharpening.
- HRC hardness of 50 56, allowing work at maximum pressure.
- 50% faster cutting thanks to aggressive tooth geometry.
- Saw blade made of resilient 65 Mn manganese steel.
- Easy piercing of plates without pre-cuts.
- System to prevent jamming during cutting.
- For cutting holes in plasterboard.
- 7 teeth / inch (7T/8P).
- Blade length 150 mm.

#### **CUTTER FOR POLYSTYRENE FOAM AND INSULATION**

3Cr13 STEEL

345mm BLADE 500mm KNIFE



CAT NO.

PRO-NS103

3-01-16-02-103

- Styrofoam and insulation cutter with specially ground teeth to cut a variety of insulation materials without tearing or blocking the knife.
- Contoured two-component plastic handle for safe working.
- Excellent cutting durable blade made of 3CR13 stainless steel, which has the advantage of high corrosion resistance, easy processing and sharpening.
- Blade length 345 mm.
- Total knife length 500mm.

#### **CUTTER FOR MINERAL WOOL AND POLYSTYRENE**

3Cr13 STEEL 280mm BLADE 415mm KNIFE



- A cutter for mineral wool and polystyrene foam with specially ground teeth, allowing to cut a variety of insulation materials without tearing them or blocking the cutter.
- Contoured plastic handle for safe work.
- Perfect cutting durable blade made of 3CR13 stainless steel.
- Blade length 280 mm.
- Double-sided blade.
- Total knife length 415 mm.

CODE CAT NO.
3-01-16-02-102 PRO-NS102

# CROSSCUT SAW 7T

400mm 450mm 500mm

7T 8P 65Mn

HRC 50-56









- Ergonomic handle made of ABS, bolted with three screws.
- Handle finished with TPR anti-slip rubber.
- Finger protection grip profile.
- Precision triple ground teeth.
- Impulse-hardened teeth require no sharpening.
- HRC hardness of 50 56, allowing work at maximum pressure.
- 50% faster cutting thanks to aggressive tooth geometry.
- Saw blade made of resilient 65 Mn manganese steel.
- 90° and 45° angles included in the saw handle.
- 7 teeth / inch (7T/8P).
- Blade lengths 400, 450 and 500 mm.

CODE	CAT NO.	DIMENSIONS
3-01-16-00-001	PRO-PD001	400 mm
3-01-16-00-002	PRO-PD002	450 mm
3-01-16-00-003	PRO-PD003	500 mm





11T 12P

65Mn

HRC 50-56







CODE	CAT NO.	DIMENSIONS
3-01-16-02-00-011	PRO-PD011	400mm
3-01-16-02-00-012	PRO-PD012	450mm
3-01-16-02-00-013	PRO-PD013	500 mm

- Ergonomic handle made of ABS, bolted with three screws.
- Handle finished with TPR anti-slip rubber.
- Finger protection grip profile.
- Precision triple ground teeth.
- Impulse-hardened teeth require no sharpening.
- HRC hardness of 50 56, allowing work at maximum pressure.
- $\mbox{-}\ 50\%$  faster cutting thanks to aggressive tooth geometry.
- Saw blade made of resilient 65 Mn manganese steel.
- $90^{\circ}$  and  $45^{\circ}$  angles included in the saw handle.
- 11 teeth / inch (11T/12P).
- Blade lengths 400, 450 and 500 mm.

# SAW FOR CELLULAR CONCRETE 17T



















- Ergonomic handle made of ABS, bolted with three screws.
- Handle finished with TPR anti-slip rubber.
- Teeth that do not require sharpening.
- Carbide teeth welded to the saw blade.
- 50% faster cutting.
- Teflon-coated saw blade.
- Saw blade made of resilient 65 Mn manganese steel.
- $90^{\circ}$  and  $45^{\circ}$  angles included in the saw handle.
- Saw for easy cutting of cellular concrete blocks.
- 17 carbide teeth.
- Length 600 mm



#### **SAW FOR CELLULAR CONCRETE 33T**



33













- Ergonomic handle made of ABS, bolted with three screws. finished with TPR anti-slip rubber.

   Non-sharpening 33 teeth carbide-welded to the saw.
- Non-sharpening 33 teeth, carbide-welded to the saw blade. 50% faster cutting.
- Teflon-coated saw blade lobe made of resilient 65 Mn manganese steel.
- 90° and 45° angles included in the saw handle. Saw for easy cutting of cellular concrete blocks.

CODE	CAT NO.	DIMENSIONS
3-01-16-01-002	PRO-PK002	600 mm













- Powder coated steel frame.
- Handle finished with non-slip sponge.
- TPR and ABS handle.
- 65 Mn manganese steel blade.
- HRC 44-48.

CODE	CAT NO.	DIMENSIONS
3-01-24-PK-105	PRO-PD105	530mm
3-01-24-PK-006	PRO-PD006	610mm
3-01-24-PK-007	PRO-PD007	760mm

# SAWS FOR METAL

**SAWS FOR METAL PRO-PM101** 









- Round lacquered steel frame.
- Aluminum handle.
- 1 blade included.

3-01-24-PK-101	PRO-PM101	300mm
CODE	CAT NO.	DIMENSIONS

#### METAL SAW PRO-PM202









- Square lacquered steel frame.
- Aluminum handle.
- 1 blade included.
- Easier blade replacement.
- Possibility to place the blade horizontally.

CODE	CAT NO.	DIMENSIONS
3-01-24-PK-202	PRO-PM20	2 300mm

#### 3-COMPONENT METAL SAW PRO-PM203





1

BLADE

280 mm





CODE	CAT NO.	DIMENSIONS
3-01-24-PK-203	PRO-PM203	300mm

- Finished with TPR anti-slip rubber.
- 3-component handle.
- 1 blade included.

#### **METAL SAW PRO-PM204**





- 2-component handle.

- It is used to cut steel, pipes, plastics, etc.

CODE CAT NO. DIMENSIONS 3-01-24-PK-204 PRO-PM204 280 mm

# SAW BLADES

#### **BIMETAL SAW BLADE**



- 24 teeth/inch.
- Made of M2 molybdenum based high speed steel.
- High resistance to abrasion and bending.
- Thermoplasticity increased by 50% compared to carbon steel.
- HARDNESS HRC 64-65.

#### FLEXIBLE METAL SAW BLADE



300



- 24 teeth/inch.
- Made of resilient 65 Mn manganese steel.
- Very high flexibility.
- HRC hardness of 50 56, allowing work at maximum pressure.

#### SAW BLADE FOR WET WOOD



CODE	CAT NO.	DIMENSIONS
3-01-24-PK-023	PRO-PD023	530mm
3-01-24-PK-024	PRO-PD024	610mm
3-01-24-PK-025	PRO-PD025	760mm











- For cutting fresh branches or those soaked in water.
- Made of 65 Mn manganese steel.
- Teeth hardened and profiled.
- Blade sharpened and hardened on both sides.

#### **DRY WOOD SAW BLADE**





- For cutting dry wood.
- Made of 65 Mn manganese steel.
- Teeth hardened and profiled.
- Blade sharpened and hardened on both sides.

CODE	CAT NO.	DIMENSIONS
3-01-24-PK-020	PRO-PD020	530mm
3-01-24-PK-021	PRO-PD021	610mm
3-01-24-PK-022	PRO-PD022	760mm

#### STRAIGHT SHEET METAL SHEARS



CODE CAT NO.
3-01-23-NB-202 PRO-NB202









- Chrome-molybdenum additionally hardened steel blades.
- Non-slip blade finish for greater cutting precision and increased safety.
- Cutting edges induction hardened, hardness 56-60 HRC.
- Useful for cutting cold rolled steel sheets with thicknesses up to 1.2 mm, aluminum sheets up to 1.5 mm and stainless steel sheets up to 0.7 mm.

#### **LEFT SHEET METAL SHEARS**



CODE CAT NO.
3-01-23-NB-201 PRO-NB201







- Chrome-molybdenum, extra LEFT hardened steel blades.
- Non-slip blade finish for greater cutting precision and increased safety.
- Cutting edges induction hardened, hardness 56-60 HRC.
- Useful for cutting cold rolled steel sheets with thicknesses up to 1.2 mm, aluminum sheets up to 1.5 mm and stainless steel sheets up to 0.7 mm.

#### RIGHT SHEET METAL SHEARS



CODE	CAT NO.
3-01-23-NB-203	PRO-NB203







- · Chrome and molybdenum extra RIGHT hardened steel blades.
- Non-slip blade finish for greater cutting precision and increased safety.
- Cutting edges induction hardened, hardness 56-60 HRC.
- Useful for cutting cold rolled steel sheets with thicknesses up to 1.2 mm, aluminum sheets up to 1.5 mm and stainless steel sheets up to 0.7 mm.

# PELICAN LEFT SHEET METAL SHEARS









- Blades made of extra-hardened S55C carbon steel.
- Non-slip grips.
- Cutting edges of 56-60 HRC hardness.
- Useful for cutting cold rolled steel sheet up to 1.4 mm thick, copper sheet up to 2 mm thick and stainless steel sheet up to 1 mm thick.

#### PELICAN LEFT SHEET METAL SHEARS



STEEL





- Non-slip grips.
- Cutting edges of 56-60 HRC hardness.
- Useful for cutting cold rolled steel sheets with thickness up to 0.78 mm, copper sheets up to 0.94 mm and stainless steel sheets up to 0.6 mm.

#### STRAIGHT SHEET METAL SHEARS

CAT NO.

CODE

CODE

3-01-23-NB-002

3-01-23-NB-006











- Blades made of extra-hardened S55C carbon steel.
- Non-slip grips.
- Cutting edges of 56-60 HRC hardness.
- Useful for cutting cold rolled steel sheets with thickness up to 0.78 mm, copper sheets up to 2 mm and stainless steel sheets up to 0.6 mm.

#### PELICAN RIGHT SHEET METAL SHEARS

CAT NO.





STEEL



- Blades made of extra-hardened S55C carbon steel
- Non-slip grips.
- Cutting edges of 56-60 HRC hardness.
- Useful for cutting cold rolled steel sheets up to 1.4 mm thick, copper sheets up to 2 mm thick and stainless steel sheets up to 1 mm thick.

#### PELICAN RIGHT SHEET METAL SHEARS









- Blades made of extra-hardened S55C carbon steel
- Non-slip grips.
- Cutting edges of 56-60 HRC hardness.
- Useful for cutting cold rolled steel sheets with thickness up to 0.78 mm, copper sheets up to 0.94 mm and stainless steel sheets up to 0.6 mm.

# WIRE CUTTERS

CAT NO.

PRO-NB004

CODE

3-01-23-NB-004



CARBON STEEL HANDLE

18"







- Cutters for rods and wires.
- Designed for construction, service and workshop work in various
- Jaws of hardened chrome vanadium steel.
- Handles made of high quality carbon steel.
- Cutters equipped with a joint for greater cutting power.
- Ergonomic plastic handles.
- Jaw hardness: 50-56 HRC.







ANODIZED









- Workshop pliers.
- Cutting pliers.
- Knife.
- PH screwdriver.
- SL 1 screwdriver.
- SL 2 screwdriver.
- SL screwdriver and file.
- Steel lock.
- Small knife.
- Saw.
- Can opener.
- Bottle opener.

# **CUTTING TOOLS**

# **EMERGENCY MULTITOOL**















- Ratchet socket.
- Seatbelt cutter.
- Changing the direction of the ratchet.
- Hammer for glass.
- Battery.
- Saw.

- Knife.
- PH/SL bits.
- Can opener.
- Bottle opener.
- Wrench for 6 sizes of screws.
- LED flashlight.

CODE	CAT NO.
3-01-32-MT-002	PRO-MT002

## MULTIFUNCTION KNIFE WITH LED













- Knife.

- Saw.
- Bottle opener.
- SL/PH screwdrivers.
- Can opener.
- Corkscrew.
- Needle with a hole.
- File.
- LED flashlight.
- Battery.

CODE	CAT NO.
3-01-32-MT-004	PRO-MT004

# **LOCKABLE FOLDING KNIFE**



ANODIZED AI







- Chrome-vanadium blade.
- Blade lock.

**CODE** 3-01-32-MT-005 CAT NO. PRO-MT005

# SMALL MULTITOOL WITH LED FLASHLIGHT





- Knife.
- LED flashlight.
- Bottle opener.
- PH screwdriver.
- Clip hook.
- Hex key.
- Battery.

6 FUNCTIONS	3Cr13 STAINLESS STEEL	ANODIZED AI	LED FLASHLIGHT
/		/	

**CODE** 3-01-32-MT-007

CAT NO. PRO-MT007

# **CUTTING TOOLS**

## **PVC PIPE CUTTERS**

An indispensable tool for installation work where PVC, PP, PU and PE pipes are used. It allows to precisely cut the pipe to the desired size while maintaining an even and unsharpened cut

**Note!** In cold weather (such as winter), warm the tubing in warm water to protect it from cracking.

**PVC PIPE CUTTER 0-42MM STEEL 65MN** 

OSTRZE

ALUMINUM CASTING CUTTING SCOPE 0-42 mm

> SCOPE 0-42 mi

CUTTIN

G SCOPE

ALUMINUM CASTING

ALUMINUM CASTING

- Blade material 65Mn with electroplated coating
- Rubberized handle for more comfortable working
- The body made of hardened aluminum
- Automatic jaw opening, one-hand operation possible.

#### **PVC PIPE CUTTER 0-42MM STEEL 65MN**

CAT NO.

PRO-BY101

CODE

**CODE** 3-01-18-20-102

CODE

CODE

3-01-18-20-107

3-01-18-20-103

3-01-18-20-101



- Blade material 65Mn with electroplated coating

- The body made of hardened aluminum

- Manual jaw opening.

## PVC PIPE CUTTER 0-51MM STEEL 65MN

CAT NO.

PRO-BY102



- Blade material 65Mn with electroplated coating

- Rubberized handle for more comfortable working

- The body made of hardened aluminum

- Automatic jaw opening, one-hand operation possible.

# COPPER PIPE CUTTERS

CAT NO.

PRO-BY107

CAT NO.

PRO-BY103

PIPE CUTTER 3-22MM STEEL SK5



Compact a confined sp

Compact and robust design perfect for use in confined spaces.

- The cutter made of high quality aluminum.

Comfortable handle for quick adjustment, and cutting.

- Cutting range 3-22mm.

- Blade made of SK5 steel.

#### PIPE CUTTER 3-35MM STEEL SK5



 Compact and robust design perfect for use in confined spaces. ALUMINUM SK5 CASTING CUTTING SCOPE 3-35 mm

CUTTING SCOPE 3-22 mm

- The cutter made of high quality aluminum.

- Comfortable handle for quick adjustment, and cutting.

- Cutting range 3-35mm.

- Blade made of SK5 steel.

# 12



## **DRILL BITS FOR METAL**

#### HSS4241













- HSS 4241 rolled drill bits for metal.
- Universal application.
- Apex angle 118°.
- High drilling performance and long service life.
- Manufactured to DIN 338 standards.

CODE	CAT NO.	DIMENSIONS	CODE	CAT NO.	DIMENSIONS	CODE	CAT NO.	DIMENSIONS
3-01-10-WS-001	PRO-WS001	1.0mm	3-01-10-WS-008	PRO-WS008	4.5mm	3-01-10-WS-015	PRO-WS015	8.0mm
3-01-10-WS-002	PRO-WS002	1.5mm	3-01-10-WS-009	PRO-WS009	5.0mm	3-01-10-WS-016	PRO-WS016	8.5mm
3-01-10-WS-003	PRO-WS003	2.0mm	3-01-10-WS-010	PRO-WS010	5.5mm	3-01-10-WS-017	PRO-WS017	9.0mm
3-01-10-WS-004	PRO-WS004	2.5mm	3-01-10-WS-011	PRO-WS011	6.0mm	3-01-10-WS-018	PRO-WS018	9.5mm
3-01-10-WS-005	PRO-WS005	3.0mm	3-01-10-WS-012	PRO-WS012	6.5mm	3-01-10-WS-019	PRO-WS019	10mm
3-01-10-WS-006	PRO-WS006	3.5mm	3-01-10-WS-013	PRO-WS013	7.0mm	3-01-10-WS-020	PRO-WS020	) 12mm
3-01-10-WS-007	PRO-WS007	4 0mm	3-01-10-WS-014	PRO-WS014	7 5mm			

#### **HSS TITANIUM-COATED**





CODE	CAT NO.	DIMENSIONS	CODE	CAT NO.	DIMENSIONS
3-01-10-WS-101	PRO-WS101	1.0mm	3-01-10-WS-111	PRO-WS111	6.0mm
3-01-10-WS-102	PRO-WS102	1.5mm	3-01-10-WS-112	PRO-WS112	6.5mm
3-01-10-WS-103	PRO-WS103	2.0mm	3-01-10-WS-113	PRO-WS113	7.0mm
3-01-10-WS-104	PRO-WS104	2.5mm	3-01-10-WS-114	PRO-WS114	7.5mm
3-01-10-WS-105	PRO-WS105	3.0mm	3-01-10-WS-115	PRO-WS115	8.0mm
3-01-10-WS-106	PRO-WS106	3.5mm	3-01-10-WS-116	PRO-WS116	8.5mm
3-01-10-WS-107	PRO-WS107	4.0mm	3-01-10-WS-117	PRO-WS117	9.0mm
3-01-10-WS-108	PRO-WS108	4.5mm	3-01-10-WS-118	PRO-WS118	9.5mm
3-01-10-WS-109	PRO-WS109	5.0mm	3-01-10-WS-119	PRO-WS119	10.0mm
3-01-10-WS-110	PRO-WS110	5.5mm	3-01-10-WS-120	PRO-WS120	12.5mm









- HSS titanium coated metal drill bits.
- Drill spiral, ground.
- Drill bits manufactured to DIN 338 standard.
- Point angle 135° for perfect centering.
- Made of HSS high speed steel.
- Titanium nitride coating reduces vibration and increases drill bit life.
- Fast drilling by 40-60% compared to traditional drill bits.
  Ideal for precise, repeatable
- drilling.
   Very high surface
- hardness.
   Handle: cylindrical.

### **HSS CO COBALT**





CODE	CAT NO.	DIMENSIONS	CODE	CAT NO.	DIMENSIONS
3-01-10-WS-201	PRO-WS201	1.0mm	3-01-10-WS-212	PRO-WS212	6.5mm
3-01-10-WS-202	PRO-WS202	1.5mm	3-01-10-WS-213	PRO-WS213	7.0mm
3-01-10-WS-203	PRO-WS203	2.0mm	3-01-10-WS-214	PRO-WS214	7.5mm
3-01-10-WS-204	PRO-WS204	2.5mm	3-01-10-WS-215	PRO-WS215	8.0mm
3-01-10-WS-205	PRO-WS205	3.0mm	3-01-10-WS-216	PRO-WS216	8.5mm
3-01-10-WS-206	PRO-WS206	3.5mm	3-01-10-WS-217	PRO-WS217	9.0mm
3-01-10-WS-207	PRO-WS207	4.0mm	3-01-10-WS-218	PRO-WS218	9.5mm
3-01-10-WS-208	PRO-WS208	4.5mm	3-01-10-WS-219	PRO-WS219	10.0mm
3-01-10-WS-209	PRO-WS209	5.0mm	3-01-10-WS-220	PRO-WS220	11.0mm
3-01-10-WS-210	PRO-WS210	5.5mm	3-01-10-WS-221	PRO-WS221	12.00mm
3-01-10-WS-211	PRO-WS211	6.0mm	3-01-10-WS-222	PRO-WS222	13.00mm









- Spiral drill bit made of high quality alloyed high speed steel according to DIN 338, cobalt content 5%.
- Right-hand spiral N-type.
- Point angle 135.°
- Cross ground in compliance with DIN1412C.
- Diameter tolerance h 8.
- Solid bar ground spiral drill bit with excellent outer surface finish.
- Precision drill bits with high heat resistance and durability.
- For use on drill stands or column drills.
- For alloy and carbon steels with tensile strength up to 1000 N/mm, stainless steel V2A/ V4A, grey cast iron, iron sinter, acid and heat resistant steels.

## SET OF DRILL BITS FOR METAL 5 PCS.

#### **HSS 4241**











- HSS 4241 rolled drill bits for metal.

- Universal application.
- Apex angle 118°.
- High drilling performance and long service life.
- Manufactured in compliance with DIN 338 standards.
- Cylindrical tool holder.
- 5 pcs. dimensions: 3, 4, 5, 6, 8 x 160 mm.

CODE CAT NO.

3-01-10-WZ-030 PRO-ZW030

## DRILL BIT SETS FOR METAL 19 PCS.

#### SETS:

#### Sets include 19 drill bits with diameters:

- 1.0 mm, - 3.5 mm, - 6.0 mm, - 8.5 mm, - 1.5 mm, - 4.0 mm, - 6.5 mm, - 9.0 mm, - 2.0 mm, - 4.5 mm, - 7.0 mm, - 10.0 mm. - 2.5 mm, - 5.0 mm, - 7.5 mm,

- 3.0 mm, - 5.5 mm, - 8.0 mm,

#### HSS DRILL BIT SET 4241













- HSS 4241 rolled drill bits for metal.
- Universal application.
- Apex angle 118°.
- High drilling performance and long service life.
- Manufactured to DIN 338 standards.

**CODE CAT NO.**3-01-10-WZ-020 PRO-ZW020

#### TITANIUM COATED DRILL BIT SET















- Made of HSS high speed steel.
- Drill spiral, ground. Handle: cylindrical.
- Drill bits manufactured to DIN 338 standard. Very high surface hardness.
- Point angle 135° for perfect centering.
- Titanium nitride coating reduces vibration and increases drill bit life. Ideal for precise, repeatable drilling.
- Fast drilling by 40-60% compared to traditional drill bits.

#### HSS CO (COBALT) DRILL BIT SET

















- Spiral drill bit made of high quality alloyed high speed steel according to DIN 338, cobalt content 5%
- Right-hand helical type N. Point angle 135°.
- Cross ground in compliance with DIN1412C.
- Diameter tolerance h 8.
- Solid bar ground spiral drill bit with excellent outer surface finish.
- Precision drill bits with high heat resistance and durability.
- For use on drill stands or column drills.
- For alloy and carbon steels with tensile strength up to 1000 N/mm, stainless steel V2A/ V4A, grey cast iron, iron sinter, acid and heat resistant steels.

## **CYLINDRICAL WIDIA DRILLS**













CODE	CAT NO.	DIMENSIONS
3-01-10-WS-301	PRO-WS301	3 × 60 mm
3-01-10-WS-302	PRO-WS302	4 × 120 mm
3-01-10-WS-303	PRO-WS303	5 × 85 mm
3-01-10-WS-304	PRO-WS304	5 × 120 mm
3-01-10-WS-305	PRO-WS305	6 × 100 mm
3-01-10-WS-306	PRO-WS306	6 × 200 mm
3-01-10-WS-307	PRO-WS307	8 × 120 mm
3-01-10-WS-308	PRO-WS308	8 × 200 mm
3-01-10-WS-309	PRO-WS309	8 × 300 mm

CODE	CAT NO.	DIMENSIONS
3-01-10-WS-310	PRO-WS310	10 × 300 mm
3-01-10-WS-311	PRO-WS311	10 × 120 mm
3-01-10-WS-312	PRO-WS312	10 × 200 mm
3-01-10-WS-313	PRO-WS313	12 × 150 mm
3-01-10-WS-314	PRO-WS314	12 × 200 mm
3-01-10-WS-315	PRO-WS315	12 × 300 mm
3-01-10-WS-316	PRO-WS316	14 × 150 mm
3-01-10-WS-317	PRO-WS317	14 × 200 mm

- Cylindrical stone widia drills.
- Universal application in various surfaced (masonry brick, silicate brick, etc.).
- High drilling performance and long service life.
- Tool holder: cylindrical.

## SDS PLUS ENDURANCE DRILL BITS













CODE	CAT NO.	DIMENSIONS	CODE	CAT NO.	DIMENSIONS
3-01-10-WS-401	PRO-WS401	5 × 110 mm	3-01-10-WS-419	PRO-WS419	12 × 310 mm
3-01-10-WS-402	PRO-WS402	5 × 160 mm	3-01-10-WS-420	PRO-WS420	12 × 360 mm
3-01-10-WS-403	PRO-WS403	6 × 110 mm	3-01-10-WS-421	PRO-WS421	12 × 460 mm
3-01-10-WS-404	PRO-WS404	6 × 160 mm	3-01-10-WS-422	PRO-WS422	14 × 160 mm
3-01-10-WS-405	PRO-WS405	6 × 210 mm	3-01-10-WS-423	PRO-WS423	14 × 210 mm
3-01-10-WS-406	PRO-WS406	6 × 260 mm	3-01-10-WS-424	PRO-WS424	14 × 260 mm
3-01-10-WS-407	PRO-WS407	8 × 110 mm	3-01-10-WS-425	PRO-WS425	14 × 310 mm
3-01-10-WS-408	PRO-WS408	8 × 160 mm	3-01-10-WS-426	PRO-WS426	14 × 360 mm
3-01-10-WS-409	PRO-WS409	8 × 210 mm	3-01-10-WS-427	PRO-WS427	14 × 400 mm
3-01-10-WS-410	PRO-WS410	8 × 260 mm	3-01-10-WS-428	PRO-WS428	14 × 460 mm
3-01-10-WS-411	PRO-WS411	10 × 110 mm	3-01-10-WS-429	PRO-WS429	16 × 160 mm
3-01-10-WS-412	PRO-WS412	10 × 160 mm	3-01-10-WS-430	PRO-WS430	16 × 210 mm
3-01-10-WS-413	PRO-WS413	10 × 210 mm	3-01-10-WS-431	PRO-WS431	16 × 310 mm
3-01-10-WS-414	PRO-WS414	10 × 260 mm	3-01-10-WS-432	PRO-WS432	16 × 360 mm
3-01-10-WS-415	PRO-WS415	10 × 460 mm	3-01-10-WS-433	PRO-WS433	16 × 400 mm
3-01-10-WS-416	PRO-WS416	12 × 160 mm	3-01-10-WS-434	PRO-WS434	16 × 460 mm
3-01-10-WS-417	PRO-WS417	12 × 210 mm	3-01-10-WS-435	PRO-WS435	18 × 210 mm
3-01-10-WS-418	PRO-WS418	12 × 260 mm	3-01-10-WS-436	PRO-WS436	18 × 260 mm

	Dell b	4-		~f L	ماسات	بطناهييه	بمالم	04001	
-	ום וווזט	เร	made	ot r	าเฉท	quality	allov	steel.	

- Innovative carbide cutting geometry for aggressive demolition effect.
- Spiral with 4 coils for optimum burr removal.
- Reinforced helix bevel for optimal drilling when the drill bit is in contact with reinforcement.
- Core with reinforced helix geometry to give more energy when striking from a pitchfork drill crown.
- Designed for drilling in concrete.


CODE	CAT NO.	DIMENSIONS
3-01-10-WS-437	PRO-WS437	18 × 310 mm
3-01-10-WS-438	PRO-WS438	18 × 360 mm
3-01-10-WS-439	PRO-WS439	18 × 400 mm
3-01-10-WS-440	PRO-WS440	18 × 460 mm
3-01-10-WS-441	PRO-WS441	20 × 210 mm
3-01-10-WS-442	PRO-WS442	20 × 260 mm
3-01-10-WS-443	PRO-WS443	20 × 310 mm
3-01-10-WS-444	PRO-WS444	20 × 350 mm
3-01-10-WS-445	PRO-WS445	20 × 400 mm
3-01-10-WS-446	PRO-WS446	20 × 460 mm
3-01-10-WS-480	PRO-WS480	7 × 110 mm
3-01-10-WS-481	PRO-WS481	7 × 160 mm
3-01-10-WS-482	PRO-WS482	9 × 110 mm
3-01-10-WS-483	PRO-WS483	9 × 160 mm
3-01-10-WS-484	PRO-WS484	10 × 310 mm
3-01-10-WS-485	PRO-WS485	10 × 360 mm

#### SDS PLUS PGM CERTIFIED DRILL BITS









- Drill bits automatically soldered in a German vacuum furnace.
- Two carbide blades welded at 1120°C high temperature.
- Durable, stronger and highly resistant drill bit and blade surface.
- Classic winding makes it easy to transport the drilling dust and work efficiently.
- PGM Association Certified Drill www.pgm.eu
- Only the drills produced according to the latest technology and strict tolerance limits bear the PGM mark (Prüfgemein-schaft Mauerbohrer).
- The mark guarantees geometrically accurate holes so that the fasteners used will provide solid support and achieve rated values.
- Tool holder: SDS PLUS.

PGM CERTIFICATE+

CODE	CAT NO.	DIMENSIONS
3-01-10-WS-550	PRO-WS550	5 × 120 mm
3-01-10-WS-551	PRO-WS551	5 × 210 mm
3-01-10-WS-552	PRO-WS552	6 × 100 mm
3-01-10-WS-553	PRO-WS553	6 × 200 mm
3-01-10-WS-554	PRO-WS554	8 × 120 mm
3-01-10-WS-555	PRO-WS555	8 × 200 mm
3-01-10-WS-556	PRO-WS556	8 × 300 mm
3-01-10-WS-557	PRO-WS557	10 × 120 mm
3-01-10-WS-558	PRO-WS558	10 × 200 mm
3-01-10-WS-559	PRO-WS559	10 × 300 mm
3-01-10-WS-560	PRO-WS560	12 × 150 mm
3-01-10-WS-561	PRO-WS561	12 × 200 mm
3-01-10-WS-562	PRO-WS562	12 × 300 mm



#### SDS ENDURANCE MAX CROSS TIP DRILL BIT

45-51 HRC

89-91 HRA



40CR

YG8

40CR

YG8





- Drill bits made of high quality 40Cr alloy steel with HRC 45-51 hardness and tips made of YG8 high hardness carbide HRA 89-91.
- The full 4 coils of cutter and the reinforced centering tip give you the ability to drill safely into hard materials especially reinforced concrete.
- The electrofusion welding process makes the steel body and solid carbide tip tightly bonded to extend the life.
- The special shape of the grooves, enables fast transportation of drilling dust and high drilling speed.
- Tool holder: SDS PLUS

CODE	CAT NO.	DIMENSIONS	CODE
3-01-10-WS-500	PRO-WS500	5 × 160 mm	3-01-10-\
3-01-10-WS-501	PRO-WS501	5 × 210 mm	3-01-10-
3-01-10-WS-502	PRO-WS502	6 × 110 mm	3-01-10-\
3-01-10-WS-503	PRO-WS503	6 × 160 mm	3-01-10-
3-01-10-WS-504	PRO-WS504	6 × 210 mm	3-01-10-\
3-01-10-WS-505	PRO-WS505	6 × 260 mm	3-01-10-
3-01-10-WS-506	PRO-WS506	6 × 310 mm	3-01-10-\
3-01-10-WS-507	PRO-WS507	8 × 110 mm	3-01-10-
3-01-10-WS-508	PRO-WS508	8 × 160 mm	3-01-10-\
3-01-10-WS-509	PRO-WS509	8 × 210 mm	3-01-10-
3-01-10-WS-510	PRO-WS510	8 × 260 mm	3-01-10-\
3-01-10-WS-511	PRO-WS511	8 × 310 mm	3-01-10-
3-01-10-WS-512	PRO-WS512	8 × 460 mm	3-01-10-\

CODE	CAT NO.	DIMENSIONS
3-01-10-WS-513	PRO-WS513	10 × 110 mm
3-01-10-WS-514	PRO-WS514	10 × 160 mm
3-01-10-WS-515	PRO-WS515	10 × 210 mm
3-01-10-WS-516	PRO-WS516	10 × 260 mm
3-01-10-WS-517	PRO-WS517	10 × 310 mm
3-01-10-WS-518	PRO-WS518	10 × 460 mm
3-01-10-WS-519	PRO-WS519	10 × 600 mm
3-01-10-WS-520	PRO-WS520	12 × 160 mm
3-01-10-WS-521	PRO-WS521	12 × 210 mm
3-01-10-WS-522	PRO-WS522	12 × 260 mm
3-01-10-WS-523	PRO-WS523	12 × 310 mm
3-01-10-WS-524	PRO-WS524	12 × 460 mm
3-01-10-WS-525	PRO-WS525	12 × 600 mm

## DRILL BIT SETS FOR CONCRETE

SDS PLUS 4 PCS.





- Drill bits made of high quality alloy steel, creating a reliable
- Innovative carbide cutting geometry for aggressive demolition
- Core with reinforced helix geometry to give more energy when striking from a pitchfork drill crown.

CONCRETE

- Designed for drilling in concrete and stone.

 $\square$ N 8035

 $\square$ N

8035

- SDS tool holder.
- 4 pcs. sizes 5, 6, 8, 10 x 160 mm.

#### SDS PLUS 5 PCS.

3-01-10-WZ-031

3-01-10-WZ-032

CODE

CAT NO.

PRO-ZW031





- tool for the job. - Innovative carbide cutting geometry for aggressive demolition
- Core with reinforced helix geometry to give more energy when striking from a pitchfork drill crown.
- Designed for drilling in concrete and stone.
- SDS tool holder.
- 5 pcs. dimensions: 5, 6 x 110 mm i 8, 10, 12 x 160 mm.





## DRILL BIT SETS FOR STONE

CAT NO.

PRO-ZW035







 $\square$ IN

8039

- Universal application in various surfaced (masonry brick, silicate brick, etc.).
- High drilling performance and long service life.

 $\square$ N

8039

- Tool holder: cylindrical.
- 5 pcs. dimensions: 5 x 85 mm; 6 x 100 mm; 7, 8, 10 x 150 mm

#### WIDIA 8 PCS.

3-01-10-WZ-035

CODE



- Cylindrical widia drill bits for stone.

- Universal application in various surfaces (masonry brick, silicate brick, etc.).
- High drilling performance and long service life.
- Tool holder: cylindrical.
- 8 pc dimensions: 3 x 70 mm; 4 x 75 mm; 5 x 85 mm; 6, 7 x 100 mm; 8, 9, 10 x 120 mm

#### 3-01-10-WZ-036 PRO-ZW036



SDS

PLUS



40CR

YG8

40CR

YG8

# **POINT CHISELS**

#### **SDS PLUS**

CODE



CODE PRO-WA601 14 × 250 mm 3-01-10-WS-601

CAT NO.

- SDS-plus point chisel 250 mm.
- Point chisel for rotary hammers without rev-lock.
- Application: Concrete, brick.

#### **ENDURANCE SDS PLUS CRMO PICK**



CODE CAT NO. DIMENSIONS 3-01-10-WS-620 PRO-WS620 14 × 250 mm

- CRMO (chromium molybdenum) steel.
- Chisel point for rotary hammers without rev-lock.
- Processed material: concrete, reinforced concrete (ferroconcrete), granite, artificial and natural stone, brick, masonry, plaster, etc. size: 14 mm x 250 mm.
- Tool holder: SDS PLUS

#### **ENDURANCE SDS MAX CRMO PICK**



- CRMO (chromium molybdenum) steel.

- Point chisel for rotary hammers without rev-lock.

Processed material: concrete, reinforced concrete (ferroconcrete), granite, artificial and natural stone, brick, masonry, plaster, etc. size: 14 mm x 250 mm.



14×25

0

CrMo

CrMo



CODE CAT NO. DIMENSIONS 3-01-10-WS-630 PRO-WS630 18 × 280 mm

- Tool holder: SDS PLUS

## **MIDDLEBREAKER**

SDS PLUS CRMO MIDDLEBREAKER

14×24

SDS MAX





- High impact steel 40Cr.
- Curved shape of the working part for easier drilling of furrows.
- Recommended for use with rotary hammers.
- Application: Concrete, reinforced concrete, granite, artificial and natural stone, brick, masonry, plaster, etc.
- Size: 14 mm x 240 mm x 22 mm
- Tool holder: SDS PLUS

CODE	CAT NO.	DIMENSIONS
3-01-10-WS-615	PRO-WS615 14	1 × 240 × 22 mm

#### **SDS MAX MIDDLEBREAKER**

18×300 ×26mm

SDS MAX

STEEL 40CR



- High impact steel 40Cr.
- Curved shape of the working part for easier drilling of
- Recommended for use with rotary hammers.
- Application: Concrete, reinforced concrete, granite, artificial and natural stone, brick, masonry, plaster, etc.
- Size: 18 mm x 300 mm x 26 mm
- Tool holder: SDS MAX

CODE	CAT NO.	DIMENSIONS
3-01-10-WS-635	PRO-WS635 18	× 2300 × 26 mm



#### SDS PLUS FLAT CHISEL



- DSD PLUS flat chisel.
- For rotary hammers without rev-lock.
- Application: Concrete, brick.

CODE	CAT NO.	DIMENSIONS
3-01-10-WS-610	PRO-WA610	14 × 250 × 20 mm
3-01-10-WS-611	PRO-WA611	14 × 250 × 40 mm
3-01-10-WS-612	PRO-WA612	14 × 250 × 60 mm

#### **ENDURANCE SDS PLUS CRMO FLAT CHISEL**



STEEL 40CR





- CRMO (chromium molybdenum) steel.
- Point chisel for rotary hammers without rev-lock.
- Application: Concrete, reinforced concrete, granite, artificial and natural stone, brick, masonry, plaster, etc.
- Tool holder: SDS PLUS.

CODE	CAT NO.	DIMENSIONS
3-01-10-WS-621	PRO-WS621	14 × 250 × 20 mm
3-01-10-WS-622	PRO-WS622	14 × 250 × 40 mm
3-01-10-WS-623	PRO-WS623	14 × 250 × 60 mm

# ıs

# **POWER TOOL ACCESSORIES**

#### **ENDURANCE SDS MAX CRMO FLAT CHISEL**

SDS MAX

CrMo



- CRMO (chromium molybdenum) steel.
- Point chisel for rotary hammers without rev-lock.
- Application: Concrete, reinforced concrete, granite, artificial and natural stone, brick, masonry, plaster, etc.
- Tool holder: SDS max.

CODE	CAT NO.	DIMENSIONS
3-01-10-WS-631	PRO-WS631	18 × 280 × 25 mm
3-01-10-WS-632	PRO-WS632	18 × 300 × 50 mm
3-01-10-WS-633	PRO-WS633	18 × 300 × 70 mm

# HOLELSAWS

# DIAMOND DRY-CUTTING HOLESAW











- Diamond dry cutting holesaws with vacuum brazed diamond.
- M14 mounting spindle for direct mounting on an angle grinder.
- Designed for making holes in ceramic tiles, stone gres tiles and other hard materials.
- Sizes 5mm to 16mm additionally equipped with cooling wax, which facilitates ergonomic work.
- Circular motions during drilling are recommended to

#### WITH COOLING WAX

WITH COOL	ING WAX	
CODE	CAT NO.	DIMENSIONS
3-01-10-WA-292	PRO-WA292	5mm
3-01-10-WA-293	PRO-WA293	6mm
3-01-10-WA-294	PRO-WA294	8mm
3-01-10-WA-295	PRO-WA295	10mm
3-01-10-WA-296	PRO-WA296	12mm
3-01-10-WA-297	PRO-WA297	14mm
3-01-10-WA-298	PRO-WA298	16mm

#### WITHOUT WAX

CODE	CAT NO.	DIMENSIONS		
3-01-10-WA-299	PRO-WA299	18mm		
3-01-10-WA-300	PRO-WA300	20mm		
3-01-10-WA-301	PRO-WA301	25mm		
3-01-10-WA-302	PRO-WA302	27mm		
3-01-10-WA-303	PRO-WA303	35mm		
3-01-10-WA-304	PRO-WA304	38mm		

#### WITHOUT WAX

	PRO-WA305	45mm
3-01-10-WA-306		
0 01 10 11/1 000	PRO-WA306	55mm
3-01-10-WA-307	PRO-WA307	65mm
3-01-10-WA-308	PRO-WA308	68mm
3-01-10-WA-309	PRO-WA309	75mm

WET

#### **DIAMOND WET-CUTTING HOLESAW**














- CODE
   CAT NO.
   DIMENSIONS

   3-01-10-WA-200
   PRO-WA200
   20mm

   3-01-10-WA-201
   PRO-WA201
   25mm

   3-01-10-WA-202
   PRO-WA202
   30mm

   3-01-10-WA-203
   PRO-WA203
   35mm

   3-01-10-WA-204
   PRO-WA204
   38mm
- CODE
   CAT NO.
   DIMENSIONS

   3-01-10-WA-205
   PRO-WA205
   45mm

   3-01-10-WA-206
   PRO-WA206
   55mm

   3-01-10-WA-207
   PRO-WA207
   65mm

   3-01-10-WA-208
   PRO-WA208
   68mm

   3-01-10-WA-209
   PRO-WA209
   75mm
- The pilot drill allows for fast and precise cutting without chipping the materials being cut.
- Steel body with high quality diamond electroplated edge.
- A hole in the side of the drill provides effective cooling and removal of dust and chips.
- Equipped with a sponge for cooling the holesaw during operation and dust leveling.

#### **SDS WIDIA CONCRETE HOLESAW**



SDS ΥG PLUS

M22

- Diamond holesaws with YG8 tungsten carbide teeth for drilling in masonry, natural stone, artificial stone, concrete,
- The outer edge of the holesaw is provided with a spiral cut-out for the removal of material and holes for cooling the tool.
- SDS PLUS holder.

CODE	CAT NO.	DIMENSIONS
3-01-10-WA-401	PRO-WA501	65mm
3-01-10-WA-402	PRO-WA502	68mm
3-01-10-WA-403	PRO-WA503	80mm



WOOD

STEEL 65Mn **PILOT** DRILL

#### 7-IN-1 WOOD HOLE SAW





- Fret saws are designed for fast and precise drilling of holes in wood, plasterboard, chipboards, building panels, plastic, etc.
- Blades made of 65 Mn manganese steel. Blade teeth especially
- hardened. Finished with a steel clamping plate and pilot drill.
- Set includes 7 holesaws in sizes: 25mm, 32mm, 38mm, 45mm, 50mm, 56mm, 62mm.

# BITS FOR WOOD

#### AUGER DRILL BITS FOR WOOD



CODE

3-01-10-WS-709

3-01-10-WS-710



PRO-WS709

PRO-WS710 18x230 mm

CAT NO.

DIMENSIONS

16x230 mm







- Drill bits designed for deep and precise drilling in soft and hard wood, chipboard, plywood.
- They are made of high-grade carbon steel and end with a threaded guide cone for precise guidance.
- Used in construction joinery roofing and
- Drill bits manufactured to DIN1052 standard.

#### SPIRAL DRILL BITS FOR WOOD













CODE	CAT NO.	DIMENSIONS
3-01-10-WS-804	PRO-WS804	6x90 mm
3-01-10-WS-805	PRO-WS805	6x250 mm
3-01-10-WS-806	PRO-WS806	7x110 mm
3-01-10-WS-807	PRO-WS807	8x120 mm
3-01-10-WS-808	PRO-WS808	8x250 mm
3-01-10-WS-809	PRO-WS809	9x125 mm
3-01-10-WS-810	PRO-WS810	10x130 mm
3-01-10-WS-811	PRO-WS811	10x250 mm
3-01-10-WS-812	PRO-WS812	11x140 mm
3-01-10-WS-813	PRO-WS813	12x150 mm
3-01-10-WS-814	PRO-WS814	12x250 mm

- They are designed for precision drilling of small and medium diameter holes in the material.
- Drill bits designed for drilling in wood, uncoated chipboard, plywood and fiberboard.
- They are made of high quality carbon steel with a centering point and two cutting edges.
- Can be used in hand drills, electric drills and lathes.
- Point additionally machine sharpened for more accurate centering.
- Drill bits manufactured to a standard similar to DIN7487-G.

#### **DRILL BITS FOR WOOD**



CUTTING EDGES







CODE	CAT NO.	DIMENSIONS
3-01-10-WS-900	PRO-WS900	10x152 mm
3-01-10-WS-901	PRO-WS901	12x152 mm
3-01-10-WS-902	PRO-WS902	14x152 mm
3-01-10-WS-903	PRO-WS903	16x152 mm
3-01-10-WS-904	PRO-WS904	18x152 mm
3-01-10-WS-905	PRO-WS905	20x152 mm
3-01-10-WS-906	PRO-WS906	22x152 mm
3-01-10-WS-907	PRO-WS907	24x152 mm
3-01-10-WS-908	PRO-WS908	25x152 mm
3-01-10-WS-909	PRO-WS909	26x152 mm
3-01-10-WS-910	PRO-WS910	28x152 mm

CODE	CAT NO.	DIMENSIONS
3-01-10-WS-911	PRO-WS911	30x152 mm
3-01-10-WS-912	PRO-WS912	32x152 mm
3-01-10-WS-913	PRO-WS913	34x152 mm
3-01-10-WS-914	PRO-WS914	35x152 mm
3-01-10-WS-915	PRO-WS915	36x152 mm
3-01-10-WS-916	PRO-WS916	38x152 mm
3-01-10-WS-917	PRO-WS917	40x152 mm
3-01-10-WS-918	PRO-WS918	45x152 mm
3-01-10-WS-919	PRO-WS919	48x152 mm
3-01-10-WS-920	PRO-WS920	50x152 mm

- Drill bits for larger diameters.
- They have curved cutting edges for precise cutting.
- Special design for easy drilling into hard wood and e.g. knots.
- Drill bits hardened for longer service life and greater durability.

## SHIELDS

Discs / Wheels - an abrasive tool consisting of abrasive grains and an abrasive carrier - a bond. The abrasive grains (alumina, silicon carbide, boron nitride, or diamond) do not have any specific shape, and their size affects the specific surface roughness.

Ceramic bonded electrocorundum and silicon carbide grinding wheels are widely used in almost all industries. The possibility of a wide modification of their parameters and good abrasive properties made it possible to machine most of the materials currently used with this type of grinding wheels. Electrocorundum is a synthetic abrasive composed of crystalline aluminum oxide (α-Al2O3) called alumina and a small amount of admixtures.

PRO discs / grinding wheels work with hand-held angle, face/vertical, straight grinders with electric and pneumatic drive.

# DISC FOR METAL











- Thin discs for efficient, precise cutting.
- Used for cutting universal, structural, tool steels.
- Characteristics: short cutting time, reduced energy consumption, long service life, comfortable work.
- 6mm thick discs for efficient, precise grinding of steel surfaces.

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-512	PRO-WT512	115 x 1.0 x 22.23
3-01-10-WT-501	PRO-WT501	125 x 1.0 x 22.23
3-01-10-WT-502	PRO-WT502	125 x 1.6 x 22.23
3-01-10-WT-503	PRO-WT503	125 x 2.5 x 22.23
3-01-10-WT-505	PRO-WT505	125 x 6.0 x 22.23
3-01-10-WT-504	PRO-WT504	230 x 2.0 x 22.23

# METAL INOX DISC











- Discs designed for most cutting operations on steel, cast iron, steel materials. Particularly items with larger cross-sectional areas: bars, flat bars, sheets, castings, stainless and acidresistant steels.
- Discs with a higher degree of hardness lighter cutting, especially on harder grades of material.

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-513	PRO-WT513	115 x 1.0 x 22.23
3-01-10-WT-506	PRO-WT506	125 x 1.0 x 22.23
3-01-10-WT-507	PRO-WT507	125 x 1.6 x 22.23
3-01-10-WT-508	PRO-WT508	230 x 2.0 x 22.23

# ABRASIVE INOX FLAP DISC















- A flap disc with a durable polyester backing.
- For machining structural, carbon and stainless steel. For heavy, aggressive grinding, edging, chamfering, weld removal, deburring.
- High performance, resistant to edge grinding, longer service life.

CODE	CAT NO.	DIMENSIONS	CODE	CAT NO.	DIMENSIONS
3-01-10-WT-621	PRO-WT621	40 x125 mm	3-01-10-WT-624	PRO-WT624	100 x125 mm
3-01-10-WT-622	PRO-WT622	60 x 125 mm	3-01-10-WT-625	PRO-WT625	120 x 125 mm

## FLAP DISC FOR METAL















- For machining: metal, wood and especially for surface grinding.
- Soft grinding, no vibration.
- High material removal rate.

CODE	CAT NO.	DIMENSIONS	CODE	CAT NO.	DIMENSIONS
3-01-10-WT-601	PRO-WT601	40 x125 mm	3-01-10-WT-604	PRO-WT604	100 x125 mm
3-01-10-WT-602	PRO-WT602	60 x 125 mm	3-01-10-WT-605	PRO-WT605	120 x 125 mm
3-01-10-WT-603	PRO-WT603	80 x125 mm			

## **CORUNDUM CUTTING DISC FOR METAL**













 CODE
 CAT NO.
 DIMENSIONS

 3-01-10-WT-001
 41-125 x 1.0 x 22.23

 3-01-10-WT-002
 41-125 x 1.6 x 22.23

Wheels designed for most of the cutting operations on steel, cast iron, cast steel materials, especially items with larger cross-sectional areas: bars, flat bars, metal sheets, casting riser heads.
 Medium hardness - for lighter cuts, especially on harder grades of material.

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-003		41-125 x 2.5 x 22.23
3-01-10-WT-004		41-230 x 2.0 x 22.23

# **CORUNDUM GRINDING DISC**
















CODE	CAT NO.	DIMENSIONS
3-01-10-WT-005	PRO-WW005	27-125 x 6.0 x 22.23

#### **CORUNDUM DISCS FOR METAL - INOX**













- Thin grinding wheels for efficient, precise cutting.
- Used for cutting general purpose, structural, tool, stainless and acid resistant steels.
- Features: short cutting time, reduced energy consumption, long service life, comfortable work.

		CODE	CAT NO.	DIMENSIONS	
		3-01-10-WT-006	PRO-WT006	41-125 x 1.0 x 22.23	
4		3-01-10-WT-007	PRO-WT007	41-125 x 1.6 x 22.23	
		3-01-10-WT-008	PRO-WT008	41-230 x 2.0 x 22.23	
- 1					

# DISCS FOR STONE














 Wheels designed for cutting concrete, ferroconcrete, terrazzo, natural and artificial stones, ceramic materials, as well as brittle, hard cast iron.



# DIAMOND SEGMENT DISCS





OPENING 22.2



WET DRY

- For dry and wet cutting of concrete, brick, clinker, natural and artificial stone.
- Mounting hole: 22.2 mm suitable for use with angle grinders.

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-101	PRO-WT101	115 x 22.2 mm
3-01-10-WT-102	PRO-WT102	125 x 22.2 mm
3-01-10-WT-103	PRO-WT103	180 x 22.2 mm
3-01-10-WT-104	PRO-WT104	230 x 22.2 mm

# SOLID DIAMOND DISCS











- For cutting ceramics, tiles, concrete, terracotta, brick, stone, etc.
- Full body suitable for wet cutting.
- Mounting hole: 22.2 mm suitable for use with angle grinders.

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-105	PRO-WT105	115 x 22.2 mm
3-01-10-WT-106	PRO-WT106	125 x 22.2 mm
3-01-10-WT-107	PRO-WT107	180 x 22.2 mm
3-01-10-WT-108	PRO-WT108	230 x 22.2 mm

# TURBO DIAMOND DISCS





OPENING 22.2





- Turbo blade for cutting concrete, stone, hard ceramic, stoneware, thin stone, etc.
- Full body suitable for wet cutting.
- Mounting hole: 22.2 mm suitable for use with angle grinders.

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-109	PRO-WT109	115 x 22.2 mm
3-01-10-WT-110	PRO-WT110	125 x 22.2 mm
3-01-10-WT-111	PRO-WT111	180 x 22.2 mm
3-01-10-WT-112	PRO-WT112	230 x 22.2 mm

## DIAMOND BLADES FOR SLIM CERAMICS



OPENING 22.2







- Ceramic slim disc for cutting concrete, stone hard ceramics, stoneware, clinker, reinforced concrete.
- Full body suitable for wet cutting.
- Mounting hole: 22.2 mm suitable for use with angle grinders.

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-120	PRO-WT120 11	5x1.2x10x22.2 mm
3-01-10-WT-121	PRO-WT121	125x1.2x10x22.2 mm

## **ENDURANCE SOLID DIAMOND DISCS**





- High quality hot stamped diamond blades.
- Dense diamond coating.
- Extremely efficient and durable.
- Increased cutting speed and blade life.

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-135	PRO-WT135	200x7x1.6x 25.4 mm
3-01-10-WT-134	PRO-WT134	125x7x1.2x22.2 mm
3-01-10-WT-133	PRO-WT133	115x7x1.2x22.2 mm

## ENDURANCE DIAMOND SEGMENT DISCS



OPENING 22.2

 $\bigcirc$ 

7mm

WET

- Dense diamond coating.
- Extremely efficient and durable.
- Increased cutting speed and blade life.

- High quality hot stamped diamond blades.

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-130	PRO-WT130 1	15x7x1.2x22.2 mm
3-01-10-WT-131	PRO-WT131	125x7x1.2x22.2 mm
3-01-10-WT-132	PRO-WT132 23	30x7x1.8x22.2 mm

## **TURBO ENDURANCE DIAMOND DISCS**









- High quality hot stamped diamond blades.
- Dense diamond coating.
- Extremely efficient and durable.
- Increased cutting speed and blade life.

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-136	PRO-WT136	115 x 7 x 1.2 x 22.2 mm
3-01-10-WT-137	PRO-WT137	125 x 7 x 1.2 x 22.2 mm
3-01-10-WT-138	PRO-WT138	230 x 7 x 1.8 x 22.2 mm



## **VACUUM BRAZED SEGMENTED DIAMOND DISCS**



OPENING 22.2 mm



- The blade is designed for dry cutting with a grinding machine and does not require additional cooling.
- Very wide application for all kinds of materials like tiles, stoneware, brick, steel, wood, plastic etc.
- Diamond coating is applied by vacuum brazing, which increases the resistance of the blade to high temperatures and improves performance.
- Special design for fast disc cooling and effective heat dissipation.

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-151	PRO-WT15	1 125 x 22.2 mm

## **COLD PRESSED DIAMOND SEGMENTED DISC**



OPENING 32 mm

4300 rpm



- Disc with sintered diamond blade. Long life. Quick cut.
- Application: for stone, old concrete, concrete products, brick, building materials, asphalt, etc.
- Compensation grooves allow dry operation without the need for water cooling.
- Reducing rings included: 32mm x 25.4 mm and 32 mm x 22.23

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-201	PRO-WT201 35	50x10x2.2x3.6mm
3-01-10-WT-202	PRO-WT202	400x10x2.6x4.0mm

# LASER-WELDED SEGMENTED DIAMOND DISCS





- Shield on steel backing. Designed for cutting stone, brick, asphalt, granite curbs, reinforced concrete.
- Diamond blade for perfect, professional cuts.
- Disc with increased resistance to high temperatures.
- High dry cutting performance, easy to cut reinforced concrete.
- Reducing rings included: 32mm x 25.4 mm and 32 mm x 22.23

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-211	PRO-WT211 35	0x10x2.4x3.2mm
3-01-10-WT-212	PRO-WT212	400x10x2x6x3.4mm

## "PLANER" WOOD SAW BLADE

DIAMETER 125mm OPENING 22.2

3 теетн



 Use: Cutting in wood, profiling, cleaning and sanding, notching and grooving, rip-cutting and cross-cutting of all types of wood and other materials.
 Cutting and picking in aerated concrete, etc.

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-150	PRO-WA150 12	25 x 3T x 3.8 x 22.23 mm



## DIAMOND CUTTING AND GRINDING DISC



M14





- Designed for cutting and grinding stone tiles, ceramic tiles, stoneware, etc.
- The diamond coating is applied by electroplating reducing the risk of vibration during cutting and grinding.
- Double-sided disc with the possibility to switch the spindle and use both sides of the disc. Be careful not to damage the screws after the changover.
- Tool socket: M14

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-152	PRO-WT152 12	25 × 1.6 × 30 mm

## DIAMOND GRINDING DISCS

- For fast cutting of thick layers of concrete.
- Effective in leveling concrete, granite and natural stone surfaces, etc.
- The design allows for edge grinding, such as chamfering the edges of slabs of concrete, granite and natural stone.
- Effectively matts the surface before applying a new coating.
- High quality diamonds fixed with special soft bond to make tool wear slow, especially when machining hard materials.
- Large gaps and openings for better dust removal and segment cooling.

SINGLE



DIAMETER 125mm 1 ROW

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-270	PRO-WT270	125 × 5 × 22.23 mm

DOUBLE



DIAMETER 125mm 2 ROWS

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-250	PRO-WT250	125 × 5 × 22.23 mm

**TURBO** 



DIAMETER 125mm TURBO

CODE	CAT NO.	DIMENSIONS	
3-01-10-WT-260	PRO-WT260	125 × 5 × 22.23 mm	

## **GRINDING DISCS**

UNIVERSAL GRINDING DISC WITH HOOK AND LOOP



- VELCRO M14
- Mounting for angle grinders with M14 spindle thread.
- Comes with an adapter to allow attachment to a drill.
- Thick sponge stabilizes work by dampening vibrations
- Velcro fastening for paper, mesh or disc
- Durable plastic structure

CODE	CAT NO.	DIMENSIONS
3-01-10-WA-005	PRO-WA005	100mm
3-01-10-WA-006	PRO-WA006	125mm

#### **VELCRO-BACKED**




1/4"

- Attaches to equipment with 1/4 tool holder.
- Velcro attachment for paper, mesh or disc.
- Flexible rubber disc design.

CODE	CAT NO.	DIMENSIONS
3-01-10-WA-008	PRO-WA008	100mm

#### **DIAMOND GRINDING DISC**



-	For dry grinding and polishing of
	ceramics, stoneware, natural
	stone, terrazzo, glass, etc.
	Applied top quality diamond



VELCRO

surface for efficient work with the hardest materials.

GR

Velcro backed disc, easily attached and replaced. Provides excellent finish to flat surfaces as well as cut edges.

AIN	CODE	CAT NO.	GRAIN
	3-01-10-WT-163	PRO-WT163	400
)	3-01-10-WT-164	PRO-WT164	800
)	3-01-10-WT-165	PRO-WT165	1500

## DIAMOND GRINDING BLOCK



CODE	CAT NO.	GRAIN
3-01-10-WA-010	PRO-WA010	60
3-01-10-WA-011	PRO-WA011	120
3-01-10-WA-012	PRO-WA012	200
3-01-10-WA-013	PRO-WA013	400

- For smoothing cut edges and surfaces of stoneware, ceramic tiles and natural stones. Perfect for grinding and smoothing hard materials: stone, glass, ceramic, hard plastic, fiberglass, etc.
- The ergonomic and flexible design of the knuckle makes work easier and does not tire the hand.
- Application: Grinding and smoothing of cut edges, removal of stains or rust, polishing of corners and places difficult to reach with power tools.
- Dry running cubes, very efficient, waterproof and hard to damage.
- Functions of each grain size: #60, #120 and #200 for smoothing (the smaller the number, the larger the grain and the faster material abrasion), #400 for polishing.
- Size of diamond surface 55x90 mm.

# JIGSAW BLADE SETS

#### WZ-JIG-S10A











10 pcs.

Jigsaw blade set includes blades for cutting wood, chipboard, plywood, sheet metal, aluminum and non-ferrous metals, tile, cast iron.



	EEST	W B	ZESZ	CZOT WZ-J	ÓW E	O WYRZ	YNAREK
71270	MINIT	THOIR	12440	THIC	1344D		
2000	appe	S. Park	i	9	ê PR		TIBLE
-			0	P	R		169

HCS - High Carbon Steel	PARTIE DE LA CONTROL DE LA CON
HSS - High Speed Steel BIM - Bi Metal Steel	

	CUTTING	STEEL AND TEETH	MATERIAL
T127D	Precise straight cut	HSS, tooth set, milled	Thin to thick sheets (3-15 mm), tubes + profiles (diameter <30 mm), aluminum
T101B	Pure straight cut	HCS, side and teeth - ground	Soft wood, particle board, carpentry, fibreboard (3-30 mm)
T244B	fast and curvilinear cutting	HCS, teeth set, ground	Soft wood (5-50 mm), chipboard, blockboard, fibreboard
T101BR	clean cut without scratches	HCS, side and teeth - ground	Soft wood, particle board, carpentry, fiberboard (3-30 mm), laminated boards,
T144D hiç	gh-speed cutting	HCS, teeth set, ground	Soft wood (5-50 mm), chipboard, blockboard, fibreboard
T111C	DIY quick cut	HCS, teeth opened, milled	Soft wood (4-50 mm), chipboard, blockboard, fibreboard,
	pure and	HCS, with teeth	Softwood, plywood, panels
T101AO	curvilinear cutting	pointed, side and coat teeth	ed (1.5-15 mm) ground
T118A	DIY	HSS, corrugated, milled	Thin sheets (1-3 mm)
T118BF	Flexible, durable, resistant to breaking	BIM, corrugated, milled	Medium-thick plates, sheets perforated (2.5-6 mm), wood, plastic
T150RIFF	Precise	Coated with carbide,	For soft glaze, cast iron (5-10 mm),

DE	CAT NO.
Z-040	PRO-WA040


T118A DIY HSS, corrugated, milled

#### WZ-JIG-S10B

ABBREVIATIONS

T - T-grip

Jigsaw blade set includes blades for cutting wood, particle board, plywood, sheet metal, aluminum and non-ferrous metals.





I	2657/		REST	CZOT WZ-JI			YRZYN	AREK
11010	1000	(Sum)	iner.					
OPR	100	Cipie	and the	gpp.	gps		T S	A
			ì		Ī	Obes	PRO	
9	0.4	No.	Neces	9	1	-	9	信

## 10 pcs. CUTTING STEEL AND TEETH MATERIAL


Thin sheet metal (1-3 mm), aluminum and non-ferrous metals HSS, teeth Precise Thin to thick plates (3-15 mm), tubes + opened, milled straight cut profiles (diameter <30 mm) HCS, teeth Soft wood (4-50 mm), chipboard, DIY quick cut set, milled blockboard, fibreboard, high speed cutting HCS, side and T101B cut teeth - ground carpentry, fibreboard (3-30 mm) T119BO DIY cutting curvilinear HCS, corrugated, Soft wood (2-15 mm), plywood, milled chipboard, blockboard, fiberboard,



SET B

#### WZ-JIG-S10C

- Jigsaw blade set includes blades for cutting wood, chipboard, plywood.





	m	etal aluminum	wood plywood SET C
	CUTTING	STEEL AND TEETH	MATERIAL
T144D hi	gh-speed cutting	HCS, teeth set, ground	Soft wood (5-50 mm), chipboard, blockboard, fibreboard
T101D	clean cut	HCS, side and teeth - ground	Soft wood, particle board, carpentry, fibreboard (10-45 mm)
T111C	DIY quick cut	HCS, teeth set, milled	Soft wood (4-50 mm), chipboard, blockboard, fibreboard, high speed cutting
T101B	Pure straight cut	HCS, side and teeth - ground	Soft wood, particle board, carpentry, fibreboard (3-30 mm)
	curvilinear	HCS, corrugated,	Soft wood (2-15 mm), plywood, chipboard, blockboard, fiberboard,
T101AO	pure and curvilinear cutting	HCS, with teeth pointed, side and teeth ground	Softwood, plywood, coated boards (1.5-15 mm)

#### SET A

- Jigsaw blade set includes blades for cutting wood, chipboard, plywood.



ABBREVIATIONS
T - T-grip HCS - High Carbon Steel
HSS - High Speed
BIM - Bi Metal Steel

CODE	CAT NO.
3-01-10-WZ-045	PRO-WA045
3-01-10-112-043	FRO-WA043



	CUTTING	STEEL AND TEETH	MATERIAL
T101B Cle	ean straight cut	HCS, side and teeth ground	Soft wood, chipboard, blockboard, fibreboard (3-30 mm)
T244D	Fast and curvilinear cutting	HCS, teeth opened, ground	Soft wood (5-50 mm), chipboard, blockboard, fibreboard
T11	1C DIY quick cut	HCS, tooth set, milled	Soft wood (4-50 mm), chipboard, blockboard, fibreboard, high speed cutting
T144D	fast cut	HCS, teeth opened, ground	Soft wood (5-50 mm), chipboard, blockboard, fibreboard
T119BO D	DIY cutting curvilinear	HCS, corrugated, milled	Soft wood (2-15 mm), plywood, chipboard, blockboard, fiberboard,

#### **D**I⊭ **r**utting

 - Jigsaw blade set includes blades for cutting wood, particle board, plywood, sheet metal, aluminum and non-ferrous metals.



5 PCS.

ABBREVIATIONS
T - T-grip
HCS - High Carbon Steel
HSS - High Speed
BIM - BI Metal Steel

CODE
CAT NO.
3-01-10-WZ-046
PRO-WA046



	CUTTING	STEEL AND TEETH	MATERIAL
T118A DIY	(	HSS, corrugated, milled	Thin metal sheets (1-3 mm), aluminum
T127D	Precise straight cut	HSS, teeth opened, milled	Thin to thick plates (3-15 mm), tubes + profiles (diameter <30 mm)
T111C DIY	quick cut	HCS, teeth opened, milled	Soft wood (4-50 mm), chipboards, woodworking, fibreboard,
T144D	fast cut	HCS, teeth opened, ground	Soft wood (5-50 mm), chipboard, blockboard, fibreboard
T119B0	DIY curvilinear cutting	HCS, corrugated, milled	Soft wood (2-15 mm), plywood, chipboard, blockboard, fiberboard,

#### SET C



5 PCS.

CRIMPED WIRE

M6



CODE	CAT NO.
3-01-10-WZ-047	PRO-WA047



 Jigsaw blade set includes blades for cutting thin sheet metal and nonferrous metals.

CUTTIN	IG STEEL AND TEETH	MATERIAL
T118B DIY	HSS, corrugated, milled	Thin sheets (1-3 mm),

# FRONT BRUSHES

#### FRONT BRUSH CORRUGATED WIRE HANDLE 6MM



			//	
- Professional front brush with optimally	hardened	crimped	wire for efficient	
work in roughing applications		-		

ø60mm

- Made of high quality hardened wire.
- Designed to remove rust, scale, clean surfaces, remove paint, clean welds.

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-301	PRO-WA401	50mm
3-01-10-WT-302	PRO-WA402	60mm
3-01-10-WT-303	PRO-WA403	75mm

#### FRONT BRUSH CORRUGATED WIRE HANDLE M14





- Professional front brush with optimally hardened crimped wire for efficient work in roughing applications.
- Made of high quality hardened wire.
- Designed to remove rust, scale, clean surfaces, remove paint,

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-306	PRO-WA406	60mm
3-01-10-WT-407	PRO-WA407	75mm
3-01-10-WT-408	PRO-WA408 1	00mm

#### FRONT BRUSH TWISTED WIRE HOLDER M14









- Professional front brush with optimally hardened crimped wire for efficient work in roughing applications.
- Made of high quality hardened wire.
- Designed to remove rust, scale, clean surfaces, remove paint,

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-311	PRO-WA311	60mm
3-01-10-WT-312	PRO-WA312	75mm
3-01-10-WT-313	PRO-WA313 1	00mm

#### **DISC BRUSH CORRUGATED WIRE HANDLE 6MM**



M6







- Maximum performance when working on steel or heavily corroded surfaces
- Made of high quality hardened wire.
- Designed to remove rust, scale, clean surfaces, remove paint, clean welds.

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-316	PRO-WA316	60mm
3-01-10-WT-317	PRO-WA317	75mm
3-01-10-WT-318	PRO-WA318 1	00mm

#### **DISC BRUSH CORRUGATED WIRE M14 HOLDER**









- Maximum performance when working with medium hard surfaces.
- Dedicated to tools with angle grinders.
- Ability to work at high speeds.
- Made of high quality hardened wire.
- Designed to remove rust, scale, clean surfaces, remove paint,

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-321	PRO-WA321	100mm
3-01-10-WT-322	PRO-WA322	115mm

#### **DISC BRUSH CRIMPED WIRE HANDLE M14**









- Maximum performance when removing deep corrosion and thick layers of paint.
- Dedicated to tools with angle grinders.
- Ability to work at high speeds.
- Made of high quality hardened wire.
- Designed to remove rust, scale, clean surfaces, remove paint,

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-325	PRO-WA32	25 100mm

#### **DISC BRUSH CRIMPED WIRE HANDLE 6MM**





- Universal shank allows attachment to drill chuck and straight grinder.
- Made of high quality hardened wire.
- Ability to work in hard-to-reach places.
- Designed to remove rust, scale, clean surfaces, remove paint, clean welds.

CODE	CAT NO.	DIMENSIONS
3-01-10-WT-328	PRO-WA328	17mm
3-01-10-WT-329	PRO-WA329	25mm































#### PH BITS 50 MM

CODE	CAT NO.	DIMENSIONS	QUANTITY
3-01-22-WB-004	PRO-WB004	1 x 50 mm	10

CODE	CAT NO.	DIMENSIONS	QUANTITY
3-01-22-WB-008	PRO-WB008	1 x 50 mm	10
3-01-22-WB-009	PRO-WB009	2 x 50 mm	10

#### PH BITS 25 MM

CODE	CAT NO.	DIMENSIONS	QUANTITY
3-01-22-WB-002	PRO-WB002	1 x 25 mm	25

#### PZ BITS 25 MM

CODE	CAT NO.	DIMENSIONS	QUANTITY
3-01-22-WB-006	PRO-WB006	1 x 25 mm	25
3-01-22-WB-128	PRO-WB128	2 x 25 mm	100

#### PH BITS 25 MM ANTI-SLIP PZ BITS 25 MM ANTI-SLIP

CODE	CAT NO.	DIMENSIONS	QUANTITY
3-01-22-WB-130	PRO-WB130	1 x 25 mm	25
3-01-22-WB-131	PRO-WB131	2 x 25 mm	25

CODE	CAT NO.	DIMENSIONS	QUANTITY
3-01-22-WB-132	PRO-WB132	1 x 25 mm	25
3-01-22-WB-133	PRO-WB133	2 x 25 mm	25
3-01-22-WB-135	PRO-WB135	2 x 25 mm	100

# **HEX BITSTORX BITS**























CODE	CAT NO.	DIMENSIONS	QUANTITY
3-01-22-WB-010	PRO-WB010	3 x 25 mm	10
3-01-22-WB-011	PRO-WB011	4 x 25 mm	10
3-01-22-WB-012	PRO-WB012	5 x 25 mm	10
3-01-22-WB-013	PRO-WB013	6 x 25 mm	10

CODE	CAT NO.	DIMENSIONS	QUANTITY
3-01-22-WB-014	PRO-WB014	10 x 25 mm	10
3-01-22-WB-116	PRO-WB016	20 x 25 mm	10
3-01-22-WB-118	PRO-WB018	30 x 25 mm	10

# **MIXED BITS**













BIT SET













#### SET:

- 1 X PZ1, - 2 X PZ2, - 1 X PH1,

- 2 X PH2,

- 1 X HEX3,

- 1 X HEX4,
- 1 X HEX5,
- 1 X HEX6,
- 1 X T10,
- 1 X T15,
- 1 X T20, - 1 X T25,

- 1 X T30

- 1 x PH1 25 pcs,
  - 2 x PH2 25 pcs,

SET:

- 1 x PZ1 25 pcs,

- 1 x PZ2 25 pcs,

- 1 x HEX3 10 pcs,
- 1 x HEX4 10 pcs,
- 1 x HEX5 10 pcs,
- 1 x HEX6 10 pcs,
- 1 x T10 10 pcs,
- 1 x T15 10 pcs,
- 1 x T20 10 pcs,
- 1 x T25 10 pcs,
- 1 x T30 10 pcs,
- 1 x MIX (PZ, PH, HEX and T) 15

CODE	CAT NO.	DIMENSIONS	QUANTITY
3-01-22-WB-129	PRO-WB129	MIX	15

CODE	CAT NO.
3-01-22-WB-101	PRO-ZB101

# DOUBLE-SIDED BITSBITS WITH PH2 STOP



























#### **DOUBLE-SIDED PZ1 - PZ2 BITS**

CODE	CAT NO.	DIMENSIONS	QUANTITY	CODE	CAT NO.	DIMENSIONS	QUANTITY
3-01-22-WB-020	PRO-WB020	65 mm	5	3-01-22-WB-126	PRO-WB126	2 x 25 mm	2

# **MAGNETIC CHUCK**











# QUICK-ACTION MAGNETIC CHUCK





CODE	CAT NO.	DIMENSIONS	QUANTITY	CODE	CAT NO.	DIMENSIONS	QUANTITY
3-01-22-WB-122	PRO-WB122	35 x 65 mm	2	3-01-22-WB-201	PRO-WB201	1/4"	1

## ADAPTER FOR CAPS MAGNETIC CAP























CODE	CAT NO.	DIMENSIONS	QUANTITY	CODE	CAT NO.	DIMENSIONS	QUANTITY
3-01-22-WB-023/123 PRO-WB023/123 50 mm 2		2	3-01-22-WB-124	PRO-WB124	8 mm, 65 mm	2	
				3-01-22-WB-125	PRO-WB125	10 mm, 65 mm	2
				3-01-22-WB-138	PRO-WB138	11 mm, 65 mm	2
				3-01-22-WB-139	PRO-WB139	12 mm, 65 mm	2

# **BIT SET 20 PIECES**

















- Made of high quality CrV 6150 steel.
- Hardened, protected against corrosion, additionally reinforced.
- Easy exchange of bits and sockets.
- Large, non-slip, two-component handles for high torque with minimum effort.
- ABS box.

#### SET:

- adapter 25 mm, 1/ 4";
- 25 mm bits:
  - flat bits SL4, SL5 2 pieces,
  - PH1 and PH2 bits 2 pieces, bits PZ1 and PZ2 2

  - pieces, T15 and T20
  - O bits 2 pieces,
  - O HEX4 and HEX5 bits 2 pieces;
- - PH1, PH2, PZ1, PZ2, T30 and T40;
- socket bits: 8, 10, 12.



## **BIT SET 26 PIECES**



CODE CAT NO. 3-01-22-WB-031 PRO-ZB031















- Made of high quality CrV 6150 steel.
- Hardened, protected against corrosion, additionally reinforced.
- Easy exchange of bits and sockets.
- Large, non-slip, two-component handles for high torque with minimum effort.
- ABS box.

#### SET:

- 25 mm bits:
  - SL3, SL4, SL5, SL6 flat bits 4 pieces, PH
  - bits: PH1, PH2 and PH3 3 pieces,

  - PZ bits: PZ1, PZ2 and PZ3 3 pieces,
    TORX bits: T10, T15, T20, T25, T30 and T40 6
  - O pieces,
  - O HEX bits: HEX3, HEX4, HEX5 and HEX6 4 pieces;
- 50 mm bits:

PH2, PH3, PZ1, PZ2, T40;

- socket bits: 8.

# **BIT SET 43 PIECES**



CAT NO. CODE 3-01-22-WB-032 PRO-ZB032















- Made of high quality CrV 6150 steel.
- Hardened, protected against corrosion, additionally reinforced.
- Easy exchange of bits and sockets.
- Large, non-slip, two-component handles for high torque with minimum effort.
- ABS box.

#### SET:

- 25 mm bits:
  - flat bits SL3 (2 pcs), SL4 (2 pcs), SL5 (2 pcs), SL6 (2 pcs), SL7 (2 pcs) 10 pieces, PH1 (3 pcs), PH2 (5 pcs) and PH3 (2 pcs) bits - 10 pieces,
  - PZ0, PZ1, PZ2 (3 pcs) and PZ3 bits 6 pieces,
  - O TORX T10, T15, T20 (2 pcs), T25 (2 pcs), T27, T30 (2 pieces) and T40 bits - 10 pieces,
  - O HEX bits HEX3, HEX4, HEX5 and HEX6 4 pieces;
- 50 mm quick release coupling:
- adapter 25 mm, 1/4".

## 41IN1 BIT AND SOCKET SET WITH RATCHET



















CAT NO. 3-01-30-WZ-105 PRO-ZB105

- Bits and sockets made of high quality chrome vanadium steel.
- Powder coated.
- The large, short, non-slip handle ensures high torque with minimum effort.
- Box made of durable ABS.

#### SET:

- Ratchet screwdriver 1 pc;
- Magnetic holder for bits 60 mm 1 pc;
- Adapter for socket 25 mm 1 pc;
- 1/4" sockets 6 pcs: 5, 6, 7, 8, 9. 10mm;
- Bits 25 mm 32 pieces:
  - flat bits: SL3, SL4, SL5, SL6, 1/8, 5/32, 3/16, 1/4;
  - PH bits: PH0, PH1, PH2, PH3; PZ bits: PZ0, PZ1, PZ2,

  - O PZ3; SQ bits (square): SQ0, SQ1, SQ2, SQ3;
  - O HEX bits: 3, 4, 5, 6, 1/8, 5/32, 3/16, 1/4;
    O TORX bits: T15, T20, T25, T30.

# **IMPACT STEEL BIT SET S2 34IN1**















- Bits, sockets and accessories made of high-grade oxidized S2 steel.
- Box made of durable PP.

- Extended magnetic holder for bits 1 pc;
- Magnetic holder for bits 1 pc;
- Adapter for 3/8 sockets 1 pc;
- Magnetic socket 1/4", 5/16" 2 pcs;
- Bits 25 mm 24 pcs:
  - flat bits: SL6;
  - PH bits: PH1, PH2x6, PH3x2;
  - O SQ bits (square): SQ1, SQ2x3, SQ3x2; TORX bits: T15, T20x3, T25x3, T30;
- - O SQ bits (square): SQ2; O TORX bits: T20, T25.

CAT NO. CODE PRO-ZB106 3-01-30-WZ-106



## BIT AND DRILL BIT SET IMPACT, STEEL S2 18IN1

HRC 54-58

S2









- Bits made of high quality oxidized S2 steel.
- Box made of durable PP.



#### SET:

- Magnetic holder for bits 1 pc;
- Bits 25 mm 8 pcs:
  - PH bits: PH2x2, Ph3;
  - O SQ bits (square): SQ2x2, SQ3; TORX bits: T20 T25;
- 50 mm bits 4 pcs:
  - PH bits:
  - PH2, PH3;
  - O SQ bits (square): SQ2; O TORX bits: T25;
- Titanium drills 5 pcs:

6, 5, 4, 3, 2mm.

3-01-30-WZ-107 PRO-ZB107

CODE

## **SET OF BITS AND SOCKETS**

CAT NO.

51-54













- Hardened, protected against corrosion, additionally reinforced.
- Easy exchange of bits and sockets.

- Made of high quality CrV 6150 steel.

Large, non-slip, two-component handles for high torque with minimum effort.

#### SET:

- T-shaped holder for bits and sockets 1 pc;
- Ratchet screwdriver 1 pc;
- Magnetic holder for bits 1 pc;
- Adapter for socket (25 mm) 1 pc;
- Bits (6.35× 25 mm ) 16 pcs:
  - 3 mm, 4 mm, 5 mm, 6 mm, PH0, PH1, PH2, PH3,

  - **₽** PZ0, PZ1, PZ2, PZ3, T10, T15,
  - O T20, T25;
- 1/4" sockets 9 pcs:
  - O 5 mm, 6 mm, 7 mm, 8 mm, 9 mm, 10 mm, 11 mm, 12 mm, 13 mm.


# WORKSHOP 1 3



#### **PLIERS AND CUTTERS**

HIGH LEVERAGE system

#### HIGH LEVERAGE PLIERS



Since in pliers and cutters with the HIGH LEVERAGE system the distance between the connecting rivet and the cutting edge (a) is considerably smaller than in standard pliers (a'), less force is required to cut a wire of the same thickness.

STANDARD PLIERS

## UNIVERSAL PLIERS

60-64

- Made of cold forged chrome vanadium steel (CrV 60), additionally

HRC

HRC.

BLADE

CrV

DIN

5746

DIN

5746

60

nickel plated.

- Hardness of rivet connecting the arms HRC 34-38.

Structural hardness of the pliers HRC 44-48.
Hardness of cutting blades HRC 60-64.

180mm

160mm

180mm

160mm

Two-component, non-slip handle made of TPR.

- Cutting edges to cut steel bars

up to 1.6 or 1.8 mm in diameter depending on the length of the pliers.

Perfectly shaped jaws to guarantee a good grip on the workpiece.

Durable jaw serrations to prevent slippage of material.

- 58 mm arm spacing.

40%

LESS

EFFORT

- Compliant with DIN 5746.



CODE	CAT NO.	LENGTH
3-01-18-01-201	PRO-BY201	160mm
3-01-18-01-202	PRO-BY202	180mm

# UNIVERSAL PLIERS HD



HRC BLADE

nickel plated.

- 40% less work effort with the HIGH LEVERAGE system.

HRC

44-48

- Hardness of rivet connecting the arms HRC 34-38.
- Structural hardness of the pliers HRC 44-48.
- Hardness of cutting blades HRC 60-64.
- Two-component, non-slip handle made of TPR.
- Cutting edges cut steel bars up to 1.6 or 1.8 mm in diameter depending on the length of the pliers.
- Durable jaw serrations to prevent slippage of material.
- $\mbox{-}$  Arm distance 55 or 56 mm depending on the length of the pliers.
- Compliant with DIN 5746.



CODE	CAT NO.	LENGTH
3-01-18-01-006	PRO-BY006	160mm
3-01-18-01-007	PRO-BY007	180mm

## UNIVERSAL PLIERS S-HD

70% LESS EFFORT

200mm HRC 44-48 HRC BLADE 58-62

Ni SYSTEM

TPR HANDLE



CODE CAT NO. LENGTH
3-01-18-20-010 PRO-BY010 200 mm

- Durable structure made of chrome-nickel steel.
- Two-component, non-slip handle made of TPR (thermoplastic rubber)
- 70% less effort during work thanks to the S-HD system.
- Structural hardness of the pliers HRC 44-48.
- Hardness of cutting blades HRC 58-62.
- Forged, ultra-strong structure reinforced with integral rivets.

## **UNIVERSAL PLIERS**

150mm 200mm HRC 44-48

CrV



CODE	CAT NO.	LENGTH	
3-01-18-20-004	PRO-BY004 150 mm		
3-01-18-20-005	PRO-BY005	200mm	

- Forged from high-grade steel and induction hardened.
- Cutting edges carefully machined and sharpened by hand.
- Hardness HRC 44-48.
- Three-position latch.
- Universal design.
- Equipped with an adjustable button.
- Two-component handle.
- Inductively hardened jaws.
- Monoblock design.
- Non-slip TPR handle.

## UNIVERSAL PLIERS VDE



HRC 44-48 HRC BLADE 60-64

CrV

1000V AC



CODE	CAT NO.	LENGTH
3-01-18-10-201	PRO-BV201	160mm
3-01-18-10-202	PRO-BV202	180mm

- Made of cold forged chrome vanadium steel additionally nickel plated.
- Hardness of rivet connecting the arms HRC 34-38.
- Structural hardness of pliers HRC 44-48, cutting blades HRC 60-64.
- Two-component non-slip TPR handle manufactured in accordance with EN60900:2004.
- Cutting edge, allowing cutting of medium hardness steel bars up to 2.0 mm or 2.4 mm in diameter and high hardness wire up to 1.6 mm or 2.0 mm in diameter.
- Perfectly shaped jaws to guarantee a good grip on the workpiece.
- Durable jaw serrations to prevent slippage of material.
- Suitable for working with voltages up to 1000 V AC.



## MORSE STRAIGHT CRIMPING PLIERS

210mm H

HRC 32-38 BLADE HRC 46-50

CrMo



additionally nickel plated.

- Handle made of cold forged chrome vanadium steel (CrV),

 Handle made of cold forged chrome vanadium steel (CrV), additionally nickel-plated.

Jaws made of cold forged chrome-molybdenum steel (CrMo),

- Structural hardness of the pliers HRC 32-38.
- Hardness of the cutting edge structure and jaws HRC 46-50.
- Cutting edges induction hardened.
- Profiled jaws to ensure that the workpiece is properly covered.
- For applications requiring maximum clamping without slipping or sliding.
- Durable jaw serrations to prevent slippage of material.
- A lever mechanism with three pivot points.
- Pliers equipped with a locking system.
- Wire cutter.
- Handle with lock switch and adjustable jaw opening.

 CODE
 CAT NO.
 LENGTH

 3-01-18-01-110
 PRO-BY110
 210 mm

## **MORSE CURVED CRIMPING PLIERS**

210mm

HRC 32-38 BLADE HRC 46-50

CrMo

- Jaws made of cold forged chrome-molybdenum steel (CrMo), additionally nickel plated.
- Handle made of cold forged chrome vanadium steel (CrV), additionally nickel-plated.
- Structural hardness of the pliers HRC 32-38.
- Hardness of the cutting edge structure and jaws HRC 46-50.
- Cutting edges induction hardened.
- Profiled jaws to ensure that the workpiece is properly covered.
- For applications requiring maximum clamping without slipping or sliding.
- Durable jaw serrations to prevent slippage of material.
- A lever mechanism with three pivot points.
- Pliers equipped with a locking system.
- Wire cutter.
- Handle with lock switch and adjustable jaw opening.

# CODE CAT NO. LENGTH 3-01-18-01-109 PRO-BY109 210 mm

# **VDE FLAT-NOSED PLIERS**



160mm

HRC 44-48 HRC BLADE 60-64

CrV

1000V AC

- Made of cold forged chrome vanadium steel additionally nickel plated.
- Hardness of rivet connecting the arms HRC 34-38.
- Structural hardness of the pliers HRC 44-48.
- Hardness of cutting blades HRC 60-64.
- Two-component non-slip TPR handle manufactured in accordance with EN60900:2004.
- Perfectly shaped jaws.
- Durable jaw serrations to prevent slippage of material.
- Suitable for working with voltages up to 1000 V AC.









## **ELONGATED STRAIGHT PLIERS SHD**

70% LESS EFFORT 200mm

HRC 44-48 HRC BLADE 58-62

Cr-Ni

S-HD SYSTEM TPR HANDLE



- Durable structure made of chrome-nickel steel.

- Two-component, non-slip handle made of TPR (thermoplastic rubber).
- 70% less effort during work thanks to the S-HD system.
- Structural hardness of the pliers HRC 44-48.
- Hardness of cutting blades HRC 58-62.
- Forged, ultra-strong structure reinforced with integrated rivets.

CODE CAT NO. LENGTH
3-01-18-20-011 PRO-BY011 200 mm

## CHANNEL LOCK PLIERS FOR PIPES

250mm 300mm STEEL 31CrV3 HARDENED IN WHOLE



- Useful for plumbing and general construction work.
- Made of high quality chrome vanadium steel.
- Hardened in whole.
- Powder coated.
- Double coated handle with PVC and anti-slip coating.

# **CHANNEL LOCK PLIERS**



HRC 44-48 CrV

DIN 5746







CODE	CAT NO.	LENGTH
3-01-18-20-001	PRO-BN001	200mm
3-01-18-20-002	PRO-BN002	250mm
3-01-18-20-003	PRO-BN003	300mm

- Forged from high-grade steel and induction hardened.
- Cutting edges carefully machined and sharpened by hand.
- Hardness HRC 44-48.
- Three-position latch.
- Universal design.
- Equipped with an adjustable button.
- Two-component, non-slip handle made of TPR.
- Induction hardened jaws.
- Monoblock design.
- 17 position possible sizes.

## AUTOMATIC INSULATION STRIPPER

0.25-6 mm STEEL A3

ABS



- Used for stripping insulation.
- Working range 0.25 to 6 mm<sub>2</sub>.
- The cutting jaws are made of extremely tough steel with a hardness of 40 - 55 HRC, which ensures long durability of the tool.
- Ergonomic handle made of durable A3 steel for increased comfort.

# **AUTOMATIC INSULATION STRIPPER**

HRC 40-45

CrV



- Used for stripping and crimping 22 10 AWG (American Wire Gauge) connector terminals.
- Working range 0.2 6 mm, for crimping terminals 0.2 6 mm.
- The cutting jaws are made of extremely durable steel with hardness of 40 - 55 HRC, which ensures long durability of the tool.
- Bimaterial, ergonomic handle increases comfort.

## **6" CABLE PLIERS**

8-14 AWG

FORGED STEEL 6"

1.6 2.0 2.6 3.2 mm



- High strength due to the use of forged, hardened steel.
- Easy to use spring loaded hinge with safety lock.
- For fast stripping without damaging the wire up to size 14 AWG (American Wire Gauge).





STRUCTURAL MATERIAL







- Pliers made of sturdy polyamide material with fiberglass.
- Working range of the pliers: 0.2-6 mm.
- Pliers equipped with a cutter for wires with a maximum diameter of 3mm.
- Handle and jaws can be locked.

## **INSULATION PLIERS**

8-20 AWG 0.8-3.2

WIRE CUTTER 2.5 3.0 3.5 4.0 5.0mm



- Used for stripping and crimping 10 22 AWG (American Wire Gauge) connector terminals.
- The elongated end of the pliers allows pulling and looping of wire, cable.
- Inductively hardened blades precisely cut screws of all sizes and leave a perfect guide thread.
- Bimaterial handle to absorb shock during operation.

## **EXTERNAL STRAIGHT SEGER PLIERS**

175 mm CARBON STEEL

Ni



- Durable structure of high-grade nickel-plated carbon steel.
- Dual-layer, non-slip handle.
- Pliers for assembling and disassembling circlip rings in machines and equipment of various types.

## **EXTERNAL CURVED SEGER PLIERS**

175 mm

CARBON STEEL Ni



- Durable structure of high-grade nickel-plated carbon steel.
- Dual-layer, non-slip handle.
- Pliers for assembling and disassembling circlip rings in machines and equipment of various types.

## **INTERNAL STRAIGHT SEGER PLIERS**

175 mm CARBON STEEL Ni





- Durable structure of high-grade nickel-plated carbon steel.
- Dual-layer, non-slip handle.
- Pliers for assembling and disassembling circlip rings in machines and equipment of various types.

## INTERNAL CURVED SEGER PLIERS

175 mm CARBON

Ni



- Durable structure of high-grade nickel-plated carbon steel.
- Dual-layer, non-slip handle.
- Pliers for assembling and disassembling circlip rings in machines and equipment of various types.



180mm

HRC 42-48 HRC BLADE 58-62 CrV 60



- Made of cold forged chrome vanadium steel (CrV 60) with extra polished working part.
- Structural hardness of the cutter HRC 42-48.
- Hardness of cutting blades HRC 58-62.
- Cutting edge, allowing to cut steel bars up to 1.6 mm in diameter.
- 55 mm arm spacing.
- Compliant with DIN 5746.

SIDE CUTTER

160mm

HRC 44-48 HRC BLADE 60-64

CrV 60



- Made of cold forged chrome vanadium steel
- (CrV 60), additionally nickel-plated.
- Hardness of rivet connecting the arms HRC 34-38.
- Structural hardness of the cutter HRC 44-48.
- Hardness of cutting blades HRC 60-64.
- Two-component, non-slip handle made of TPR.
- Cutting edge, allowing to cut steel bars up to 1.6 mm in diameter.
- 55 mm arm spacing.
- Compliant with DIN 5746.

## **HD SIDE CUTTER**

40% LESS EFFORT

160mm

HRC 44-48 HRC BLADE 60-64 CrV 60



CODE CAT NO.
3-01-18-01-008 PRO-BC008

- Made of cold forged chrome vanadium steel (CrV 60), additionally nickel plated.
- 40% less work effort with the HIGH LEVERAGE system.
- Hardness of rivet connecting the arms HRC 34-38.
- Structural hardness of the pliers HRC 44-48.
- Hardness of cutting blades HRC 60-64.
- Two-component, non-slip handle made of TPR.
- Cutting edge cutting steel bars up to 1.6 mm in diameter.
- 55 mm arm spacing.
- Compliant with DIN 5746.

## S-HD SIDE CUTTER

70% LESS EFFORT

200mm

HRC 44-48 Cr-Ni

S-HD SYSTEM

-HD TEM

TPR HANDLE



CODE CAT NO.
3-01-18-20-012 PRO-BY012

- Durable structure made of chrome-nickel steel.
- Two-component, non-slip handle made of TPR (thermoplastic rubber).

BLADE 58-62

- 70% less effort during work thanks to the S-HD system.
- Structural hardness of the pliers HRC 44-48.
- Hardness of cutting blades HRC 58-62.
- Forged, ultra-strong structure reinforced with integral rivets.

# VDE HD SIDE CUTTER



160mm

HRC 44-48 HRC BLADE 60-64

CrV

1000V AC



CODE CAT NO.
3-01-18-10-203 PRO-BY203

- Made of cold forged chrome vanadium steel additionally nickel plated.
- Hardness of rivet connecting the arms HRC 34-38.
- Structural hardness of the pliers HRC 44-48.
- Hardness of cutting blades HRC 60-64.
- Two-component non-slip TPR handle manufactured in accordance with EN60900:2004.
- Cutting edge for cutting soft rods diameter up to 2.6 mm, medium hardness up to 2.4 mm and high hardness up to 2.0 mm.
- Suitable for working with voltages up to 1000 V AC.











## S-HD FACE CUTTER

70% LESS EFFORT

200mm

HRC 44-48 HRC BLADE 58-62 Cr-Ni

S-HD SYSTEM TPR HANDLE



- Durable structure made of chrome-nickel steel.
- Two-component, non-slip handle made of TPR (thermoplastic rubber).
- 70% less effort during work thanks to the S-HD system.
- Structural hardness of the pliers HRC 44-48.
- Hardness of cutting blades HRC 58-62.
- Forged, ultra-strong structure reinforced with integrated rivets.

## **FACE CUTTER**

250mm 300mm STEEL C50

HARDENED IN WHOLE



- Cutter for pulling and cutting nails and other items.
- Useful for carpentry, roofing and joinery work.
- Made of high quality unalloyed steel C50.
- Hardened in whole.
- Double coated handle with PVC and anti-slip coating.

# FACE CUTTER



HRC 42-48 HRC BLADE 60-64

CrV 60



- Made of cold forged chrome vanadium steel (CrV 60), additionally nickel plated.
- Hardness of rivet connecting the arms HRC 42-48.
- Structural hardness of the cutter HRC 42-48.
- Hardness of cutting blades HRC 58-62.
- Cutting edge, allowing to cut steel bars up to 2.2 mm in diameter.
- 56 mm arm spacing.
- Compliant with DIN 5746.

# IMPACT SCREWDRIVERS











- Made of high quality CrV 6150 steel.
- Blade oxidized, protected against corrosion, additionally reinforced.
- Magnetic tip.
- Hexagonal reinforcement for increased torque when using a wrench screwdriver.

	CODE	CAT NO.	DIMENSIONS
	3-01-30-WW-045	PRO-WW045	6 × 38 mm
Ö	3-01-30-WW-046	PRO-WW046	5 × 75 mm
Ö	3-01-30-WW-047	PRO-WW047	6 × 100 mm
Ö	3-01-30-WW-048	PRO-WW048	8 × 150 mm
$\overline{}$			

	CODE	CAT NO.	DIMENSIONS
$\oplus$	3-01-30-WW-049	PRO-WW049	2 × 38 mm
$\odot$	3-01-30-WW-050	PRO-WW050	1 × 75 mm
$\overline{\oplus}$	3-01-30-WW-051	PRO-WW051	2 × 100 mm
$\oplus$	3-01-30-WW-052	PRO-WW052	3 × 150 mm

## MECHANICAL SCREWDRIVERS

- HRC 51-54
- CrV



- Made of high quality CrV 6150 steel.
- Blade oxidized, protected against corrosion, additionally reinforced.
- Magnetic tip.
- Large, non-slip hexagonal handle.

## FLAT MECHANICAL SCREWDRIVERS



ΡН	AND P7	MECHANIC	CAL SCR	<b>EWDRIVERS</b>





	Ü	Ü	V	<b>W</b>		٠		i	ł	
MEC	(AH	NICA	L T	ORX	SC	RE	NDF	RIVE	RS	

	CODE	CAT NO.	DIMENSIONS
(*)	3-01-30-WW-011	PRO-WW011	0 × 75 mm
*	3-01-30-WW-012	PRO-WW012	1 × 100 mm
⊕	3-01-30-WW-013	PRO-WW013	2 × 100 mm
<b>®</b>	3-01-30-WW-014	PRO-WW014	3 × 150 mm

	CODE	CAT NO.	DIMENSIONS
<b>①</b>	3-01-30-WW-006	PRO-WW006 0	× 75 mm
$\Theta$	3-01-30-WW-007	PRO-WW007	1 × 100 mm
$\oplus$	3-01-30-WW-008	PRO-WW008	2 × 100 mm
$\oplus$	3-01-30-WW-009	PRO-WW009	2 × 150 mm
<b>(</b>	3-01-30-WW-010	PRO-WW010	3 × 150 mm



	CODE	CAT NO.	DIMENSIONS
<b>(2)</b>	3-01-30-WW-015	PRO-WW015	8 × 75 mm
<b>(3)</b>	3-01-30-WW-016	PRO-WW016	10 × 100 mm
<b>②</b>	3-01-30-WW-017	PRO-WW017	15 × 100 mm
<b>②</b>	3-01-30-WW-018	PRO-WW018	20 × 100 mm

CODE	CAT NO.	DIMENSIONS
3-01-30-WW-019	PRO-WW019	25 × 100 mm
3-01-30-WW-020	PRO-WW020	27 × 100 mm
3-01-30-WW-021	PRO-WW021	30 × 100 mm
3-01-30-WW-022	PRO-WW022	40 × 125 mm
	3-01-30-WW-019 3-01-30-WW-020 3-01-30-WW-021	3-01-30-WW-019 PRO-WW019 3-01-30-WW-020 PRO-WW020 3-01-30-WW-021 PRO-WW021

## VDE SCREWDRIVERS FOR ELECTRICIANS

- Made of high quality CrV 6150 steel.
- Blade oxidized, protected against corrosion additionally reinforced.
- Magnetic tip.
- Suitable for working with voltages up to 1000 V AC.

















	CODE	CAT NO.	DIMENSIONS
	3-01-30-WW-027	PRO-WW027	3 × 100 mm
	3-01-30-WW-028	PRO-WW028	4 × 100 mm
Θ	3-01-30-WW-029	PRO-WW029	6.5 × 150 mm
	CODE	CAT NO.	DIMENSIONS
<b>(</b>	<b>CODE</b> 3-01-30-WW-030	CAT NO. PRO-WW030	<b>DIMENSIONS</b> 0 × 60 mm
<b>(</b>			

## SCREWDRIVER SETS





- Made of high quality CrV 6150 steel.
- Blade oxidized, hardened and tempered, corrosion protected, additionally reinforced.
- Magnetic tip.
- Large, non-slip, two-component hex handle for high torque with minimum effort.





5 mm, 6 mm PH1, PH2



6 mm, 8 mm

#### **SCREWDRIVER SET 12IN1**



CAT NO. CODE 3-01-30-WZ-102 PRO-WZ102















- Made of high quality CrV 6150 steel.
- Blade oxidized, hardened and tempered, corrosion protected, additionally reinforced.
- Magnetic tip.
- Large, non-slip, two-component handle for high torque with minimum effort.



4 mm, 5 mm, 6 mm



PH 1, PH 2, PH3

T10, T15, T20



H3, H4, H5

## **SCREWDRIVER SET 14IN1**



CODE CAT NO. 3-01-30-WZ-104 PRO-WZ104















- Made of high quality CrV 6150 steel.
- Ergonomic, easy to use with magnetic tip.
- 3 possible blade positions (straight, 30° and 60° offset), lockable by means of a side button.
- Large, non-slip, two-component handle for high torque with minimum effort.

**⇒** 5 mm, 6 mm, 7 mm;

O H4, H5, H6;

PH1, PH2, PH3;

magnetic holder for bits

T10, T15, T20;

- 1 pc.

#### **IMPACT SCREWDRIVERS SET**



SET:



8 × 150 mm, 6 × 100 mm, 5 × 75 mm, 6 × 38 mm

PH 3  $\times$  150 mm, PH 2  $\times$  100 mm, PH 1x 75 mm, PH 2  $\times$  38

HRC 51-54









- Made of high quality CrV 6150 steel.
- Blade oxidized, hardened and tempered, corrosion protected, additionally reinforced.
- Magnetic tip.
- Large, non-slip, two-component hex handle for high torque with minimum effort.
- Impact, oil and grease resistant handle.
- Hexagonal reinforcement for increased torque when using a wrench screwdriver.

CODE	CAT NO.
3-01-30-W∠-111	PRO-W∠111

## **INSULATED SCREWDRIVERS SET**



#### SFT-



1.0 × 5.5 × 125 mm, 0.8 × 4.0 × 100 mm, 0.5 × 3.0 ×100 mm



PH 2 × 100 mm, PH 1 × 80 mm

Voltage tester

CODE CAT NO. 3-01-30-WZ-122 PRO-WZ122











HRC



- Made of high quality CrV 6150 steel.
- Blade oxidized, hardened and tempered, corrosion protected, additionally reinforced.
- Magnetic tip.
- Large, non-slip, two-component hexagonal handle for high torque with minimum effort.
- Handle elements made of plastic, enabling comfortable handling of the screwdriver during work.
- Soft, non-slip zones for full torque transfer through the handle.
- Insulation tested to 10,000 volts, which guarantees safe working conditions up to 1,000 volts according to DIN EN 60900 (IEC 60900: 2004).
- VDE and GS certification markings stamped into the handle.
- IEC 60900 designations: 2004 and 1000 V stamped on the insulating layer of the screwdriver.

## **INSULATED SCREWDRIVERS SET**



Voltage tester 140 mm

- 1.2 × 6.5 × 100, 1 × 5 × 100, 0.8 × 4 × 100, 0.5 × 3 × 100:
- PH2 × 100, PH1x 80;
- PZ2 × 100, PZ1 × 80;

T20 × 100, T15 × 100, T10 × 100













- Made of high quality CrV 6150 steel.
- For use at 1000 V AC and 1500 V DC in the temperature range -25°C
- Large, non-slip, 2-component handle for high torque with minimum effort, equipped with a quick-release coupling for easy blade changes.
- Blade oxidized, hardened and tempered, corrosion protected,
- Each piece of kit tested at 10,000V to ensure safe use.

CODE	CAT NO.
3-01-30-WZ-123	PRO-WZ123

## **MECHANICAL SCREWDRIVERS SET**



2 × 100 mm, 1 × 75 mm, 0 × 60 mm, 2 × 38 mm

6 × 150 mm, 5 × 125 mm, 3 × 75 mm

Magnetizer / demagnetizer













- Made of high quality CrV 6150 steel.
- Blade oxidized, hardened and tempered, corrosion protected, additionally reinforced.
- Magnetic tip.
- Large, non-slip, two-component hexagonal handle for high torque with minimum effort.

CODE	CAT NO.
3-01-30-WZ-101	PRO-WZ101

## PRECISION SCREWDRIVERS SET

















- Made of high quality CrV 6150 steel.
- Blade oxidized, hardened and tempered, corrosion protected,
- Magnetic tip.
- Large, non-slip, two-component hexagonal handle for high torque with minimum effort.

- T-handle with ratchet for bits 1 pc;
- Long Bits:

  - 150 mm: PH1, PH2 2 pieces, TORX 115 mm: T10, T15, T20, T25, T27- 5 o pieces, HEX 163 mm: HEX3, HEX4, HEX5,
  - O HEX6;
- 50 mm bits:

PZ1, PZ2, SL6, T20, T30, T40 - 6 pieces.

CAT NO. CODE 3-01-30-WZ-142 PRO-WZ142

# T-TYPE HEX SCREWDRIVERS SET

51-54







CODE CAT NO. 3-01-30-WZ-143 PRO-WZ143

- Made of high quality chrome vanadium steel.
- T-shaped plastic handle with hanging hole.

## SET:

- 4 screwdrivers on front of package, 4 screwdrivers on back
- Sizes: 2, 2.5, 3, 4, 5, 6, 8, 10 mm.

## **VOLTAGE SAMPLERS**

**DIGITAL** 



CODE	CAT NO.			
3-01-30-WW-101	PRO-WW101			









SIZE SL3

The test is performed "by touch" or induction only by bringing the indicator close to the tested installation.

#### Purpose/Application:

- Checking of electric installations in the voltage range of 12-250V.
- The tester is used for direct and indirect checking of AC, DC voltage in the range 12V 250V, grounding.
- Equipped with a tester that detects a break in the insulated wire.

#### Technical data:

- maximum voltage 250V
- voltage range 12V 250V
- DC (direct) and AC (alternating) voltage types
- 3mm wide flat head screwdriver bit (SL3), made of chrome vanadium steel
- ICD display showing the range of detected voltage
- voltage ranges 12V, 36V, 55V, 110V, 250V
- black plastic housing

ABS











- Sampler made of durable ABS.
- Length: 140mm
- Measuring range 100 to 250 V AC.
- Features an insulated full-length stem.
- Metal tip made of CrV steel.
- Long life of the neon diode.

CODE CAT NO.
3-01-30-WW-102 PRO-WW102

190M



CODE CAT NO.
3-01-30-WW-103 PRO-WW103













- Length: 190mm
- Measuring range 100 to 250 V AC.
- With a clear plastic housing that allows to see the indicator light in any position of the handle.
- Features an insulated full-length stem.
- Metal tip.
- Long life of the neon diode.
- Packaged in 24 pieces per display.

## ALLEN WRENCH SETS

SET OF SHORT ALLEN WRENCHES WITH A **BALL WT-09-HKK** 





- Made of high quality chrome vanadium steel (CrV 6150).
- Optimized hardness of the wrenches HRC 52-56.
- Ball joint, allowing the wrench to deviate up to 25° in any plane from the bolt axis
- Hardened wrench working parts.
- Chamfered edges for quick adjustment of wrench to bolt.
- Chrome plated wrench coating for anti-corrosion effect.
- Guaranteed high strength and durability.
- A safety feature that prevents the wrench from slipping out of the
- The wrench fits to the bolt to prevent deformation and damage
- A set of wrenches equipped with a compact handle made of high-quality plastic.
- Wrench sizes included: 1.5; 2; 2.5; 3; 4; 5; 6; 8 and 10 mm.

#### SET OF LONG ALLEN WRENCHES WT-09-HKD

CAT NO.

PRO-ZK001

CODE

3-01-22-WT-001



CODE CAT NO. 3-01-22-WT-002 PRO-7K002





- Made of high quality chrome vanadium steel (CrV 6150).
- Optimized hardness of the wrenches HRC 52-56.
- Ball joint, allowing the wrench to deviate up to 25° in any plane from the bolt axis.
- Hardened wrench working parts.
- The chamfered edges allow a quick fit for the wrench and screw.
- Chrome plated wrench coating for anti-corrosion effect.
- Guaranteed high strength and durability.
- A safety feature that prevents the wrench from slipping out of the
- The wrench fits to the bolt to prevent deformation and damage to the bolt.
- A set of wrenches equipped with a compact handle made of high-quality plastic.
- Wrench sizes included: 1.5; 2; 2.5; 3; 4; 5; 6; 8 and 10 mm.

## SET OF LONG ANTI-SLIP ALLEN WRENCHES WT-09-HKDA



CODE CAT NO. 3-01-22-WT-005 PRO-ZK005



6150





- Made of high quality chrome vanadium steel (CrV 6150).
- Optimized hardness of the wrenches HRC 52-56.
- Ball joint, allowing the wrench to deviate up to 25° in any plane from the bolt axis
- Hardened wrench working parts.
- The chamfered edges allow a quick fit for the wrench and screw.
- Chrome plated wrench coating for anti-corrosion effect.
- Additional non-slip coating (red) for safety and comfort.
- Guaranteed high strength and durability.
- A safety feature that prevents the wrench from slipping out of the
- The wrench fits to the bolt to prevent deformation and damage to the
- A set of wrenches equipped with a compact handle made of highquality plastic.
- Wrench sizes included: 1.5; 2; 2.5; 3; 4; 5; 6; 8 and 10 mm.

## **TORX WRENCH SETS**

#### SET OF SHORT TORX WRENCHES WT-09-TOK





Made of high quality chrome vanadium steel (CrV 6150).

- Optimized hardness of wrenches HRC 52-56.
- Hardened wrench working parts.
- The chamfered edges allow a quick fit for the wrench and screw.
- Chrome plated wrench coating for anti-corrosion effect.
- Guaranteed high strength and durability.
- A safety feature that prevents the wrench from slipping out of the screw.
- The wrench fits to the bolt to prevent deformation and damage to the bolt.
- A set of wrenches equipped with a compact handle made of high-quality plastic.
- Wrench sizes included: T10; T15; T20; T25; T27; T30 T40, T45; T50.

## SET OF LONG TORX WRENCHES WT-09-TOD



HRC 52-56

CrV 6150



T10; T15; T20; T25; T27; T30 T40; T45; T50



- Made of high quality chrome vanadium steel (CrV 6150).
- Optimized hardness of the wrenches HRC 52-56.
- Hardened wrench working parts.
- The chamfered edges allow a quick fit for the wrench and screw.
- Chrome plated wrench coating for anti-corrosion effect.
- Guaranteed high strength and durability.
- A safety feature that prevents the wrench from slipping out of the screw.
- The wrench fits to the bolt to prevent deformation and damage to the bolt.
- A set of wrenches equipped with a compact handle made of high-quality plastic.
- Wrench sizes included: T10; T15; T20; T25; T27; T30, T40, T45;
   T50

# SET OF TORX AND HEX WRENCHES



HRC 52-56 CrV 6150





6(mm) HEX: <u>1.5: 2: 2.5:</u> 3:4: 5: 6: 8: <u>10.</u> TORX: <u>110</u>: <u>115</u>: 120: 125: 127: <u>130</u>: <u>140</u>: <u>145</u>: <u>150</u>.

# 13

#### SET OF TORX AND HEX WRENCHES WITH A BALL WT-18-HKTOK



- Made of high quality chrome vanadium steel (CrV 6150).
- Optimized hardness of the wrenches HRC 52-56.
- Ball joint, allowing the wrench to deviate up to  $25^{\circ}$  in any plane from the bolt axis.
- Hardened wrench working parts, satin finish.
- Chamfered edges for quick adjustment of wrench to bolt.
- Chrome plated wrench coating for anti-corrosion effect.
- Guaranteed high strength and durability.
- Safety feature to prevent the wrench from slipping.
- The wrench fits to the bolt to prevent deformation and damage to the bolt.
- A set of wrenches equipped with a compact handle made of high-quality plastic.

## **RING WRENCHES**

LIFETIME WARRANTY CrV

DIN 3113



- Manufactured in compliance with DIN 3113.
- High-quality chrome vanadium steel ensures long-lasting durability of the wrench.
- The 15° offset eyelet makes it easy to work in hard-to-reach places.

CODE	CAT NO.	SIZE	CODE	CAT NO.	SIZE
3-01-25-WK-001	PRO-WK001	6mm	3-01-25-WK-012	PRO-WK012	17mm
3-01-25-WK-002	PRO-WK002	7mm	3-01-25-WK-013	PRO-WK013	18mm
3-01-25-WK-003	PRO-WK003	8mm	3-01-25-WK-014	PRO-WK014	19mm
3-01-25-WK-004	PRO-WK004	9mm	3-01-25-WK-015	PRO-WK015	20mm
3-01-25-WK-005	PRO-WK005	10mm	3-01-25-WK-016	PRO-WK016	21mm
3-01-25-WK-006	PRO-WK006	11mm	3-01-25-WK-017	PRO-WK017	22mm
3-01-25-WK-007	PRO-WK007	12mm	3-01-25-WK-018	PRO-WK018	23mm
3-01-25-WK-008	PRO-WK008	13mm	3-01-25-WK-019	PRO-WK019	24mm
3-01-25-WK-009	PRO-WK009	14mm	3-01-25-WK-020	PRO-WK020	27mm
3-01-25-WK-010	PRO-WK010	15mm	3-01-25-WK-021	PRO-WK021	30mm
3-01-25-WK-011	PRO-WK011	16mm	3-01-25-WK-022	PRO-WK022	32mm

## RATCHET RING WRENCH





72T



- The ratchet has 72 teeth which is reflected into a 5 degree working stroke.
- Wrench made of CrV steel.
- Polished wrench.

CODE	CAT NO.	SIZE
3-01-25-WK-301	PRO-WK301	6mm
3-01-25-WK-302	PRO-WK302	8mm
3-01-25-WK-303	PRO-WK303	10mm
3-01-25-WK-304	PRO-WK304	12mm
3-01-25-WK-305	PRO-WK305	13mm
3-01-25-WK-306	PRO-WK306	14mm
3-01-25-WK-307	PRO-WK307	15mm
3-01-25-WK-308	PRO-WK308	17mm
3-01-25-WK-309	PRO-WK309	19mm

## RATCHET AND JOINT RING WRENCH



- The ratchet has 72 teeth which is reflected into a 5 degree
- The wrench has a joint that allows to access any hard-to-reach
- Wrench made of CrV steel.
- Polished wrench.





JOINT

72T

CODE	CAT NO.	SIZE
3-01-25-WK-321	PRO-WK321	6mm
3-01-25-WK-322	PRO-WK322	8mm
3-01-25-WK-323	PRO-WK323	10mm
3-01-25-WK-324	PRO-WK324	12mm
3-01-25-WK-325	PRO-WK325	13mm
3-01-25-WK-326	PRO-WK326	14mm
3-01-25-WK-327	PRO-WK327	15mm
3-01-25-WK-328	PRO-WK328	17mm
3-01-25-WK-329	PRO-WK329	19mm

## SET OF RING WRENCHES



CODE	CAT NO.	QUANTITY
3-01-25-WK-101	PRO-ZK101	8
3-01-25-WK-102	PRO-ZK102	12
3-01-25-WK-103	PRO-ZK103	18

#### LIFETIME WARRANTY





DIN 3113

- Manufactured in compliance with DIN 3113.
- High-quality chrome vanadium steel ensures long-lasting durability of the wrench.
- The 15° offset eyelet makes it easy to work in hard-to-reach places.

#### **SET OF 18 PIECES**

Wrench sizes included:

6	- 17	19					
---	------	----	--	--	--	--	--

#### **SET OF 12 PIECES**

Wrench sizes included:

6-13	15	17	19	22
mm	mm	mm	mm	mm

#### **SET OF 8 PIECES**

Wrench sizes included:

VVICII	UII SIZ	CO IIIC	iluucu			
				14		

# RATCHET DRIVE WITH A RATCHET FUNCTION



CODE	CAT NO.	QUANTITY
3-01-25-WK-112	PRO-ZK112	12
3-01-25-WK-113	PRO-ZK113	18







DIN 3113

- Manufactured in compliance with DIN 3113.
- High-quality chrome vanadium steel ensures long-lasting durability of the wrench.
- The 15° offset eyelet makes it easy to work in hard-to-reach places.
- A handy ratchet wrench which can be used with a ratchet mechanism.

#### **SET OF 18 PIECES**

Wrench sizes included:

	,					
6-17	19	22	24	27	30	32

## SET OF 12 PIECES

Wrench sizes included

VVICION SIZE	,	IIICIU	u	cu.			
6-13		15		17	19	1	22
1111111	,		,		1111111	,	1111111

# SUPER DRIVE WITH EYELET FOR 6 TYPES OF SCREWS





CODE	CAT NO.	QUANTITY
3-01-25-WK-121	PRO-ZK121	8
3-01-25-WK-122	PRO-ZK122	12
3-01-25-WK-123	PRO₌7K123	12

LIFETIME WARRANTY



HRC 42-47

DIN 3113

- Manufactured in compliance with DIN 3113.
- High-quality chrome vanadium steel ensures long-lasting durability of the wrench.
- The 15° offset eyelet makes it easy to work in hard-to-reach places.
- Part with ring wrench designed to loosen 6 types of screws. Wrench part with  $30\,^\circ$  pitch.

## **SET OF 18 PIECES**

Wrench sizes included:

6-17	19	22	24	27 mm	30	32

## **SET OF 12 PIECES**

Wrench sizes included:

6-13		17		
mm	mm	mm	mm	mm

#### **SET OF 8 PIECES**

Wrench sizes included:

8	9 10		13			19 mm
---	------	--	----	--	--	----------

## SET OF WRENCHES

#### FOR MACHINED SCREWS



CODE	CAT NO.	QUANTITY
3-01-25-WK-125	PRO-ZK125	6
3-01-25-WK-126	PRO-ZK126	11

LIFETIME WARRANTY CrV

HRC 42-47 DIN 3113

- Manufactured in compliance with DIN 3113.
- High-quality chrome vanadium steel ensures long-lasting durability of the wrench.
- The 15° offset eyelet makes it easy to work in hard-to-reach places.
- A handy ratchet wrench which can be used with a ratchet mechanism.

#### Set of 11 pieces Set of 6 pieces

Wrench sizes included:

Wrench sizes included:

Cr





6 pcs.

72T

## WITH A RATCHET



 The ratchet has 72 teeth which is reflected in a 5 degree working stroke.

- Wrenches made of CrV steel.
- Polished wrench.
- SIZES: 12/13/2010-15-17-19

#### WITH A RATCHET AND JOINT

CODE CAT NO.

PRO-WK232

3-01-25-WK-232



6 pcs.

72T

JOINT

 The ratchet has 72 teeth which is reflected in a 5 degree working stroke.

Cr

- The wrenches have a joint that allows to reach hard-to-reach places.
- Wrenches made of CrV steel.
- Polished wrench.
- SIZES: 12/13/2010-15-17-19

## **SET OF RING WRENCHES 8 PIECES**





CODE CAT NO. 3-01-25-WK-201 PRO-ZK201

- Manufactured in compliance with DIN 3113.
- High-quality chrome-vanadium steel ensures long-term durability of the wrench.
- Sizes: 8, 9, 10, 12, 13, 14, 17, 19 mm.

#### **SET OF RING WRENCHES 12 PIECES**

PRO-ZK202



DIN 3113

12 pcs.



- Manufactured in compliance with DIN 3113.
- High-quality chrome-vanadium steel ensures long-term durability of the wrench.
- Sizes: 6, 7, 8, 9, 10, 11, 12, 13, 14, 17, 19, 22 mm.

## SET OF FLAT DOUBLE-SIDED WRENCHES



DIN 3113 8 pcs.

## **SET OF 8 PIECES**

3-01-25-WK-202



- Manufactured in compliance with DIN 3113.
- High-quality chrome-vanadium steel ensures long-term durability of the wrench.
- Sizes: 6/7, 8/9, 10 /11, 12/ 13, 14/15, 16/17, 18/19, 20/22 mm.

# **SET OF OFFSET RING WRENCHES**

DIN 3113

8 pcs.

## SET OF 8

CODE



- Manufactured in compliance with DIN 3113.
- High-quality chrome-vanadium steel ensures long-term durability of the wrench.
- Sizes: 6/7, 8/9, 10 /11, 12/ 13, 14/15, 16/17, 18/19, 20/22 mm.

## **RATCHET RING WRENCH 4 IN 1**

CrV

4IN1

72T



- CODE
   CAT NO.
   SIZE

   3-01-25-WK-241
   PRO-WK241
   8×9×10×11 mm

   3-01-25-WK-141
   PRO-WK141
   10x13x17x19 mm

   3-01-25-WK-243
   PRO-WK143 16×17×18×19 mm
- High-quality chrome-vanadium steel ensures long-term durability of the wrench.
- Precise yet powerful ratchet mechanism based on a 72-tooth inner ring.
- Body made of CrV steel alloy.
- Driven even with minimum space, the wrench requires only  $5^{\circ}$  of tilt.
- Intuitive clockwise and counterclockwise rotation switch.
- Sizes: 10x13x17x19 mm; 8×9×10×11 mm; 16×17×18×19 mm;

## UNIVERSAL RING WRENCH

Cr

8-22 mm 270 mm

35IN1



SCALE	SMALL EYE	LARGE EYE
METRIC	8-13 mm	14-22 mm
INCH	5/16"-1/2"	9/16"-7/8"
TORX E-10-E-14 E-16-	E-24	
CODE	CAT NO.	

- Made of durable chrome vanadium steel. CrV
- The universal wrench will replace 35 different tools.
- In metric scale, it will replace wrenches in sizes 8-22 mm.
- In inch scale, it will replace wrenches ranging in size from 5/16" to 7/8".
- The universal wrench will replace E-10 to E-24 torx type wrenches.
- The wrench fits most types of nuts and fittings such as hexagonal, round, square or rounded fasteners.
- The specially made inner edges of the wrench allow for a secure grip and no unnecessary wrench jumps.
- Wrench length 270 mm

## 1/2" UNIVERSAL SOCKET

PRO-WK161

1/2"

11-32 mm



CODE CAT NO.

3-01-25-WK-144 PRO-WK144

3-01-25-WK-161

- 1/2" input.
- Outer hexagon up to 47 mm.
- Working rods made of chrome molybdenum steel.
- Hexagonal rods stack on bolts and nuts from 11 32 mm.
- For all metric and inch dimensions, tetragonal, pentagonal, hexagonal, octagonal, Torx.

3/8" UNIVERSAL SOCKET

CAT NO.

PRO-WK145



7-19 mm



- **-** 3/8" input.
- Outer hexagon up to 27 mm.
- Working rods made of chrome molybdenum steel.
- Hexagonal rods stack on bolts and nuts from 7 19 mm.
- For all metric and inch dimensions, tetragonal, pentagonal, hexagonal, octagonal, Torx.

**CODE** 3-01-25-WK-145

## **UNIVERSAL SOCKET WITH RATCHET 3/8"**



7-19 mm

72T





- Wrench and socket made of chrome vanadium steel;
- 3/8" input.
- Outer hexagon up to 27 mm.
- Working rods made of chrome molybdenum steel.
- Hexagonal rods stack on bolts and nuts from 7-19 mm.
- For all metric and inch dimensions, quadrant, pentagon, hexagon, octagon, TORX.

## Examples of screws



Examples of butterflies and hooks



# UNIVERSAL SOCKET WITH RATCHET 1/2"



11-32 mm

72T







- 1/2" input.

- Working rods made of chrome molybdenum steel.

- Outer hexagon up to 47 mm.

- Hexagonal rods stack on bolts and nuts from 11-32 mm.

- Wrench and socket made of chrome vanadium steel;

For all metric and inch dimensions, quadrant, pentagon, hexagon, octagon, TORX.

Examples of screws



Examples of butterflies and hooks



# HOOK WRENCH FOR PIPES AND

PRO-WK143



8-25 mm 1/4"-1





- High quality chrome vanadium steel ensures long tool life.
- Allows work on pipe and bolts in sizes 8-25 mm, 1/4"-1".
- Precision slide for jaw adjustment.
- Special jaw design with teeth that engage the screw.
- Bimaterial, non-slip handle.
- Ergonomic design for easy one-handed operation even in hard-to-reach places.

CAT NO. CODE 3-01-25-WK-151 PRO-WK151

3-01-25-WK-143

## **PLUMBER WRENCHES**









- The special jaw design of the plumber wrench provides a secure grip and fits the shape of the nut.
- Metric scale applied to wrench jaws.
- Precision wrench worm mechanism forged, hardened.
- Embossed adjustable wrench length.
- TPR handle coated with grease and oil resistant plastic.
- A hole in the handle to hang the wrench.
- Perfect as automotive workshop equipment.

## **UNIVERSAL WRENCH FOR CONTROL CABINETS**



7IN1





PRO-WK152 200 mm

PRO-WK154 300 mm

3-01-25-WK-153 PRO-WK153 250 mm

- Multi-purpose cross head wrench measuring 60 x 90 mm.
- Made of zinc alloy in silver color.
- Bits made of chrome vanadium steel.
- High torque and low risk of slipping.
- Especially for control cabinets, shut-off systems for gas, water, electricity, technical installations in buildings such as air conditioning, ventilation, shut-off valves, switchboards, etc.
- 5/7/8
- 9-10
- 9-11- 5

6/7/8/9


PH2

CODE	CAT NO.
3-01-21-GA-001	PRO-WK401

3-01-25-WK-152

3-01-25-WK-154

## STILLSON STEEL WRENCH FOR PIPES





<ul> <li>Jaws forged and groun</li> </ul>	nd from alloy steel
---	---------------------

- Malleable cast iron body.
- Scale for setting the desired pipe diameter.
- Designed for civil engineering, water construction and the oil and gas industry.

CODE	CAT NO.	LENGTH	WEIGHT
3-01-25-HK-001	PRO-WK501	10"	0.7 kg
3-01-25-HK-002	PRO-WK502	14"	1.34 kg
3-01-25-HK-003	PRO-WK503	18"	2.0 kg
3-01-25-HK-004	PRO-WK504	24"	3.87 kg

## STILLSON ALUMINUM WRENCH FOR





CODE	CAT NO.	LENGTH	WEIGHT
3-01-25-HK-011	PRO-WK511	14"	0.38 kg
3-01-25-HK-012	PRO-WK512	18"	1.34 kg
3-01-25-HK-013	PRO-WK513	24"	2.34 kg

- Super strong, ultra lightweight cast aluminum.
- Jaws forged and ground from alloy steel.
- Scale for setting the desired pipe diameter.
- Designed for civil engineering, water construction and the oil and gas industry.

# PLUMBER WRENCH 45°





- Wrench made of chrome vanadium steel.
- Recommended for heavy duty hydraulic work.
- The robust teeth prevent the wrench from slipping on oval objects, pipes and valves or bolts.
- The wrench has a worm mechanism with a screw to regulate the opening of the working jaws and a strong clamping, which is reinforced by the long arms of the wrench
- Jaws of wrench set at 45° to the handle
- Wrench length 430 mm



**FLAT COARSE FILE 200MM** 

COARSE FILE TYPE "0"











- Flat-profile file with "0" cut for pre-sanding surfaces.

- For machining metal and hard plastics and other materials.
- Made of high carbon T12 steel with hardness of 60-65 HRC.

3-01-25-PW-001 PRO-PW001

CODE

## FLAT BLOCK PLANE 200MM

BLOCK PLANE TYPE "1"

T12 HF









CAT NO.

CODE CAT NO.
3-01-25-PW-002 PRO-PW002

- Flat-profile file with "1" cut for pre-sanding surfaces.
- For machining metal and hard plastics and other materials.
- Made of high carbon T12 steel with hardness of 60-65 HRC.

#### **SEMICIRCULAR COARSE FILE 200MM**

COARSE FILE TYPE "0" T12 STEEL HRC 60-65 SIZE 200mm





- Half round file with "0" cut for rough work.

- For machining metal and hard plastics and other materials.

- Made of high carbon T12 steel with hardness of 60-65 HRC.

CODE CAT NO.
3-01-25-PW-004 PRO-PW004

#### SEMICRICULAR BLOCK PLANE 200MM

BLOCK PLANE TYPE "1" T12 STEEL HRC

SIZE 200mm





- Semicircular file with "1" cut for rough work.
- For machining metal and hard plastics and other materials.
- Made of high carbon T12 steel with hardness of 60-65 HRC.

CODE CAT NO.
3-01-25-PW-005 PRO-PW005

## **ROUND COARSE FILE 200MM**

COARSE FILE TYPE "0"

T12 STEEL









- Round-profile file with "0" cut for pre-sanding surfaces.
- For machining metal and hard plastics and other materials.
- Made of high carbon T12 steel with hardness of 60-65 HRC.

CODE CAT NO. 3-01-25-PW-007 PRO-PW007

#### **ROUND BLOCK PLANE 200MM**

BLOCK PLANE TYPE "1" T12 STEEL



SIZE 200mm





CAT NO.

PRO-PW008

- Round-profile file with "1" cut for pre-sanding surfaces.

- For machining metal and hard plastics and other materials.
- Made of high carbon T12 steel with hardness of 60-65 HRC.

TRIANGULAR COARSE FILE 200MM

CODE

3-01-25-PW-008

COARSE FILE TYPE "0"

T12









**CODE CAT NO.** 3-01-25-PW-010 PRO-PW010

- Triangular file with "0" cut for pre-sanding surfaces.
- For machining metal and hard plastics and other materials.
- Made of high carbon T12 steel with hardness of 60-65 HRC.

TRIANGULAR BLOCK PLANE 200MM

BLOCK PLANE TYPE "1" T12 STEEL



SIZE 200mm





**CODE CAT NO.** 3-01-25-PW-011 PRO-PW011

- Triangular file with "1" cut for pre-sanding surfaces.
- $\mbox{-}$  For machining metal and hard plastics and other materials.
- Made of high carbon T12 steel with hardness of 60-65 HRC.



CODE 3-01-25-PW-031

**FLAT COARSE FILE 200MM** 

COARSE FILE TYPE "0"

A3 STEEL

HRC 10+

SIZE





- Flat-profile file with "0" cut for filing and smoothing surfaces. - For machining wood, soft plastics and soft materials.

- Made of A3 steel with hardness of 10+ HRC.

**FLAT BLOCK PLANE 200MM** 

CAT NO.

PRO-PW031

**BLOCK PLANE** TYPE "1"



SIZE 200mm





- Flat-profile file with "1" cut for filing and surface smoothing.

- For machining wood, soft plastics and soft materials.

- Made of A3 steel with hardness of 10+ HRC

CODE CAT NO. 3-01-25-PW-032 PRO-PW032

**SEMICIRCULAR COARSE FILE 200MM** 

COARSE FILE TYPE "0"

A3 STEEL

HRC 10+

SIZE





CAT NO. CODE 3-01-25-PW-034 PRO-PW034 - Semi-circular file with "0" cut for filing and surface finishing.

- For machining wood, soft plastics and soft materials. - Made of A3 steel with a hardness of 10+ HRC.

**SEMICRICULAR BLOCK PLANE 200MM** 

**BLOCK PLANE** TYPE "1"

A3 STEEL

HRC 10+

SIZE





CAT NO. CODE 3-01-25-PW-035 PRO-PW035

- Semi-circular file with "1" cut for filing and surface finishing.
- For machining wood, soft plastics and soft materials.
- Made of A3 steel with hardness of 10+ HRC.

## **ROUND COARSE FILE 200MM**





- File with round profile and "0" cut for filing, surface leveling.
- For machining wood, soft plastics and soft materials.
- Made of A3 steel with hardness of 10+ HRC.

**CODE CAT NO.** 3-01-25-PW-037 PRO-PW037

#### **ROUND BLOCK PLANE 200MM**

BLOCK PLANE TYPE "1" A3 STEEL









CODE CAT NO.
3-01-25-PW-038 PRO-PW038

- File with round profile and cut "1" for filing, surface leveling.
- For machining wood, soft plastics and soft materials.
- Made of A3 steel with a hardness of 10+ HRC.

## CHAIN SHARPENING FILE

4.0MM 200MM











- A file with a special profile and cut for sharpening saw chains.

CODE CAT NO.
3-01-25-PW-051 PRO-PW051

4.8MM 200MM











- Made of GCr15 bearing steel with hardness of 60 65 HRC.
- A file with a special profile and cut for sharpening saw chains.
- Made of GCr15 bearing steel with hardness of 60 65 HRC.

CODE CAT NO.
3-01-25-PW-052 PRO-PW052



FOR METAL 200MM 3PCS

CAT NO.

PRO-PW101

CAT NO.

PRO-PW103





- A set of files with flat, round and half-round profiles and a cut type "1" for pre-sawing surfaces.
- For machining metal and hard plastics and other materials.
- Made of high carbon T12 steel with hardness of 60-65 HRC.

#### **FOR WOOD**

3-01-25-PW-101

CODE



COARSE FILE TYPE "0" HRC 10+ A3 STEEL SIZE PROFIL PROFIL

- Set of files with round and half-round profile and cut type "0" for initial surface sawing.
- For machining wood and soft plastics and other materials.
- Made from A3 high carbon steel with hardness of 10+ HRC.

#### **SET OF NEEDLE FILES** 160MM 6PCS

3-01-25-PW-103





- edges for filing and smoothing surfaces.
- For machining metal and hard plastics and other materials.
- Made of high carbon T12 steel with hardness of 60-65 HRC.

CODE CAT NO. 3-01-25-PW-107 PRO-PW107

#### FOR WOOD AND METAL 10PCS WITH INTERCHANGEABLE HANDLE





T12 STEEL 45

- A 10 in 1 set of files with flat, round, semicircular and cut "0" and "1" edges for working on different surfaces.
- For machining metal, hard plastics, wood, soft materials and other
- Made from T12 and A13 high carbon steels.

CAT NO.
PRO-PW109





## **GEL KNEE PADS**

**GEL KNEE PADS N-480** 









- Sturdy and very durable gel knee pads with injection molded anticompressive gel.
- Provide knee protection for work that requires kneeling.
- The large surface area of the knee pad protects the tibias and distributes knee pressure over a larger area.
- Designed especially for tile setters, roofers, pavers, for the home, workshop and garden.
- Universal Size.

# **GEL KNEE PADS N-490**

CAT NO.

CODE

3-01-13-01-01







Elastic bands with Velcro straps ensure a quick and

Large pad with low profile specially designed to prevent loss of grip.

Thick, high-density foam with closed cells in its structure for all-day comfort.

Made of durable 600HD polyester fabric.

Special profile for easy positioning of the knee pad

Neoprene straps for stability and comfort

- Flexible and durable Velcro fasteners ensure the knee pads stay in place.
- The profile of the knee pad allows you to work safely in a seated position while supporting your body weight on your heels.
- The foam padding is trimmed with extra durable nylon for maximum cushioning.
- Perforated neoprene lining keeps moisture out.
- Universal size.

#### CAT NO. 3-01-13-01-02 PRO-NK002

CODE



VELCRO.





#### **POLYESTER KNEE PADS N-380**

POLYESTER KNEE PADS



- Anti-compression knee pads.

- Neoprene EVA foam padding for maximum comfort, plus protection from moisture and cold.
- Elastic VELCRO closures with drawstrings for perfect knee pad positioning.
- Covered with a very durable polyester material.
- Universal Size.

## **POLYESTER KNEE PADS N-280**





VELCRO





- Anti-compression knee pads.
- Neoprene EVA foam padding for maximum comfort, plus protection from moisture and cold.
- Elastic VELCRO closures with drawstrings for perfect knee
- Covered with a very durable polyester material.
- Plastic protective cap permanently riveted to the knee pad.
- Universal Size.

CODE	CAT NO.
3-01-13-01-04	PRO-NK004

## PROTECTIVE KNEE PADS FOR PANTS















- Knee pads made of flexible EVA foam.
- Knee pads for protective pants and dungarees with pockets for
- It is possible to adjust the size of the knee pads by trimming.
- Provide knee protection for work that requires kneeling.
- Reinforced knee pads conform to EN 14404:2004+A1:2010 standard and are CE certified

CODE	CAT NO.
3-01-13-01-10	PRO-NK010

#### N-E520











- Knee pads made of flexible EVA foam.
- Knee pads for protective pants and dungarees with pockets for knee pads.
- It is possible to adjust the size of the knee pads by trimming.
- Provide knee protection for work that requires kneeling.
- Reinforced knee pads conform to EN 14404:2004+A1:2010 standard and are CE certified

CODE	CAT NO.
3-01-13-01-11	PRO-NK011







600D POLYESTER



- Tool belt 24 x 28 cm.
- Strap.
- 7 pockets.
- Additionally integrated hammer holder.
- Polyester 600 D lightweight, UV resistant.

CODE	CAT NO.
3-01-13-OR-014	PRO-SN014

# **TOOL BELT**

600D

16 POCKETS



Tool belt 76 x 33 cm.

- 16 pockets.
- Additionally integrated hammer holder.
- Polyester 600 D lightweight, UV resistant.
- Waist size 80-120cm.

CODE	CAT NO.
3-01-13-OR-015	PRO-SN015

600D

## **TOOL BELT**

CODE

3-01-13-OR-016



- Tool belt 61 x 30 cm.

- 15 pockets.

- Additionally integrated hammer holder.
- Polyester 600 D lightweight, UV resistant.

- Waist size 80-120cm.

# TOOL BELT WITH LEATHER STRAP

CAT NO.

PRO-SN016



600D POLYESTER



15 POCKETS



3-01-13-OR-018 PRO-SN018

- 74 x 41 cm tool belt with leather strap.
- 2 capacious tool pouches 18 pockets.
- Belt padded inside with breathable and soft mesh.
- Additionally integrated hammer holder.
- Polyester 600 D lightweight, UV resistant.
- Leather belt 143x5cm.
- Waist size 80-120cm.
- Leather grommets on the belt allow for mounting harnesses.

# **HAMMER HOLDER**





CODE CAT NO. 3-01-13-OR-020 PRO-SN020

1200D

- Product made of 1200 D polyester.
- Handle made of high-grade steel.

## LEATHER





- Product made of high quality leather.
- Handle made of high-grade steel.

CODE	CAT NO.
3-01-13-OR-021	PRO-SN021

## **UNIVERSAL TOOL HOLSTER**







- Universal tool holster 19 x 23 cm.
- For attaching to a tool belt or waistband.
- 9 pockets.
- Additionally integrated holders for tape measures, tapes, etc.
- Polyester 600 D lightweight, UV resistant.

CODE	CAT NO.
3-01-13-OR-017	PRO-SN017

## **POWER TOOL HOLSTER**







## POLYESTER POWER TOOL HOLSTER



- Holster made of durable 600D polyester.
- Reinforced with rivets at joints.
- Tool holder with stabilizing strap.
- Drill and bit separators.

CODE	CAT NO.
3-01-13-OR-023	PRO-SN023

## ENDURANCE LEATHER/POLYESTER POWER TOOL HOLSTER



HANDMADE

TRENGTHENED WITH RIVETS





- Holster made of durable 1200D polyester and suede leather.
- Reinforced with rivets at joints.
- Tool holder with stabilizing strap.
- Drill and bit separators.

CODE	CAT NO.
3-01-13-OR-024	PRO-SN024

# LEATHER BELT







- Leather belt 143 x 5 cm.
- For attaching holsters and tool pouches.
- Polyester 600 D lightweight, UV resistant.
- Waist size 80-120cm.
- The belt also appears in the index 3-01-13-OR-018.

CODE CAT NO.

3-01-13-OR-019 PRO-SN019

## LEATHER TOOL BELT



CODE CAT NO.
3-01-13-OR-050 PRO-SN050

CODE

3-01-13-OR-051

SUEDE STRENG WITH

NED ETS HA

HANDMADE

HANDMADE

10 POCKETS

- Belt made of suede leather.
- Strengthened with rivets at the joints.
- 2 large pockets and 2 medium-sized tool pockets.
- Steel holder for measuring tape.
- 6 smaller pockets for screwdrivers, pencils, pliers, etc.
- 2 leather holders for hammers.
- Strap made of durable polyester with three-point snap buckle.
- Size 80-120cm.

# LEATHER TOOL BELT



- Belt made of suede leather.

- Strengthened with rivets at the joints.
- 2 large tool pockets.
- 6 smaller pockets for screwdrivers, pencils, pliers etc.
- 2 leather holders for hammers.
- Strap made of durable polyester with three-point snap buckle.
- Size 80-120cm.

## **ENDURANCE POLYESTER AND LEATHER TOOL BELT**



CODE CAT NO.
3-01-13-OR-055 PRO-SN055

SUEDE

IANDMADE

TRENGTHENED

TRENGTHENED WITH RIVETS 1680D POLYESTER

- Belt made of durable 1680D polyester and suede leather.
   Elements filled with highly flexible EVA foam.
- Reinforced with rivets at the joints
- 2 large tool pockets. Pocket for screwdriver or drill has leather stabilizing strap and separators for drills and bits. Steel loop hammer holder.
- Additional lumbar belt made of durable polyester makes work easier and protects the spine. Wide leather belt with a double steel buckle.
- Size 80-120cm.

## ENDURANCE POLYESTER AND LEATHER TOOL BELT



CAT NO.

PRO-SN056

CODE

3-01-13-OR-056

SUEDE HANDMADE STRENGTHENED WITH RIVETS 1680D POLYESTER

- Belt made of durable 1680D polyester and suede leather.
- Elements filled with highly flexible EVA foam.
- Reinforced with rivets at the joints.
- 1 large and 1 medium tool pocket, and a steel roll measure
- 3 leather holders for individual tools e.g. screwdrivers, pliers etc

## **ENDURANCE POLYESTER AND LEATHER TOOL BELT**




CODE CAT NO.
3-01-13-OR-057 PRO-SN057

SUEDE HANDMADE STRENGTHNED 600D WITH RIVETS POLYESTER

- Belt made of durable 600D polyester and suede leather.
- Reinforced with rivets at the joints.
- 8 pockets for keys, pliers, screwdrivers.
- 5 small pockets for nails, bits, screws.
- 2 leather hammer holders and an accessory clip holder.
- Wide belt with three-point buckle of durable plastic for quick fastening and unfastening.
- Size 80-120cm.

## PROTECTIVE GLOVES




## **ENDURANCE**



CODE	CAT NO.	SIZE
3-01-13-BR-106	PRO-BR106	L
3-01-13-BR-105	PRO-BR105	XL

The strengthened synthetic leather glove provides great material strength with hand protection.



L

 An extra layer on the grip and top side of the glove cushions accidental impacts.



## **ENDURANCE PROTECTIVE GLOVES**





- The strengthened synthetic leather glove provides great material strength with hand protection.
- PVC seams provide anti-vibration protection and protect the wrists.
- The glove is sewn from two layers of stretch spandex.
- The cuff of the glove has an elastic band with Velcro adjustment.
- There is a soft terry cloth on the thumb for wiping sweat, and a permeable material on the index finger for touchscreen navigation.

CODE	CAT NO.	SIZE
3-01-13-BR-101 PRO-E	3R101 XL	
3-01-13-BR-102	PRO-BR102	XXL

## PROTECTIVE GLOVES "VAMPIRES" LATEX



10

TEXTILE T/C LATEX COATING







- Synthetic latex glove on T/C (cotton/polyester) textile liner.
- Back side with air access.
- Wrist welt.
- Latex coated grip side, fingers and half of the dorsal side.
- Complies with EN388 [1121].
- Good abrasion resistance.
- Size 10, 9.

CODE	CAT NO.	SIZE
3-01-13-BR-501	PRO-BR501	10

## PROTECTIVE GLOVES "DRAGONKI" LATEX FOAM



TEXTILE POLYESTER COAT LATEX FOAM







- Synthetic glove covered with latex foam on a polyester textile liner.
- Back side with air access,
- Wrist welt
- Grip side, fingers and half of the back side coated with latex foam.
- Complies with EN388 [3131].
- Good abrasion resistance.
- Size 8.

CODE	CAT NO.	SIZE
3-01-13-BR-518	PRO-BS001	8

## PROTECTIVE GLOVES WITH NITRILE CUFF



10 TEXTILE COTTON NITRILE COAT

TRILE OAT 4121 EN3



- Synthetic nitrile glove on cotton textile liner.
- Nitrile-coated grip side, fingers and half of the back side.
- Complies with EN388 [4121].
- Good abrasion resistance.
- Size 10.

CODE	CAT NO.	SIZE
3-01-13-BR-005	PRO-BR005	10

#### PROTECTIVE GLOVES ANTI-IMPACT LATEX BACK



10 TEXTILE T/C

LATEX COATING



- Synthetic latex glove on T/C (cotton/polyester) textile liner.
- Back side with air access.
- Wrist welt.
- Latex coated grip side, fingers and half of the dorsal side.
- Latex foam points placed on the back.
- Complies with EN388 [1121].
- Good abrasion resistance.
- Size 10.

CODE	CAT NO.	SIZE
3-01-13-BR-008	PRO-BR008	10

#### PROTECTIVE GLOVES ANTI-VIBRATIONS



T/C TEXTILE COAT LATEX FOAM







- Synthetic latex glove on T/C (cotton/polyester) textile liner.
- Back side with air access.
- Wrist welt.
- Grip side, lace side and half of back side coated with latex foam dots.
- Complies with EN388 [4121].
- Good abrasion resistance.
- Size 10.

CODE	CAT NO.	SIZE
3-01-13-BR-009	PRO-BR009	10

# MAGNETIC ARMBAND







- Magnetic band equipped with 6 neodymium magnets for holding small metal objects: screws, nails, drill bits in the direct working range.
- Strong Velcro for comfortable working in all conditions.
- Soft underband for comfort and convenience.
- Adjustable band length to accommodate any wrist or forearm size

CODE	CAT NO.
3-01-13-OR-007	PRO-NK007

## SAFETY GOGGLES TRANSPARENT

#### **SAFETY GOGGLES TRANSPARENT SG-50**





- Wide joint between lenses and arms for tight protection.
- Strong, ultra-lightweight polycarbonate lenses that block 99.9% of harmful UV rays.
- Scratch protection coating.
- "Shoulder" shaped arms for stability.
- Universal shape nose pads to fit everyone.
- Applied Standards/Technical Specifications: EN 166: 2001

CODE	CAT NO.
3-01-13-01-405	PRO-SG405

## **SAFETY GOGGLES TRANSPARENT SG-60**





- Flexible and highly durable glass and blades.
- Strong, ultra-lightweight polycarbonate lenses that block 99.9% of harmful UV rays.
- Scratch protection coating.
- "Paddle" shaped arms for stability.
- Universal shape nose pads to fit everyone.
- Applied Standards/Technical Specifications: EN 166: 2001

3-01-13-1	31-400	110-30400
ANTI	ANTI	POLYCARBON
SCRATCH	UV	ATE

CODE 3-01-13-01-406

CAT NO.

DDO-SC406

## TRANSPARENT SAFETY GOGGLES WITH STRING SG-70C



- Wide joint between lenses and arms for tight protection.
- Strong, ultra-lightweight polycarbonate lenses that block 99.9% of harmful UV rays.
- Scratch protection coating.
- "Paddle" shaped arms for stability, adjustable.
- Universal shape nose pads to fit everyone.
- Applied Standards/Technical Specifications: EN 166: 2001

CODE	CAT NO.
3-01-13-01-407	PRO-SG407

## **SAFETY GOGGLES TRANSPARENT SG-80**





- Wide joint between lenses and arms for tight protection.
- Strong, ultra-lightweight polycarbonate lenses that block 99.9% of harmful UV rays.
- Scratch protection coating.
- "Paddle" shaped arms for stability.
- Universal shape nose pads to fit everyone.
- Applied Standards/Technical Specifications: EN 166: 2001

CODE	CAT NO.
3-01-13-01-408	PRO-SG408

POLYCARBON

POLYCARBON

POLYCARBON

#### **TINTED SAFETY GOGGLES**



- Flexible and highly durable glass and blades.
- Strong, ultra-lightweight, tinted polycarbonate lenses that block 99.9% of harmful UV rays.
- Scratch protection coating. "Paddle" shaped arms to ensure stability. Universal shape nose pads to fit everyone.
- Applied Standards/Technical Specifications: EN 166: 2001

CODE	CAT NO.
3-01-13-01-410	PRO-SG410

## PVC SAFETY GOGGLES WITH BAND





- Wide joint between lenses and arms for tight protection.
- Strong, ultra-lightweight polycarbonate lenses that block 99.9% of harmful UV rays.
- Scratch protection coating. Universal shape nose pads to fit everyone. Removable and replaceable glass and band.
- Ventilation System.
- Applied Standards/Technical Specifications: EN 166: 2001

CODE	CAT NO.
3-01-13-01-401	PRO-SG401

## **PVC SAFETY GOGGLES WITH BAND SG-20**



- Wide joint between lenses and arms for tight protection.
- Strong, ultra-lightweight polycarbonate lenses that block 99.9% of harmful UV rays.
- Scratch protection coating.
- Universal shape nose pads to fit everyone.
- Applied Standards/Technical Specifications: EN 166: 2001



## TRANSPARENT SAFETY GOGGLES WITH LED


TRANSPARENT SAFETY GLASSES WITH LED SG-70L





- Wide joint between lenses and arms for tight protection.
- Strong, ultra-lightweight polycarbonate lenses that block 99.9% of harmful UV rays. Scratch protection coating.
- "Blade" shaped arms for stability
   Universal shape nose pads to fit everyone.
- Complete with battery.

CODE	CAT NO.
3-01-13-01-409	PRO-SG409



# **LED HEAD FLASHLIGHTS**

# LED HEAD FLASHLIGHT











Modern head flashlight equipped with COB LED strip (3W) - much brighter and more economic than the standard LED.

- Working brightness 120 lumens.
- Lamp body made of durable plastic
- ABS, covered with TPR (thermoplastic rubber).
- Powered by AAA batteries (3 included).
- Adjustable and detachable headband made of durable material for easy attachment to head or helmet.
- Adjustable light angle.

CODE CAT NO. 3-01-13-OS-102 PRO-LD102

# LED HEAD FLASHLIGHT











CAT NO. 3-01-13-OS-101 PRO-LD101

- Modern head flashlight equipped with an innovative LED strip CREE XPE(3W) much brighter and more economical than the standard LED.
- Operating brightness 120 or 180 lumens.
- Lamp body made of aluminum and durable ABS plastic.
- 4 light modes: 100% CREE, 30% CREE, 100% COB, COB STROBE.
- Additional red warning light located on the back of the flashlight.
- Powered by AAA batteries (3 included).
- Adjustable and detachable headband made of durable material for easy attachment to head or helmet.
- Adjustable light angle.

# **HEADLAMP**













- Modern head flashlight, equipped with CREE XPE LED (3W) much brighter and more economical than a standard LED. - Working brightness - 120 lumens.
- Lamp body made of durable ABS plastic.
- Modes of operation: LEFT button: 100%, 30%, STROBE and RIGHT button: motion sensor switch to ON and OFF mode.
- Powered by a 1200mAh LI-ION (polymer battery).
- Maximum operating time 4 hours. Charging time 2.5 hours.
- Includes USB cable for charging the battery. Charging: Red LED. Battery charged: Green LED.
- Adjustable and detachable headband made of durable material for easy attachment to head or helmet.
- Adjustable light angle.

CODE CAT NO. 3-01-13-OS-103 PRO-LD103

LED HEADLAMP WITH LI-ION BATTERY AND MOTION SENSOR + MAGNET 300LM

















CODE CAT NO.
3-01-13-OS-104 PRO-LD104

- Flashlight equipped with COB LED strip (5W).
- Working brightness 300 lumens.
- Lamp body made of ABS, covered with thermoplastic rubber.
- Flashlight modes:
- right button: 30%/100%/off
- left button: motion detector activation 30%/100%/ off
- Powered by an 800 mAh lithium-ion battery.
- Charging time 2.5 hours.
- Operating time: 3 hours (100%), 4.5 hours (30%)
- Adjustable and detachable headband made of durable material for easy attachment to head or helmet.
- The flashlight can be detached from the headband and placed on a metal surface using built-in magnets.

# LED WORKSHOP LIGHTS

LED WORKSHOP LAMP













CODE CAT NO.
3-01-13-OS-001 PRO-LD001

- Modern portable lamp with a COB LED strip (3W) and a LED diode (3W).
- Operating brightness 220 lumens or 80 lumens.
- Lamp body made of durable ABS plastic, covered with TPR (thermoplastic rubber).
- Powered by AAA batteries (4 included).
- The handle comes with a magnet for easy attachment of the lamp to metal surfaces.
- Lower case with 360° vertical and horizontal adjustment.
- In the back of the casing there is a hook for hanging the lamp in any place.

# LED WORKSHOP LAMP



CODE CAT NO.
3-01-13-OS-002 PRO-LD002









- Modern portable lamp equipped with COB LED strip (3W) and LED diode (1W).
- The operating brightness is 220 lumens or 50 lumens.
- Lamp body made of durable ABS plastic, covered with TPR (thermoplastic rubber).
- Powered by AA batteries ( 3 pieces included).
- Universal design and movable handle for easy operation.
- In the lower part of the casing there is a hook for hanging the lamp in any place.



# LED WORKSHOP LAMP















- Modern portable lamp with COB LED strip (3W).
- Working brightness 250 lumens.
- Lamp body made of durable ABS plastic, lens made of polystyrene.
- Powered by AA batteries (3 included).
- The foot has a strong neodymium magnet for easy attachment of the lamp to metal surfaces.
- The lower part of the housing can be adjusted in 360°.

CODE	CAT NO.
3-01-13-OS-204	PRO-LD204

# LED WORKSHOP LAMP













- Modern portable lamp equipped with COB LED strip (3W).
- Working brightness 200 lumens.
- Lamp body made of durable ABS plastic, lens made of polystyrene.
- Powered by AA batteries (3 included).
- The casing has a strong neodymium magnet for easy attachment of the lamp to metal surfaces.
- The housing has a hook for easy hanging of the lamp in various situations.

CODE	CAT NO.
3-01-13-OS-205	PRO-LD205

# LED WORKSHOP LAMP















- Modern portable lamp equipped with COB LED strip (3W) and LED diode (1W).
- There are red LEDs built into the COB LED strip for use as an emergency light.
- Operating brightness 220 lumens or 60 lumens.
- Lamp body made of durable ABS plastic, covered with TPR (thermoplastic rubber).
- Powered by AA batteries (3 included).
- There is a strong neodymium magnet in the foot for easy attachment of the lamp to metal surfaces.
- The lower part of the housing can be adjusted in 360°.
- In the back of the casing there is a hook for hanging the lamp.

CODE	CAT NO.
3-01-13-OS-203	PRO-LD203

# LED WORKSHOP LAMP



















- The lamp is equipped with a COB LED strip (5W) and a LED diode (3W).
- Operating brightness 350 and 130 lumens.
- Lamp body made of ABS plastic. Protection class IP44.
- Trims made of TPR (damage-resistant thermoplastic rubber).
- Four light modes 100%/50%/TOP/Red emergency light.
- Powered by 4 x AAA batteries (included).
- In the back of the casing there is a hook for hanging the lamp in any place.
- The lamp's vertically movable foot features a rotating magnet for easy installation and operation.

CODE	CAT NO.
3-01-13-OS-210	PRO-LD210

# LED WORKSHOP LAMP

















- The lamp is equipped with a COB LED strip (3W) and 3 red LEDs. Working brightness 230 lumens.
- Lamp body made of ABS plastic, covered with thermoplastic rubber.
- Powered by a 3.7v, 1800 mAh lithium ion battery.
- In the back of the housing a button that is also an emergency light.
   There is a neodymium magnet in the footer and in the back of the case.
- On the top placed a steel hook that can be used to both hang or lean the lamp.
- Included are accessories for mains and car charging.

CODE	CAT NO.
3-01-13-OS-207	PRO-LD207

# LED WORKSHOP LAMP WITH BATTERY AND DIMMER 400LM

















- Flashlight equipped with COB LED strip (10W).
- Working brightness 400 lumens.
- Lamp body made of ABS plastic.
- Flashlight equipped with a dimmer to work in different lighting.
- Powered by a 2000Ah lithium-ion battery.
- Charging time 3 hours.
- Number of charges: 500.
- Operating time: 2 hours (100%)
- Magnetic foot adjustable in 360 degrees, USB cable included.

CODE	CAT NO.
3-01-13-OS-211	PRO-LD211



# LED FLASHLIGHTS

LED FLASHLIGHT













- Flashlight equipped with CREE LED strip (10W)
- Working brightness 450 lumens.
- Lamp body made of aluminum alloy.
- Five light modes 100%/75%/35%/strobe/SOS.
- Strobe and SOS function activated by a gentle press of a button.
- Powered by 4 x AAA batteries (included).
- Degree of protection IP65
- The movable lens allows to adjust the light beam.

CODE	CAT NO.
3-01-13-OS-208	PRO-LD208

# **LED FLASHLIGHT 100LM**











- Flashlight equipped with COB LED strip (2W).
- Working brightness 100 lumens.
- Lamp body made of aluminum.
- Powered by AAA batteries (3 included).
- Operating time: 7 hours.

CODE	CAT NO.
3-01-13-OS-006	PRO-LD006

# LED FLASHLIGHT PEN+2XMAGNETS 200LM















- Flashlight equipped with COB LED strip (3W).
- Working brightness 200 lumens.
- Lamp body made of aluminum.
- Powered by AAA batteries (3 included).
- Operating time: 7 hours (100%).
- Two magnets built into the case and handle.
- 180 degree adjustable handle.

CODE	CAT NO.
3-01-13-OS-007	PRO-LD007

LED FLASHLIGHT + ZOOM IP43 85LM













- Flashlight equipped with 5W LED strip.
- Working brightness 85 lumens.
- Lamp body made of aluminum.
- Powered by AA batteries (1 included).
- Operating time: 4 hours. Range: 50 m.
- Dust and water resistance: IP43.
- Lens with adjustable beam width "zoom".

CODE	CAT NO.
3-01-13-OS-008	PRO-LD008

# LED REFLECTORS

# PORTABLE LED SPOTLIGHT 10W









CABLE 3M

PLUG

RUBBER CABLE 3Gx1.0mm

- Die-cast aluminum body. Tempered glass reflector glass.
- Light source: LED CHIP SMD2835. Luminous flux: >75 lm/W. Light color up to 6500K.
- Power: 10W. Power supply: 220 240V, 60Hz/ 50Hz.
- Degree of protection: IP 65.
- Cable: H05RN-F 3x1mm2. Cable length: 3 m.
- Portable, foldable aluminum stand with adjustable tilt angle.

CODE	CAT NO.
3-01-13-OS-501	PRO-LD501

# **PORTABLE LED SPOTLIGHT 10W**











ATERPROOF

RUBBER

- Die-cast aluminum body.
- Tempered reflector glass.
- Light source: LED CHIP SMD2835. Luminous flux: >70 lm/W. Light color up to 6500K.
- Power: 10W. Power supply: 220 240V, 60Hz/ 50Hz.
- Degree of protection: IP 65.
- Cable: H05RN-F 3x1mm2. Cable length: 1.5 m.
- Portable, foldable aluminum stand with adjustable tilt angle.

CODE	CAT NO.
3-01-13-OS-504	PRO-LD504



LED SPOTLIGHT IP54 30W 2400LM WITH BT LOUDSPEAKR AND 230V SOCKET



















- Portable LED light is a functional device used in the workshop, at the construction site and for various outdoor and indoor works.
- It is resistant to excessive shocks and, thanks to its IP54 rating, resistant to the weather and dust associated with construction and workshop.
- The advantage of the product is its versatility, you can freely move and position it, directing the light beam in any direction.
- Additionally, the headlight is equipped with a 230V outlet and Bluetooth speaker.
- Power: 30 WCable: 3m

CODE	CAT NO.
3-01-13-OS-607	PRO-LD607

LED SPOTLIGHT IP54 2X20W 3200LM









ATERPROOF ( PLUG F

RUBBER CABLE H05RN-F 3Gx1.5





- Portable LED light is a functional device used in the workshop, at the construction site and for various outdoor and indoor works.
- It is resistant to excessive shocks and thanks to its IP54 rating it is resistant to weather and dust present at construction sites and in workshops.
- The advantage of the product is its versatility, you can freely move and position it, directing the light beam in any direction.
- Additionally, the spotlight is equipped with 230V socket.
- Power: 2 x 20 W
- 3200 lm
- Cable: 3m

CODE	CAT NO.
3-01-13-OS-611	PRO-LD611

# LED SPOTLIGHT IP65 20W 1600LM OS-IP65-RL20N















- Portable LED light is a functional device used in the workshop, at the construction site and for various outdoor and indoor works.
- It is resistant to excessive shocks and, thanks to its IP65 rating, resistant to the weather and dust associated with construction and workshop.
- The advantage of the product is its versatility, it can be freely carried or mounted on a tripod, directing the light beam in any direction.
- Power: 20 W


CODE	CAT NO.
3-01-13-OS-601	PRO-LD601



IP65







- It is resistant to excessive shocks and, thanks to its IP65 rating, resistant to the weather and dust associated with construction and workshop.
- The advantage of the product is its versatility, it can be moved and set up freely, direction the light beam in any direction

CODE	CAT NO.	TYPE
3-01-13-OS-702	PRO-LD702	20W>80lm/W
3-01-13-OS-703	PRO-LD703	30W>80lm/W









WATERPROOF PLUG





- Portable LED light is a functional device used in the workshop, at the construction site and for various outdoor and indoor works.
- It is resistant to excessive shocks and, thanks to its IP65 rating, resistant to the weather and dust associated with construction and workshop.
- The advantage of the product is its versatility, it can be freely carried or mounted on a tripod, directing the light beam in any direction.
- Power: 50 W
- 4000 lm

CODE	CAT NO.
3-01-13-OS-604	PRO-LD604

# LED LIGHTS WITH TRIPOD IP65 100W >80LM/W, 30W >80LM/W, 50W >80LM/W

80lm/W

IP65

VDE PLUG



- Portable LED light is a functional device used in the workshop, at the construction site and for various outdoor and indoor works.
- It is resistant to excessive shocks and, thanks to its IP65 rating, resistant to the weather and dust associated with construction and workshop.
- The advantage of the product is its versatility, you can freely move and position it, directing the light beam in any direction.

CODE	CAT NO.	TYPE
3-01-13-OS-710	PRO-LD710	100W>80lm/W
3-01-13-OS-711	PRO-LD711	30W>80lm/W
3-01-13-OS-712	PRO-I D712	50W>80lm/W



# LED SPOTLIGHT WITH TRIPOD IP65 2X50W >80LM/W, 2X100W >80LM/W LED SPOTLIGHT WITH TRIPOD IN COVER IP65

80lm/W

IP65

VDE PLUG



- Portable LED light is a functional device used in the workshop, at the construction site and for various outdoor and indoor works.
- It is resistant to excessive shocks and, thanks to its IP65 rating, resistant to the weather and dust associated with construction and workshop.
- The advantage of the product is its versatility, you can freely move and position it, directing the light beam in any direction.

CODE	CAT NO.	TYPE
3-01-13-OS-714	PRO-LD714	2x50W >80lm/W
3-01-13-OS-716	PRO-LD716	2x100W >80lm/W





- Portable LED light is a functional device used in the workshop, at the construction site and for various outdoor and indoor works.
- It can withstand excessive shock and is IP65 rated to withstand the weather and dust associated with construction and workshop conditions.
- The advantage of the product is its versatility, you can freely move and position it, directing the light beam in any direction.

CODE	CAT NO.	TYPE
3-01-13-OS-713	PRO-LD713	2x50W >80lm/W + dust cover
3-01-13-OS-715	PRO-LD715	2x100W >80lm/W + cover

# LED SPOTLIGHT CASE WITH TRIPOD

600D POLYEST ER

- Made of durable polyester.
- Includes a set of headlights: 2 led lamps and tripod.
- Additionally equipped with reflective strips to improve user safety.
- Dimensions: 630 x 270 x 100 mm.



CODE	CAT NO.
3-01-13-OS-900	PRO-LD900

# TECHNICAL CHEMICAL PREPARATIONS





# TECHNICAL CHEMICAL PREPARATIONS

UNIVERSAL RUST REMOVER 400ML







**RUST REMOVING PREPARATION** WITH MOLYBDENU M DISULFIDE MOS2











Effectively removes oxides formed on the metal surface. Makes it easier to clean rusted parts and harder for rust to form again.

- dissolves rust and loosens the most stubborn joints
- eliminates squeaks and creaks by lubricating sliding surfaces
- repels moisture and water, anti-corrosive

- disconnection of old corroded screw
- loosening of rusted pins, levers, hinges, tools, pins, etc.
- lubrication of locks, smaller bearings, axles, levers, cables, handles, etc.
- prophylaxis for metal parts against corrosion and freezing

CODE	CAT NO.
3-01-90-CH-015	PRO-CH015



Rust remover and release agent for seized and corroded joints. Thanks to the molybdenum disulfide, the preparation creates a lubricating layer which prevents squeaking.

- rust remover and release agent to remove stuck connections
- has excellent rust removal and penetration properties
- protects against corrosion
- molybdenum disulfide for protection against reseizing

CODE	CAT NO.	CAPACITY
3-01-90-CH-011	PRO-CH011 20	0 ml
3-01-90-CH-001	PRO-CH001	400 ml

# WITH RUST OFF FREEZING EFFECT









### **GREASE FOR ROPES** AND CHAINS











# Releasing rusted and seized parts

- Releases corroded connections. Upon application, the product causes cooling of the workpiece down to -40°C.
- Releases all types of threaded connections, hinges and guides, can be used in the automotive industry, metallurgy, mining.
- Does not contain silicone or acids, and does not react with rubber

# APRO

Grease for ropes and chains is an adhesive lubricant that provides effective and long-lasting lubrication and maintenance of ropes and chains. The product is intended for lubrication and maintenance of metal ropes, winches, elevators, conveyors, hoists, ropes for lifting loads, all kinds of transport or drive chains, drive transmission elements, lubrication of forklift chains.



CAT NO. PRO-CH013

### CAT NO. CODE 3-01-90-CH-010 PRO-CH010

# DRY GREASE **TEFLON**













After application, it forms an adherent slip film - a dry film that does not accept dirt or dust. It is used as a release agent to prevent sticking.

- reduces friction and wear on moving parts
- prevents sticking, forms a permanent sliding layer
- contains no silicone
- protects against moisture

- automotive workshops: locks, hinges, chains, lubrication of friction parts
- woodworking industry: for covering sliding tables
- plastics and textile industry



**DRILLING AND** TAPPING OIL

3-01-90-CH-013

CODE









Drilling and tapping oil is a high performance coolant and lubricant for all machining operations where high loads and stresses are generated. Drilling and cutting oil spray extends the life of tools used in metalworking.

# Application:

- preparation for machining
- working temperature range from -35°C to +205°C
- characteristics for working at higher speeds, reducing friction and lowering temperatures

CODE	CAT NO.
3-01-90-CH-019	PRO-CH019



## SILICONE SPRAY







All-purpose, long-lasting product for preserving and protecting metal, rubber and plastic products. Antistatic and dust-reducing agent. Application:

Application:
This is an excellent all-purpose silicone lubricant that eliminates friction and material drag. The agent is used in many areas of industry, wherever there are problems with adhesion or high friction. It adds gloss to finished rubber products and ensures that the material does not crumble, stick or freeze.





# ALUZINC PREPARATION

PRO









Aluzinc Preparation is a fast drying product providing excellent protection against corrosion to all metal parts and structures.

- Protection of metal surfaces against
- repair of protective coating on hot-dip galvanized components
- repair of zinc coating after treatment or welding
- repair of cut and welded parts.

CODE	CAT NO.
2 01 00 CH 000	DBO CHOOS

### CAT NO. CODE 3-01-90-CH-004 PRO-CH004

### WELDING ANTI-SCRATCH PREPARATION













- the preparation protects welded surfaces and welding nozzles against welding spatters adherence
- adheres easily to metal surfaces, forming a durable layer that protects the metal from oxidation and corrosion
- Application:
- when welding with automatic and semi-automatic devices
- to protect welded parts and surfaces
- for the protection of nozzles and torches in electrode and shielded gas welding

CODE	CAT NO.
3-01-90-CH-016	PRO-CH016

# **PENETRATING** GREASE













- forms a fade-resistant film that withstands high pressures, rotations and strokes
- the product has lubricating properties without the necessity to disassemble the components resistant to temperatures ranging from -35 °C to +180 °C, briefly up to +200 °C
- contains no silicone, resins or acids

# **MULTIFUNCTIONAL** PREPARATION PRO40











- lubrication, drying, cleaning, dissolving and maintenance.
- does not contain silicone or mineral oils, neutral for varnishes.
- thanks to its adhesive properties, it dries and protects the electrical system from moisture.
- thanks to its capillary properties, it penetrates the smallest gaps and displaces moisture and forming a waterproof protective layer.
- is widely used in the automotive, metal, precision mechanics and energy industries.

CODE	CAT NO.	CAPACITY
3-01-90-CH-012	PRO-CH012	200 ml
3-01-90-CH-005	PRO-CH013	400 ml

# **CONTACT SPRAY 400ML**











A high quality formulation specially developed for cleaning electrical contacts. It is used to remove oxides, sulfides and other contaminants and has penetrating and dissolving properties. Does not conduct electricity, does not cause corrosion and does not leave any residues. Prevents re-oxidation of contaminant deposition.

- removes contaminants such as oxides sulphides, oils and greases
- improves contact conductivity
- does not cause metal rusting
- leaves no residue
- prevents re-oxidation and deposition of contaminants
- temperature range: 25 C to + 70 C

CODE	CAT NO.
2.04.00.011.040	DDO CHO40





# **TECHNICAL CHEMICAL PREPARATIONS**

UNIVERSAL REMOVER FOR BRAKES WITH ACETONE





Application:

- contains acetone

- evaporates instantly



- effectively cleans and degreases elements from all greasy dirt

effectively removes wax, oil, grease and glue residues

Application:
The product effectively cleans and degreases elements from any greasy dirt, effectively removes wax, oil, grease, temporary protection agents, glue residues, while rapidly evaporating. It effectively cleans brake and clutch system components, removes protective coatings from brake discs, anticorrosion coatings from injection moulds, removes soot and persistent dirt.





# UNIVERSAL REMOVER FOR BRAKES WITHOUT











- does not contain acetone
- neutral to rubber, plastics and painted surfaces
- effectively cleans and degreases elements from all greasy dirt
- effectively removes waxes, oils, greases, temporary protection agents and glue residues

Application:
The product effectively cleans and degreases elements from any greasy dirt.
Effectively removes waxes, oils, greases, temporary protection agents, adhesive residues. Does not contain acetone - neutral to rubber, plastics and painted surfaces. stubborn dirt.

CODE	CAT NO.
3-01-90-CH-003	PRO-CH003



PRO-CH002

# **MARKING PAINT 500ML**


3-01-90-CH-002







CODE	CAT NO.	COLOR
3-01-90-CH-022	PRO-CH022	yellow
3-01-90-CH-021	PRO-CH021	green
3-01-90-CH-020	PRO-CH020	orange





111

- Quick drying
- Permanent and highly visible markings
- Good adhesion to most surfaces
- Does not contain heavy metals
- Reverse dosing valve

# Application:

- Color markings on asphalt, concrete and flooring
- For marking in forestry and woodworking industries
- For marking measurement points in construction














Ask your Customer Assistant about the possibility of a makeover in your showroom.



metamorfoza.firma-pro.pl



RACK SPIRIT LEVELS PRO800



RACK 60 CM SCREEDING LEVELS





RACK BUILDER'S SQUARES AND ANGLE BARS



RACK SCREEDING LEVELS



RACK MEASURING TOOLS





RACK LEVELING SYSTEMS



RACK WRENCHES



RACK CUTTING TOOLS



RACK PLIERS AND WRENCHES



RACK JOINING TOOLS



RACK SCREWDRIVERS





RACK HAMMERS



RACK POWER TOOL ACCESSORIES



RACK DRILL BITS



RACK LIGHTING



RACK WOOD DRILL BITS AND CLAMPS



RACK H&S



RACK FLOATS AND TROWELS



RACK STIRRERS



RACK TROWELS



RACK TOOLS FOR ELECTRICIANS



RACK DISCS



RACK TOOLS FOR PLUMBERS





# LASER SHOWCASECABINETS



# **CABINETS**

CABINET LASERS

CABINET LIGHTING





# PYRAMIDS FOR SPIRIT LEVELS

**PYRAMID** PRO600

3-01-11-RE-00P

**PYRAMID** PRO600 3-01-11-RE-05P

PYRAMID PRO600 3-01-11-RE-05C

PYRAMID PRO600 3-01-11-RE-01P









PYRAMID PRO800 3-01-11-RE-02P PYRAMID PRO800 3-01-11-RE-04P PYRAMID PRO800 3-01-11-RE-12P







**PYRAMID** PRO1000 3-01-11-RE-13P



PYRAMID PRO900 3-01-11-RE-09P









# SHELVES & STANDS

RACK IRRIGATION



STAND LEVELING SYSTEMS







RACK SHOVELS

RACK AXES





